



14.4m — 44.7m

メインブーム【特殊伸縮】

TA1性能

カウンターウエイト 83t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	119.0	70.0	70.0	60.0	35.0	
8.0	105.1	70.0	70.0	60.0	35.0	32.0
9.0	93.8	70.0	70.0	60.0	35.0	32.0
10.0	84.4	70.0	70.0	60.0	35.0	32.0
11.0	76.5	70.0	70.0	60.0	35.0	32.0
12.0	69.8	70.0	70.0	60.0	35.0	32.0
14.0		60.3	60.9	53.8	35.0	32.0
16.0		51.2	51.9	47.4	35.0	28.7
18.0			44.4	42.1	32.1	25.3
20.0			38.5	37.7	28.7	22.5
22.0			33.7	34.0	25.7	20.2
24.0				30.1	23.2	18.2
26.0				26.8	21.0	16.5
28.0				23.9	19.1	15.0
30.0					17.5	13.7
32.0					16.1	12.6
34.0					14.8	11.6
36.0					13.6	10.7
38.0						9.9
40.0						9.2
42.0						8.6
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TA2性能

カウンターウエイト 83t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	119.0	70.0	70.0	60.0	35.0	
8.0	105.1	70.0	70.0	60.0	35.0	32.0
9.0	93.8	70.0	70.0	60.0	35.0	32.0
10.0	84.4	70.0	70.0	60.0	35.0	32.0
11.0	76.5	70.0	70.0	60.0	35.0	32.0
12.0	69.8	70.0	70.0	60.0	35.0	32.0
14.0		60.3	60.9	53.8	35.0	32.0
16.0		51.2	51.9	47.4	35.0	28.7
18.0			44.4	42.1	32.1	25.3
20.0			38.5	37.7	28.7	22.5
22.0			33.7	34.0	25.7	20.2
24.0				30.1	23.2	18.2
26.0				26.8	21.0	16.5
28.0				23.9	19.1	15.0
30.0					17.5	13.7
32.0					16.1	12.6
34.0					14.8	11.6
36.0					13.6	10.7
38.0						9.9
40.0						9.2
42.0						8.6
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TB1性能

カウンターウエイト 71t アウトリガー張出 9.4m(全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	115.2	70.0	70.0	60.0	35.0	
8.0	101.7	70.0	70.0	60.0	35.0	32.0
9.0	90.7	70.0	70.0	60.0	35.0	32.0
10.0	81.6	70.0	70.0	60.0	35.0	32.0
11.0	73.9	70.0	70.0	60.0	35.0	32.0
12.0	67.1	68.8	69.1	60.0	35.0	32.0
14.0		56.4	56.9	53.8	35.0	32.0
16.0		47.3	47.7	47.4	35.0	28.7
18.0			40.7	41.5	32.1	25.3
20.0			35.2	35.9	28.7	22.5
22.0			30.8	31.3	25.7	20.2
24.0				27.6	23.2	18.2
26.0				24.4	21.0	16.5
28.0				21.7	19.1	15.0
30.0					17.5	13.7
32.0					16.1	12.6
34.0					14.8	11.6
36.0					13.6	10.7
38.0						9.9
40.0						9.2
42.0						8.6
危険角度(°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量(t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TB2性能

カウンターウエイト 71t アウトリガー張出 8.4m(側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	115.2	70.0	70.0	60.0	35.0	
8.0	101.7	70.0	70.0	60.0	35.0	32.0
9.0	90.7	70.0	70.0	60.0	35.0	32.0
10.0	81.6	70.0	70.0	60.0	35.0	32.0
11.0	73.9	70.0	70.0	60.0	35.0	32.0
12.0	67.1	68.8	69.1	60.0	35.0	32.0
14.0		56.4	56.9	53.8	35.0	32.0
16.0		47.3	47.7	47.4	35.0	28.7
18.0			40.7	41.5	32.1	25.3
20.0			35.2	35.9	28.7	22.5
22.0			30.8	31.3	25.7	20.2
24.0				27.6	23.2	18.2
26.0				24.4	21.0	16.5
28.0				21.7	19.1	15.0
30.0					17.5	13.7
32.0					16.1	12.6
34.0					14.8	11.6
36.0					13.6	10.7
38.0						9.9
40.0						9.2
42.0						8.6
危険角度(°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量(t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TB3性能

カウンターウエイト 71t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	115.2	70.0	70.0	60.0	35.0	
8.0	101.7	70.0	70.0	60.0	35.0	32.0
9.0	90.7	70.0	70.0	60.0	35.0	32.0
10.0	81.6	70.0	70.0	60.0	35.0	32.0
11.0	73.9	70.0	70.0	60.0	35.0	32.0
12.0	67.1	68.8	69.1	60.0	35.0	32.0
14.0		53.6	54.3	53.8	35.0	32.0
16.0		43.3	43.9	44.5	35.0	28.7
18.0			36.5	37.0	32.1	25.3
20.0			30.9	31.4	28.7	22.5
22.0			26.6	27.0	25.7	20.2
24.0				23.5	23.2	18.2
26.0				20.6	20.9	16.5
28.0				18.2	18.5	15.0
30.0					16.4	13.7
32.0					14.7	12.6
34.0					13.2	11.6
36.0					11.9	10.7
38.0						9.9
40.0						9.2
42.0						8.6
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TC1性能

カウンターウエイト 59t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	111.4	70.0	70.0	60.0	35.0	
8.0	98.3	70.0	70.0	60.0	35.0	32.0
9.0	87.6	70.0	70.0	60.0	35.0	32.0
10.0	78.3	70.0	70.0	60.0	35.0	32.0
11.0	69.3	70.0	70.0	60.0	35.0	32.0
12.0	61.9	63.6	64.4	60.0	35.0	32.0
14.0		52.0	52.8	53.4	35.0	32.0
16.0		43.4	44.2	44.7	35.0	28.7
18.0			37.5	38.1	32.1	25.3
20.0			32.3	32.8	28.7	22.5
22.0			28.1	28.5	25.7	20.2
24.0				25.0	23.2	18.2
26.0				22.0	21.0	16.5
28.0				19.6	19.1	15.0
30.0					17.5	13.7
32.0					15.8	12.6
34.0					14.2	11.6
36.0					12.7	10.7
38.0						9.9
40.0						9.2
42.0						8.6
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TC2性能

カウンターウエイト 59t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	111.4	70.0	70.0	60.0	35.0	
8.0	98.3	70.0	70.0	60.0	35.0	32.0
9.0	87.6	70.0	70.0	60.0	35.0	32.0
10.0	78.3	70.0	70.0	60.0	35.0	32.0
11.0	69.3	70.0	70.0	60.0	35.0	32.0
12.0	61.9	63.6	64.4	60.0	35.0	32.0
14.0		52.0	52.8	53.4	35.0	32.0
16.0		43.4	44.2	44.7	35.0	28.7
18.0			37.5	38.1	32.1	25.3
20.0			32.3	32.8	28.7	22.5
22.0			28.1	28.5	25.7	20.2
24.0				25.0	23.2	18.2
26.0				21.9	21.0	16.5
28.0				19.3	19.1	15.0
30.0					17.4	13.7
32.0					15.5	12.6
34.0					13.9	11.6
36.0					12.5	10.7
38.0						9.9
40.0						9.2
42.0						8.6
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TC3性能

カウンターウエイト 59t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	111.4	70.0	70.0	60.0	35.0	
8.0	98.3	70.0	70.0	60.0	35.0	32.0
9.0	87.6	70.0	70.0	60.0	35.0	32.0
10.0	78.3	70.0	70.0	60.0	35.0	32.0
11.0	68.9	70.0	70.0	60.0	35.0	32.0
12.0	59.3	60.9	61.7	60.0	35.0	32.0
14.0		47.2	47.9	48.5	35.0	32.0
16.0		37.9	38.6	39.1	35.0	28.7
18.0			31.9	32.4	32.1	25.3
20.0			26.9	27.3	27.7	22.5
22.0			23.0	23.4	23.8	20.2
24.0				20.2	20.6	18.2
26.0				17.6	18.0	16.5
28.0				15.5	15.8	15.0
30.0					13.9	13.7
32.0					12.4	12.4
34.0					11.0	11.1
36.0					9.8	9.9
38.0						8.8
40.0						7.9
42.0						7.1
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TD1性能

カウンターウエイト 41t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	105.6	70.0	70.0	60.0	35.0	
8.0	91.4	70.0	70.0	60.0	35.0	32.0
9.0	78.7	70.0	70.0	60.0	35.0	32.0
10.0	68.6	70.0	70.0	60.0	35.0	32.0
11.0	60.6	62.4	63.2	60.0	35.0	32.0
12.0	53.9	55.7	56.5	57.2	35.0	32.0
14.0		45.2	46.0	46.7	35.0	32.0
16.0		37.5	38.3	38.9	35.0	28.7
18.0			32.4	33.0	32.1	25.3
20.0			27.6	28.2	28.7	22.5
22.0			23.8	24.4	24.8	20.2
24.0				21.2	21.6	18.2
26.0				18.5	18.9	16.5
28.0				16.3	16.6	15.0
30.0					14.6	13.7
32.0					12.9	12.6
34.0					11.4	11.5
36.0					10.1	10.1
38.0						9.0
40.0						7.9
42.0						7.0
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TD2性能

カウンターウエイト 41t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	105.6	70.0	70.0	60.0	35.0	
8.0	91.4	70.0	70.0	60.0	35.0	32.0
9.0	78.7	70.0	70.0	60.0	35.0	32.0
10.0	68.6	70.0	70.0	60.0	35.0	32.0
11.0	60.6	62.4	63.2	60.0	35.0	32.0
12.0	53.9	55.7	56.5	57.2	35.0	32.0
14.0		45.2	46.0	46.7	35.0	32.0
16.0		37.5	38.3	38.9	35.0	28.7
18.0			31.3	31.9	32.1	25.3
20.0			26.1	26.7	27.1	22.5
22.0			22.1	22.6	23.0	20.2
24.0				19.4	19.8	18.2
26.0				16.8	17.1	16.5
28.0				14.6	14.9	15.0
30.0					13.0	13.1
32.0					11.5	11.5
34.0					10.1	10.2
36.0					8.9	9.0
38.0						7.9
40.0						7.0
42.0						6.0
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TD3性能

カウンターウエイト 41t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	105.6	70.0	70.0	60.0	35.0	
8.0	91.4	70.0	70.0	60.0	35.0	32.0
9.0	78.7	70.0	70.0	60.0	35.0	32.0
10.0	65.8	67.7	68.6	60.0	35.0	32.0
11.0	55.3	57.1	57.9	58.6	35.0	32.0
12.0	47.4	49.0	49.8	50.4	35.0	32.0
14.0		37.6	38.3	38.9	35.0	32.0
16.0		29.9	30.5	31.1	31.5	28.7
18.0			25.0	25.5	25.9	25.3
20.0			20.8	21.3	21.7	21.8
22.0			17.5	18.0	18.3	18.4
24.0				15.3	15.7	15.8
26.0				13.2	13.5	13.6
28.0				11.4	11.7	11.8
30.0					10.2	10.2
32.0					8.9	8.9
34.0					7.7	7.8
36.0					6.8	6.8
38.0						5.9
40.0						5.2
42.0						4.3
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TD4性能

カウンターウエイト 41t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	120.0	70.0	70.0	60.0		
7.0	105.6	70.0	70.0	60.0	35.0	
8.0	81.3	70.0	70.0	60.0	35.0	32.0
9.0	65.4	67.3	68.1	60.0	35.0	32.0
10.0	54.1	55.9	56.7	57.4	35.0	32.0
11.0	45.8	47.4	48.2	48.9	35.0	32.0
12.0	39.4	40.9	41.6	42.3	35.0	32.0
14.0		31.5	32.2	32.7	33.2	32.0
16.0		25.0	25.7	26.2	26.7	26.8
18.0			21.0	21.5	21.9	22.0
20.0			17.4	17.8	18.2	18.3
22.0			14.6	15.0	15.4	15.5
24.0				12.7	13.1	13.1
26.0				10.8	11.2	11.2
28.0				9.3	9.6	9.6
30.0					8.2	8.3
32.0					7.1	7.1
34.0					6.1	6.1
36.0					5.2	5.3
38.0						4.3
40.0						3.4
危険角度 (°)	—	—	—	—	—	21
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TE1性能

カウンターウエイト 31t アウトリガー張出 9.4m(全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	117.2	70.0	70.0	60.0		
7.0	99.5	70.0	70.0	60.0	35.0	
8.0	84.0	70.0	70.0	60.0	35.0	32.0
9.0	72.2	70.0	70.0	60.0	35.0	32.0
10.0	62.9	64.8	65.6	60.0	35.0	32.0
11.0	55.3	57.2	58.0	58.7	35.0	32.0
12.0	49.1	50.9	51.7	52.4	35.0	32.0
14.0		41.1	42.0	42.6	35.0	32.0
16.0		33.9	34.7	35.4	35.0	28.7
18.0			29.2	29.8	30.4	25.3
20.0			24.8	25.4	25.9	22.5
22.0			21.3	21.8	22.3	20.2
24.0				18.8	19.3	18.2
26.0				16.2	16.6	16.5
28.0				14.1	14.4	14.5
30.0					12.5	12.6
32.0					11.0	11.0
34.0					9.6	9.7
36.0					8.5	8.5
38.0						7.5
40.0						6.4
42.0						5.5
危険角度(°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量(t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TE2性能

カウンターウエイト 31t アウトリガー張出 8.4m(側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	117.2	70.0	70.0	60.0		
7.0	99.5	70.0	70.0	60.0	35.0	
8.0	84.0	70.0	70.0	60.0	35.0	32.0
9.0	72.2	70.0	70.0	60.0	35.0	32.0
10.0	62.9	64.8	65.6	60.0	35.0	32.0
11.0	55.3	57.2	58.0	58.7	35.0	32.0
12.0	49.1	50.9	51.7	52.4	35.0	32.0
14.0		40.7	41.5	42.2	35.0	32.0
16.0		32.0	32.8	33.4	33.9	28.7
18.0			26.6	27.1	27.6	25.3
20.0			22.0	22.5	23.0	22.5
22.0			18.4	18.9	19.3	19.4
24.0				16.1	16.4	16.5
26.0				13.7	14.1	14.2
28.0				11.8	12.1	12.2
30.0					10.5	10.6
32.0					9.1	9.2
34.0					7.9	8.0
36.0					6.8	6.8
38.0						5.7
40.0						4.7
42.0						3.9
危険角度(°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量(t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TE3性能

カウンターウエイト 31t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	117.2	70.0	70.0	60.0		
7.0	99.5	70.0	70.0	60.0	35.0	
8.0	84.0	70.0	70.0	60.0	35.0	32.0
9.0	69.4	70.0	70.0	60.0	35.0	32.0
10.0	56.6	58.5	59.4	60.0	35.0	32.0
11.0	47.4	49.1	49.9	50.6	35.0	32.0
12.0	40.4	42.0	42.8	43.4	35.0	32.0
14.0		31.9	32.6	33.2	33.7	32.0
16.0		25.1	25.8	26.4	26.8	26.9
18.0			20.9	21.4	21.9	21.9
20.0			17.2	17.7	18.1	18.2
22.0			14.4	14.8	15.2	15.3
24.0				12.5	12.8	12.9
26.0				10.6	10.9	11.0
28.0				9.1	9.3	9.4
30.0					8.0	8.0
32.0					6.8	6.9
34.0					5.8	5.9
36.0					4.9	4.9
38.0						3.9
40.0						3.1
危険角度 (°)	—	—	—	—	—	21
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TE4性能

カウンターウエイト 31t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	117.2	70.0	70.0	60.0		
7.0	91.2	70.0	70.0	60.0	35.0	
8.0	69.9	70.0	70.0	60.0	35.0	32.0
9.0	55.9	57.8	58.7	59.4	35.0	32.0
10.0	46.0	47.8	48.6	49.3	35.0	32.0
11.0	38.7	40.4	41.2	41.8	35.0	32.0
12.0	33.1	34.7	35.4	36.0	35.0	32.0
14.0		26.4	27.1	27.7	28.2	28.3
16.0		20.8	21.4	21.9	22.4	22.5
18.0			17.3	17.8	18.2	18.3
20.0			14.1	14.6	15.0	15.1
22.0			11.7	12.1	12.5	12.5
24.0				10.1	10.4	10.5
26.0				8.4	8.8	8.8
28.0				7.1	7.4	7.4
30.0					6.2	6.3
32.0					5.2	5.2
34.0					4.0	4.1
36.0					3.0	3.1
危険角度 (°)	—	—	—	—	19	33
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TF1性能

カウンターウエイト 21t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	110.7	70.0	70.0	60.0		
7.0	91.1	70.0	70.0	60.0	35.0	
8.0	76.7	70.0	70.0	60.0	35.0	32.0
9.0	65.7	67.7	68.6	60.0	35.0	32.0
10.0	57.1	59.0	59.8	60.0	35.0	32.0
11.0	50.1	51.9	52.8	53.5	35.0	32.0
12.0	44.3	46.1	46.9	47.7	35.0	32.0
14.0		37.1	37.9	38.6	35.0	32.0
16.0		30.4	31.2	31.9	32.4	28.7
18.0			25.9	26.5	27.0	25.3
20.0			21.2	21.7	22.2	22.3
22.0			17.7	18.1	18.6	18.7
24.0				15.3	15.7	15.8
26.0				13.0	13.4	13.4
28.0				11.1	11.4	11.5
30.0					9.8	9.9
32.0					8.4	8.5
34.0					7.2	7.3
36.0					6.0	6.1
38.0						5.0
40.0						4.0
42.0						3.2
危険角度 (°)	—	—	—	—	—	—
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TF2性能

カウンターウエイト 21t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	110.7	70.0	70.0	60.0		
7.0	91.1	70.0	70.0	60.0	35.0	
8.0	76.7	70.0	70.0	60.0	35.0	32.0
9.0	65.7	67.7	68.6	60.0	35.0	32.0
10.0	54.1	59.0	59.8	60.0	35.0	32.0
11.0	50.1	51.9	52.8	53.5	35.0	32.0
12.0	43.6	45.4	46.3	47.1	35.0	32.0
14.0		34.0	34.8	35.5	35.0	32.0
16.0		26.4	27.2	27.8	28.3	28.5
18.0			21.8	22.4	22.9	23.0
20.0			17.8	18.3	18.8	18.9
22.0			14.8	15.2	15.6	15.7
24.0				12.7	13.1	13.2
26.0				10.7	11.1	11.2
28.0				9.1	9.4	9.5
30.0					7.9	8.0
32.0					6.6	6.7
34.0					5.3	5.4
36.0					4.2	4.3
38.0						3.3
危険角度 (°)	—	—	—	—	—	27
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TF3性能

カウンターウエイト 21t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	110.7	70.0	70.0	60.0		
7.0	91.1	70.0	70.0	60.0	35.0	
8.0	74.6	70.0	70.0	60.0	35.0	32.0
9.0	58.4	60.5	61.4	60.0	35.0	32.0
10.0	47.4	49.3	50.2	50.9	35.0	32.0
11.0	39.4	41.2	42.0	42.7	35.0	32.0
12.0	33.4	35.0	35.8	36.4	35.0	32.0
14.0		26.3	27.0	27.6	28.1	28.2
16.0		20.4	21.1	21.6	22.1	22.2
18.0			16.8	17.4	17.8	17.9
20.0			13.7	14.1	14.5	14.6
22.0			11.2	11.6	12.0	12.1
24.0				9.6	10.0	10.1
26.0				8.0	8.3	8.4
28.0				6.6	6.9	7.0
30.0					5.8	5.8
32.0					4.6	4.7
34.0					3.5	3.6
危険角度 (°)	—	—	—	—	27	37
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TF4性能

カウンターウエイト 21t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	108.3	70.0	70.0	60.0		
7.0	76.8	70.0	70.0	60.0	35.0	
8.0	58.5	60.6	61.5	60.0	35.0	32.0
9.0	46.5	48.4	49.2	50.0	35.0	32.0
10.0	38.0	39.8	40.6	41.3	35.0	32.0
11.0	31.8	33.4	34.2	34.8	35.0	32.0
12.0	26.9	28.5	29.2	29.8	30.3	30.5
14.0		21.4	22.0	22.6	23.1	23.2
16.0		16.5	17.1	17.7	18.1	18.2
18.0			13.6	14.1	14.5	14.6
20.0			10.9	11.3	11.7	11.8
22.0			8.8	9.2	9.6	9.6
24.0				7.5	7.8	7.9
26.0				6.1	6.4	6.4
28.0				4.7	5.1	5.2
30.0					3.8	3.9
危険角度 (°)	—	—	—	—	38	45
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TF5性能

カウンターウエイト 21t アウトリガー張出 5.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	111.8	70.0	70.0	60.0		
6.0	74.8	70.0	70.0	60.0		
7.0	54.9	56.9	57.7	58.5	35.0	
8.0	42.6	44.4	45.1	45.8	35.0	32.0
9.0	34.2	35.8	36.5	37.2	35.0	32.0
10.0	28.1	29.6	30.3	30.9	31.4	31.5
11.0	23.4	24.9	25.6	26.1	26.6	26.7
12.0	19.8	21.2	21.9	22.4	22.9	23.0
14.0		15.8	16.4	16.9	17.4	17.5
16.0		12.0	12.6	13.1	13.5	13.6
18.0			9.8	10.3	10.7	10.8
20.0			7.7	8.1	8.5	8.6
22.0			6.1	6.4	6.8	6.9
24.0				5.1	5.4	5.5
26.0				3.8	4.2	4.3
28.0						3.1
危険角度 (°)	—	—	—	30	47	49
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TG1性能

カウンターウエイト 11t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	100.8	70.0	70.0	60.0		
7.0	82.7	70.0	70.0	60.0	35.0	
8.0	69.4	70.0	70.0	60.0	35.0	32.0
9.0	59.3	61.2	62.1	60.0	35.0	32.0
10.0	51.3	53.2	54.1	54.8	35.0	32.0
11.0	44.9	46.7	47.6	48.3	35.0	32.0
12.0	39.6	41.3	42.2	42.9	35.0	32.0
14.0		33.0	33.8	34.5	35.0	32.0
16.0		25.3	26.1	26.7	27.3	27.4
18.0			20.6	21.2	21.7	21.9
20.0			16.7	17.2	17.7	17.8
22.0			13.7	14.1	14.6	14.7
24.0				11.7	12.1	12.2
26.0				9.7	10.1	10.2
28.0				8.1	8.4	8.5
30.0					7.0	7.1
32.0					5.6	5.7
34.0					4.4	4.4
36.0					3.3	3.4
危険角度 (°)	—	—	—	—	15	33
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TG2性能

カウンターウエイト 11t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	100.8	70.0	70.0	60.0		
7.0	82.7	70.0	70.0	60.0	35.0	
8.0	69.4	70.0	70.0	60.0	35.0	32.0
9.0	59.3	61.2	62.1	60.0	35.0	32.0
10.0	51.3	53.2	54.1	54.8	35.0	32.0
11.0	42.0	44.0	45.0	45.8	35.0	32.0
12.0	35.1	37.0	37.9	38.6	35.0	32.0
14.0		27.3	28.1	28.8	29.3	29.5
16.0		20.9	21.6	22.2	22.8	22.9
18.0			17.0	17.6	18.1	18.2
20.0			13.7	14.2	14.6	14.7
22.0			11.1	11.5	11.9	12.0
24.0				9.4	9.8	9.9
26.0				7.7	8.1	8.1
28.0				6.0	6.5	6.6
30.0					5.0	5.1
32.0					3.7	3.8
危険角度 (°)	—	—	—	—	33	41
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TG3性能

カウンターウエイト 11t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	100.8	70.0	70.0	60.0		
7.0	82.7	70.0	70.0	60.0	35.0	
8.0	61.1	63.5	64.5	60.0	35.0	32.0
9.0	47.5	49.6	50.5	51.3	35.0	32.0
10.0	38.2	40.1	41.0	41.7	35.0	32.0
11.0	31.5	33.2	34.0	34.7	35.0	32.0
12.0	26.4	28.0	28.8	29.5	30.0	30.1
14.0		20.7	21.4	22.0	22.5	22.6
16.0		15.7	16.4	16.9	17.4	17.5
18.0			12.8	13.3	13.7	13.8
20.0			10.1	10.6	11.0	11.1
22.0			8.0	8.5	8.8	8.9
24.0				6.8	7.1	7.2
26.0				5.4	5.7	5.8
28.0				3.9	4.3	4.4
30.0					3.0	3.1
危険角度 (°)	—	—	—	22	37	45
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TG4性能

カウンターウエイト 11t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	120.0	70.0	70.0	60.0		
6.0	88.8	70.0	70.0	60.0		
7.0	62.4	64.8	65.8	60.0	35.0	
8.0	47.1	49.2	50.1	50.9	35.0	32.0
9.0	37.1	39.0	39.8	40.5	35.0	32.0
10.0	30.0	31.8	32.6	33.2	33.8	32.0
11.0	24.7	26.4	27.2	27.8	28.4	28.5
12.0	20.7	22.3	23.0	23.6	24.1	24.2
14.0		16.3	17.0	17.6	18.0	18.1
16.0		12.2	12.9	13.4	13.8	13.9
18.0			9.9	10.4	10.8	10.9
20.0			7.6	8.1	8.5	8.6
22.0			5.9	6.3	6.6	6.7
24.0				4.7	5.2	5.3
26.0				3.1	3.6	3.7
危険角度 (°)	—	—	—	30	47	52
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TG5性能

カウンターウエイト 11t アウトリガー張出 5.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	119.1	70.0	70.0			
5.0	90.9	70.0	70.0	60.0		
6.0	60.2	62.4	63.3	60.0		
7.0	43.7	45.7	46.5	47.3	35.0	
8.0	33.5	35.3	36.0	36.7	35.0	32.0
9.0	26.5	28.2	28.9	29.5	30.1	30.2
10.0	21.5	23.0	23.7	24.3	24.8	24.9
11.0	17.6	19.1	19.8	20.3	20.8	20.9
12.0	14.7	16.0	16.7	17.2	17.7	17.8
14.0		11.6	12.2	12.7	13.1	13.2
16.0		8.4	9.0	9.5	9.9	10.0
18.0			6.7	7.1	7.5	7.6
20.0			4.9	5.4	5.7	5.8
22.0			3.3	3.9	4.3	4.4
危険角度 (°)	—	—	—	43	54	58
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TH1性能

カウンターウエイト 0t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	114.1	70.0	70.0	60.0		
6.0	90.2	70.0	70.0	60.0		
7.0	73.8	70.0	70.0	60.0	35.0	
8.0	61.7	63.7	64.6	60.0	35.0	32.0
9.0	52.5	54.4	55.3	56.1	35.0	32.0
10.0	45.2	47.1	48.0	48.7	35.0	32.0
11.0	39.3	41.2	42.0	42.8	35.0	32.0
12.0	32.7	34.7	35.6	36.4	35.0	32.0
14.0		24.9	25.8	26.5	27.1	27.2
16.0		18.7	19.4	20.1	20.6	20.8
18.0			15.0	15.6	16.1	16.2
20.0			11.8	12.3	12.8	12.9
22.0			9.3	9.8	10.2	10.3
24.0				7.8	8.2	8.3
26.0				5.9	6.4	6.6
28.0				4.4	4.8	4.9
30.0					3.4	3.5
危険角度 (°)	—	—	—	—	38	45
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TH2性能

カウンターウエイト 0t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	114.1	70.0	70.0	60.0		
6.0	90.2	70.0	70.0	60.0		
7.0	73.8	70.0	70.0	60.0	35.0	
8.0	61.7	63.7	64.6	60.0	35.0	32.0
9.0	49.6	52.1	53.2	53.9	35.0	32.0
10.0	39.0	41.3	42.3	43.1	35.0	32.0
11.0	31.6	33.6	34.5	35.3	35.0	32.0
12.0	26.1	27.9	28.8	29.6	30.2	30.2
14.0		20.1	20.9	21.5	22.1	22.2
16.0		14.9	15.6	16.2	16.8	16.9
18.0			11.9	12.5	13.0	13.1
20.0			9.2	9.7	10.2	10.3
22.0			6.9	7.5	8.0	8.1
24.0				5.5	6.0	6.1
26.0				3.8	4.3	4.4
28.0						3.0
危険角度 (°)	—	—	—	30	47	49
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TH3性能

カウンターウエイト 0t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	114.1	70.0	70.0	60.0		
6.0	90.2	70.0	70.0	60.0		
7.0	64.1	66.8	68.0	60.0	35.0	
8.0	46.6	48.9	50.0	50.8	35.0	32.0
9.0	35.7	37.8	38.7	39.5	35.0	32.0
10.0	28.3	30.2	31.1	31.8	32.4	32.0
11.0	22.9	24.7	25.5	26.2	26.8	26.9
12.0	18.9	20.5	21.3	21.9	22.5	22.6
14.0		14.6	15.3	15.9	16.4	16.5
16.0		10.6	11.3	11.8	12.3	12.4
18.0			8.4	8.9	9.4	9.5
20.0			6.3	6.7	7.2	7.2
22.0			4.3	4.9	5.4	5.5
24.0				3.2	3.7	3.8
危険角度 (°)	—	—	—	37	51	55
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)

TH4性能

カウンターウエイト 0t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	120.0	70.0	70.0			
5.0	111.7	70.0	70.0	60.0		
6.0	67.8	70.0	70.0	60.0		
7.0	47.0	49.3	50.4	50.1	35.0	
8.0	34.9	36.9	37.9	38.7	35.0	32.0
9.0	26.9	28.8	29.7	30.4	31.0	30.0
10.0	21.3	23.1	23.9	24.6	25.2	25.3
11.0	17.2	18.9	19.6	20.3	20.8	20.9
12.0	14.0	15.6	16.3	16.9	17.5	17.6
14.0		10.9	11.5	12.1	12.6	12.7
16.0		7.6	8.3	8.8	9.3	9.4
18.0			5.9	6.4	6.8	6.9
20.0			3.6	4.3	4.9	5.0
22.0					3.0	
危険角度 (°)	—	—	30	48	55	60
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)



14.4m — 44.7m

メインブーム【特殊伸縮】

TH5性能

カウンターウエイト 0t アウトリガー張出 5.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	44.7m ブーム
3.0	120.0					
3.5	120.0	70.0				
4.0	120.0	70.0	70.0			
4.5	90.4	70.0	70.0			
5.0	68.4	70.0	70.0	60.0		
6.0	44.5	46.7	47.7	47.7		
7.0	31.7	33.7	34.5	35.2	34.8	
8.0	23.7	25.5	26.3	27.0	27.6	27.1
9.0	18.3	20.0	20.7	21.3	21.9	22.0
10.0	14.4	15.9	16.6	17.2	17.7	17.8
11.0	11.4	12.9	13.5	14.1	14.6	14.7
12.0	9.1	10.5	11.1	11.7	12.1	12.2
14.0		7.0	7.6	8.1	8.5	8.6
16.0		4.5	5.1	5.6	6.0	6.1
18.0				3.6	4.2	
危険角度 (°)	—	—	45	53	62	66
フック種類	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	7	7	6	4	4

(単位 : ton)