



# 13.6m — 50.0m

# メインブーム

AS性能 C/W 100t O/R 9.2m C/S使用 ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       | 27.25mブーム |       |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|-----------|-------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |           |       |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 3.5          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 4.0          | 200.0    | 175.0     | 141.4    | 155.0 | 160.0 | 153.0 | 83.0      |       |       |       |      |
| 4.5          | 200.0    | 175.0     | 134.2    | 155.0 | 160.0 | 146.2 | 80.7      | 135.0 | 155.0 | 155.0 | 83.0 |
| 5.0          | 200.0    | 175.0     | 127.7    | 155.0 | 160.0 | 137.5 | 75.6      | 135.0 | 155.0 | 148.8 | 83.0 |
| 6.0          | 182.5    | 175.0     | 116.6    | 155.0 | 159.6 | 122.9 | 67.2      | 135.0 | 155.0 | 135.5 | 75.5 |
| 7.0          | 162.8    | 156.7     | 107.3    | 154.3 | 144.2 | 111.1 | 60.4      | 135.0 | 152.1 | 123.5 | 68.5 |
| 8.0          | 145.5    | 141.3     | 99.5     | 139.0 | 131.4 | 101.4 | 54.8      | 125.2 | 137.0 | 113.5 | 62.7 |
| 9.0          | 128.2    | 128.4     | 92.9     | 126.3 | 120.7 | 93.2  | 50.2      | 113.6 | 124.6 | 105.0 | 57.8 |
| 10.0         | 113.6    | 113.8     | 87.2     | 113.0 | 111.6 | 86.2  | 46.5      | 103.8 | 114.1 | 97.6  | 53.6 |
| 11.0         | 95.9     | 101.8     | 82.4     | 101.1 | 103.2 | 80.2  | 43.5      | 95.5  | 102.3 | 91.3  | 49.9 |
| 12.0         |          | 91.9      | 78.1     | 91.1  | 93.3  | 75.0  | 40.5      | 88.3  | 92.4  | 85.3  | 46.7 |
| 14.0         |          | 76.3      | 71.4     | 75.5  | 77.7  | 66.4  | 36.0      | 74.5  | 76.8  | 75.1  | 41.4 |
| 16.0         |          | 54.2      | 56.4     | 63.8  | 66.0  | 59.7  | 32.5      | 62.8  | 65.1  | 66.9  | 37.2 |
| 18.0         |          |           |          | 54.8  | 57.0  | 54.3  | 29.5      | 53.7  | 56.0  | 58.6  | 33.8 |
| 20.0         |          |           |          | 44.1  | 46.3  | 48.1  | 26.5      | 46.4  | 48.8  | 51.4  | 31.0 |
| 22.0         |          |           |          |       |       |       |           | 40.5  | 42.9  | 45.5  | 28.6 |
| 24.0         |          |           |          |       |       |       |           | 35.0  | 37.4  | 39.9  | 26.8 |
| 危険角度 (°)     | -        | -         | -        | -     | -     | -     | -         | -     | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |           |       |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0         | 100   | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0         | 50    | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0         | 0     | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100       | 0     | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t       | 200t  | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35      | 2.60  | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7         | 12    | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 132.0    | 135.0 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 129.7    | 133.2 | 97.5  | 68.7 | 115.0     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 116.9    | 123.1 | 88.5  | 62.3 | 109.4     | 95.5  | 67.9 | 100.0    | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 105.9    | 114.5 | 81.0  | 56.9 | 99.7      | 87.9  | 62.4 | 93.0     | 80.0 | 66.6 | 83.0      | 70.0 | 70.0     |
| 10.0         | 96.7     | 107.0 | 74.5  | 52.4 | 91.5      | 81.3  | 57.7 | 85.7     | 73.9 | 61.8 | 78.4      | 65.2 | 70.0     |
| 11.0         | 88.8     | 100.4 | 68.8  | 48.5 | 84.5      | 75.6  | 53.6 | 79.2     | 68.6 | 57.6 | 73.0      | 61.0 | 64.2     |
| 12.0         | 82.1     | 94.0  | 63.8  | 45.1 | 78.4      | 70.7  | 50.0 | 73.2     | 64.0 | 53.9 | 68.3      | 57.5 | 60.5     |
| 14.0         | 71.0     | 78.4  | 55.5  | 39.4 | 68.0      | 62.0  | 44.1 | 63.7     | 56.3 | 47.8 | 60.4      | 51.5 | 54.1     |
| 16.0         | 62.3     | 66.7  | 49.0  | 34.7 | 59.7      | 55.1  | 39.3 | 56.2     | 50.1 | 42.7 | 53.3      | 45.9 | 49.0     |
| 18.0         | 54.9     | 57.6  | 43.8  | 31.0 | 53.0      | 49.6  | 35.4 | 50.0     | 45.1 | 38.2 | 47.5      | 41.7 | 44.7     |
| 20.0         | 47.6     | 50.3  | 39.4  | 27.9 | 47.5      | 44.9  | 32.1 | 45.0     | 40.9 | 34.4 | 42.7      | 37.7 | 40.5     |
| 22.0         | 41.7     | 44.4  | 35.8  | 25.3 | 42.9      | 41.0  | 29.3 | 40.5     | 37.3 | 31.1 | 38.7      | 34.3 | 36.6     |
| 24.0         | 36.8     | 39.5  | 32.8  | 23.2 | 38.3      | 37.7  | 26.9 | 36.7     | 34.1 | 28.2 | 35.2      | 31.4 | 33.3     |
| 26.0         | 32.7     | 35.4  | 30.2  | 21.3 | 34.2      | 34.9  | 24.9 | 33.5     | 31.3 | 25.8 | 32.3      | 28.8 | 30.5     |
| 28.0         | 29.2     | 31.9  | 28.0  | 19.8 | 30.6      | 31.8  | 23.1 | 30.6     | 28.9 | 23.7 | 29.7      | 26.5 | 28.0     |
| 30.0         |          |       |       |      | 27.6      | 28.8  | 21.6 | 27.5     | 26.8 | 21.9 | 27.5      | 24.5 | 25.9     |
| 32.0         |          |       |       |      | 24.9      | 26.2  | 20.3 | 24.9     | 24.9 | 20.3 | 25.4      | 22.8 | 24.0     |
| 34.0         |          |       |       |      | 16.9      | 18.0  | 19.3 | 22.5     | 23.3 | 18.8 | 23.2      | 21.3 | 22.4     |
| 36.0         |          |       |       |      |           |       |      | 20.5     | 21.8 | 17.6 | 21.1      | 19.9 | 20.9     |
| 38.0         |          |       |       |      |           |       |      | 15.7     | 17.3 | 16.5 | 19.3      | 18.7 | 19.6     |
| 40.0         |          |       |       |      |           |       |      |          |      |      | 17.6      | 17.6 | 18.4     |
| 42.0         |          |       |       |      |           |       |      |          |      |      | 14.5      | 16.3 | 16.9     |
| 44.0         |          |       |       |      |           |       |      |          |      |      |           |      | 15.6     |
| 46.0         |          |       |       |      |           |       |      |          |      |      |           |      | 13.6     |
| 48.0         |          |       |       |      |           |       |      |          |      |      |           |      | 6.2      |
| 危険角度 (°)     | -        | -     | -     | -    | -         | -     | -    | -        | -    | -    | -         | -    | 4        |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

A1性能 C/W 100t O/R 9.2m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       | 27.25mブーム |       |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|-----------|-------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |           |       |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 3.5          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 4.0          | 200.0    | 175.0     | 141.4    | 155.0 | 160.0 | 153.0 | 83.0      |       |       |       |      |
| 4.5          | 200.0    | 175.0     | 134.2    | 155.0 | 160.0 | 146.2 | 80.7      | 135.0 | 155.0 | 155.0 | 83.0 |
| 5.0          | 194.5    | 175.0     | 127.7    | 155.0 | 160.0 | 137.5 | 75.6      | 135.0 | 155.0 | 148.8 | 83.0 |
| 6.0          | 167.0    | 167.1     | 116.6    | 155.0 | 159.6 | 122.9 | 67.2      | 135.0 | 155.0 | 135.5 | 75.5 |
| 7.0          | 145.9    | 146.0     | 107.3    | 145.4 | 144.2 | 111.1 | 60.4      | 135.0 | 146.4 | 123.5 | 68.5 |
| 8.0          | 129.0    | 129.2     | 99.5     | 128.6 | 130.3 | 101.4 | 54.8      | 125.2 | 129.6 | 113.5 | 62.7 |
| 9.0          | 115.4    | 115.5     | 92.9     | 114.9 | 116.7 | 93.2  | 50.2      | 113.6 | 115.9 | 105.0 | 57.8 |
| 10.0         | 104.1    | 104.1     | 87.2     | 103.5 | 105.3 | 86.2  | 46.5      | 102.6 | 104.6 | 97.6  | 53.6 |
| 11.0         | 94.5     | 94.6      | 82.4     | 93.9  | 95.8  | 80.2  | 43.5      | 93.1  | 95.0  | 91.3  | 49.9 |
| 12.0         |          | 86.4      | 78.1     | 85.8  | 87.7  | 75.0  | 40.5      | 84.9  | 86.9  | 85.3  | 46.7 |
| 14.0         |          | 73.3      | 71.4     | 72.6  | 74.5  | 66.4  | 36.0      | 71.6  | 73.7  | 75.1  | 41.4 |
| 16.0         |          | 54.2      | 56.4     | 62.4  | 64.4  | 59.7  | 32.5      | 61.4  | 63.5  | 65.8  | 37.2 |
| 18.0         |          |           |          | 54.3  | 56.3  | 54.3  | 29.5      | 53.2  | 55.4  | 57.8  | 33.8 |
| 20.0         |          |           |          | 44.1  | 46.3  | 48.1  | 26.5      | 46.4  | 48.8  | 51.2  | 31.0 |
| 22.0         |          |           |          |       |       |       |           | 40.5  | 42.9  | 45.5  | 28.6 |
| 24.0         |          |           |          |       |       |       |           | 35.0  | 37.4  | 39.9  | 26.8 |
| 危険角度 (°)     | -        | -         | -        | -     | -     | -     | -         | -     | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |           |       |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0         | 100   | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0         | 50    | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0         | 0     | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100       | 0     | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t       | 200t  | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35      | 2.60  | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7         | 12    | 14    | 14    | 7    |

(単位: ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 132.0    | 135.0 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 129.7    | 133.2 | 97.5  | 68.7 | 115.0     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 116.9    | 123.1 | 88.5  | 62.3 | 109.4     | 95.5  | 67.9 | 100.0    | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 105.9    | 114.5 | 81.0  | 56.9 | 99.7      | 87.9  | 62.4 | 93.0     | 80.0 | 66.6 | 83.0      | 70.0 | 70.0     |
| 10.0         | 96.7     | 106.0 | 74.5  | 52.4 | 91.5      | 81.3  | 57.7 | 85.7     | 73.9 | 61.8 | 78.4      | 65.2 | 70.0     |
| 11.0         | 88.8     | 96.5  | 68.8  | 48.5 | 84.5      | 75.6  | 53.6 | 79.2     | 68.6 | 57.6 | 73.0      | 61.0 | 64.2     |
| 12.0         | 82.1     | 88.3  | 63.8  | 45.1 | 78.4      | 70.7  | 50.0 | 73.2     | 64.0 | 53.9 | 68.3      | 57.5 | 60.5     |
| 14.0         | 71.0     | 75.1  | 55.5  | 39.4 | 68.0      | 62.0  | 44.1 | 63.7     | 56.3 | 47.8 | 60.4      | 51.5 | 54.1     |
| 16.0         | 62.3     | 64.9  | 49.0  | 34.7 | 59.7      | 55.1  | 39.3 | 56.2     | 50.1 | 42.7 | 53.3      | 45.9 | 49.0     |
| 18.0         | 54.3     | 56.8  | 43.8  | 31.0 | 53.0      | 49.6  | 35.4 | 50.0     | 45.1 | 38.2 | 47.5      | 41.7 | 44.7     |
| 20.0         | 47.6     | 50.2  | 39.4  | 27.9 | 47.5      | 44.9  | 32.1 | 45.0     | 40.9 | 34.4 | 42.7      | 37.7 | 40.5     |
| 22.0         | 41.7     | 44.4  | 35.8  | 25.3 | 42.9      | 41.0  | 29.3 | 40.5     | 37.3 | 31.1 | 38.7      | 34.3 | 36.6     |
| 24.0         | 36.8     | 39.5  | 32.8  | 23.2 | 38.3      | 37.7  | 26.9 | 36.7     | 34.1 | 28.2 | 35.2      | 31.4 | 33.3     |
| 26.0         | 32.7     | 35.4  | 30.2  | 21.3 | 34.2      | 34.9  | 24.9 | 33.5     | 31.3 | 25.8 | 32.3      | 28.8 | 30.5     |
| 28.0         | 29.2     | 31.9  | 28.0  | 19.8 | 30.6      | 31.8  | 23.1 | 30.6     | 28.9 | 23.7 | 29.7      | 26.5 | 28.0     |
| 30.0         |          |       |       |      | 27.6      | 28.8  | 21.6 | 27.5     | 26.8 | 21.9 | 27.5      | 24.5 | 25.9     |
| 32.0         |          |       |       |      | 24.9      | 26.2  | 20.3 | 24.9     | 24.9 | 20.3 | 25.4      | 22.8 | 24.0     |
| 34.0         |          |       |       |      | 16.9      | 18.0  | 19.3 | 22.5     | 23.3 | 18.8 | 23.2      | 21.3 | 22.4     |
| 36.0         |          |       |       |      |           |       |      | 20.5     | 21.8 | 17.6 | 21.1      | 19.9 | 20.9     |
| 38.0         |          |       |       |      |           |       |      | 15.7     | 17.3 | 16.5 | 19.3      | 18.7 | 19.6     |
| 40.0         |          |       |       |      |           |       |      |          |      |      | 17.6      | 17.6 | 18.4     |
| 42.0         |          |       |       |      |           |       |      |          |      |      | 14.5      | 16.3 | 16.9     |
| 44.0         |          |       |       |      |           |       |      |          |      |      |           |      | 15.6     |
| 46.0         |          |       |       |      |           |       |      |          |      |      |           |      | 13.6     |
| 48.0         |          |       |       |      |           |       |      |          |      |      |           |      | 6.2      |
| 危険角度 (°)     | -        | -     | -     | -    | -         | -     | -    | -        | -    | -    | -         | -    | 4        |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位: ton)



# 13.6m — 50.0m

# メインブーム

A2性能 C/W 100t O/R 8.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 200.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 200.0    | 175.0     | 141.4 | 155.0    | 160.0 | 153.0 | 83.0 |           |       |       |      |
| 4.5          | 200.0    | 175.0     | 134.2 | 155.0    | 160.0 | 146.2 | 80.7 | 135.0     | 155.0 | 155.0 | 83.0 |
| 5.0          | 194.5    | 175.0     | 127.7 | 155.0    | 160.0 | 137.5 | 75.6 | 135.0     | 155.0 | 148.8 | 83.0 |
| 6.0          | 167.0    | 167.1     | 116.6 | 155.0    | 159.6 | 122.9 | 67.2 | 135.0     | 155.0 | 135.5 | 75.5 |
| 7.0          | 145.9    | 146.0     | 107.3 | 145.4    | 144.2 | 111.1 | 60.4 | 135.0     | 146.4 | 123.5 | 68.5 |
| 8.0          | 129.0    | 129.2     | 99.5  | 128.6    | 130.3 | 101.4 | 54.8 | 125.2     | 129.6 | 113.5 | 62.7 |
| 9.0          | 115.4    | 115.5     | 92.9  | 114.9    | 116.7 | 93.2  | 50.2 | 113.6     | 115.9 | 105.0 | 57.8 |
| 10.0         | 104.1    | 104.1     | 87.2  | 103.5    | 105.3 | 86.2  | 46.5 | 102.6     | 104.6 | 97.6  | 53.6 |
| 11.0         | 94.5     | 94.6      | 82.4  | 93.9     | 95.8  | 80.2  | 43.5 | 93.1      | 95.0  | 91.3  | 49.9 |
| 12.0         |          | 86.4      | 78.1  | 85.8     | 87.7  | 75.0  | 40.5 | 84.9      | 86.9  | 85.3  | 46.7 |
| 14.0         |          | 73.3      | 71.4  | 72.6     | 74.5  | 66.4  | 36.0 | 71.6      | 73.7  | 75.1  | 41.4 |
| 16.0         |          | 54.2      | 56.4  | 62.4     | 64.4  | 59.7  | 32.5 | 61.4      | 63.5  | 65.8  | 37.2 |
| 18.0         |          |           |       | 54.3     | 56.3  | 54.3  | 29.5 | 53.2      | 55.4  | 57.8  | 33.8 |
| 20.0         |          |           |       | 44.1     | 46.3  | 48.1  | 26.5 | 46.4      | 48.8  | 51.2  | 31.0 |
| 22.0         |          |           |       |          |       |       |      | 40.4      | 42.5  | 45.5  | 28.6 |
| 24.0         |          |           |       |          |       |       |      | 35.0      | 37.1  | 39.4  | 26.8 |
| 危険角度 (°)     | -        | -         | -     | -        | -     | -     | -    | -         | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 132.0    | 135.0 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 129.7    | 133.2 | 97.5  | 68.7 | 115.0     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 116.9    | 123.1 | 88.5  | 62.3 | 109.4     | 95.5  | 67.9 | 100.0    | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 105.9    | 114.5 | 81.0  | 56.9 | 99.7      | 87.9  | 62.4 | 93.0     | 80.0 | 66.6 | 83.0      | 70.0 | 70.0     |
| 10.0         | 96.7     | 106.0 | 74.5  | 52.4 | 91.5      | 81.3  | 57.7 | 85.7     | 73.9 | 61.8 | 78.4      | 65.2 | 70.0     |
| 11.0         | 88.8     | 96.5  | 68.8  | 48.5 | 84.5      | 75.6  | 53.6 | 79.2     | 68.6 | 57.6 | 73.0      | 61.0 | 64.2     |
| 12.0         | 82.1     | 88.3  | 63.8  | 45.1 | 78.4      | 70.7  | 50.0 | 73.2     | 64.0 | 53.9 | 68.3      | 57.5 | 60.5     |
| 14.0         | 71.0     | 75.1  | 55.5  | 39.4 | 68.0      | 62.0  | 44.1 | 63.7     | 56.3 | 47.8 | 60.4      | 51.5 | 54.1     |
| 16.0         | 62.3     | 64.9  | 49.0  | 34.7 | 59.7      | 55.1  | 39.3 | 56.2     | 50.1 | 42.7 | 53.3      | 45.9 | 49.0     |
| 18.0         | 54.3     | 56.8  | 43.8  | 31.0 | 53.0      | 49.6  | 35.4 | 50.0     | 45.1 | 38.2 | 47.5      | 41.7 | 44.7     |
| 20.0         | 47.6     | 50.2  | 39.4  | 27.9 | 47.5      | 44.9  | 32.1 | 45.0     | 40.9 | 34.4 | 42.7      | 37.7 | 40.5     |
| 22.0         | 41.5     | 43.8  | 35.8  | 25.3 | 42.8      | 41.0  | 29.3 | 40.5     | 37.3 | 31.1 | 38.7      | 34.3 | 36.6     |
| 24.0         | 36.0     | 38.4  | 32.8  | 23.2 | 37.3      | 37.7  | 26.9 | 36.7     | 34.1 | 28.2 | 35.2      | 31.4 | 33.3     |
| 26.0         | 31.6     | 33.9  | 30.2  | 21.3 | 32.9      | 33.9  | 24.9 | 32.9     | 31.3 | 25.8 | 32.3      | 28.8 | 30.5     |
| 28.0         | 28.0     | 30.3  | 28.0  | 19.8 | 29.2      | 30.2  | 23.1 | 29.2     | 28.9 | 23.7 | 29.7      | 26.5 | 28.0     |
| 30.0         |          |       |       |      | 26.1      | 27.1  | 21.6 | 26.1     | 26.8 | 21.9 | 26.7      | 24.5 | 25.9     |
| 32.0         |          |       |       |      | 23.5      | 24.5  | 20.3 | 23.4     | 24.9 | 20.3 | 24.0      | 22.8 | 24.0     |
| 34.0         |          |       |       |      | 16.9      | 18.0  | 19.3 | 21.1     | 22.6 | 18.8 | 21.7      | 21.3 | 22.4     |
| 36.0         |          |       |       |      |           |       |      | 19.2     | 20.6 | 17.6 | 19.7      | 19.9 | 20.4     |
| 38.0         |          |       |       |      |           |       |      | 15.7     | 17.3 | 16.5 | 17.9      | 18.7 | 18.6     |
| 40.0         |          |       |       |      |           |       |      |          |      |      | 16.4      | 17.6 | 17.0     |
| 42.0         |          |       |       |      |           |       |      |          |      |      | 14.5      | 16.3 | 15.6     |
| 44.0         |          |       |       |      |           |       |      |          |      |      |           |      | 14.3     |
| 46.0         |          |       |       |      |           |       |      |          |      |      |           |      | 13.2     |
| 48.0         |          |       |       |      |           |       |      |          |      |      |           |      | 6.2      |
| 危険角度 (°)     | -        | -     | -     | -    | -         | -     | -    | -        | -    | -    | -         | -    | 4        |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

B1性能 C/W 60t O/R 9.2m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       | 27.25mブーム |       |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|-----------|-------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |           |       |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 3.5          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 4.0          | 193.5    | 175.0     | 141.4    | 155.0 | 160.0 | 153.0 | 83.0      |       |       |       |      |
| 4.5          | 176.5    | 175.0     | 134.2    | 155.0 | 160.0 | 146.2 | 80.7      | 135.0 | 155.0 | 155.0 | 83.0 |
| 5.0          | 162.1    | 162.2     | 127.7    | 155.0 | 160.0 | 137.5 | 75.6      | 135.0 | 155.0 | 148.8 | 83.0 |
| 6.0          | 138.8    | 138.9     | 116.6    | 138.3 | 140.0 | 122.9 | 67.2      | 135.0 | 139.3 | 135.5 | 75.5 |
| 7.0          | 120.8    | 121.0     | 107.3    | 120.4 | 122.1 | 111.1 | 60.4      | 119.6 | 121.4 | 123.5 | 68.5 |
| 8.0          | 106.6    | 106.7     | 99.5     | 106.1 | 107.9 | 101.4 | 54.8      | 105.3 | 107.2 | 109.3 | 62.7 |
| 9.0          | 95.0     | 95.1      | 92.9     | 94.5  | 96.3  | 93.2  | 50.2      | 93.7  | 95.6  | 97.8  | 57.8 |
| 10.0         | 85.4     | 85.5      | 87.2     | 84.9  | 86.7  | 86.2  | 46.5      | 84.0  | 86.0  | 88.2  | 53.6 |
| 11.0         | 77.4     | 77.4      | 79.4     | 76.8  | 78.6  | 80.2  | 43.5      | 75.9  | 77.9  | 80.1  | 49.9 |
| 12.0         |          | 69.8      | 72.2     | 69.1  | 71.2  | 73.2  | 40.5      | 68.1  | 70.4  | 73.0  | 46.7 |
| 14.0         |          | 57.4      | 59.7     | 56.6  | 58.8  | 60.7  | 36.0      | 55.6  | 57.9  | 60.5  | 41.4 |
| 16.0         |          | 48.2      | 50.5     | 47.3  | 49.5  | 51.4  | 32.5      | 46.2  | 48.5  | 51.1  | 37.2 |
| 18.0         |          |           |          | 40.1  | 42.3  | 44.2  | 29.5      | 39.0  | 41.3  | 43.9  | 33.8 |
| 20.0         |          |           |          | 34.4  | 36.6  | 38.3  | 26.5      | 33.2  | 35.6  | 37.9  | 31.0 |
| 22.0         |          |           |          |       |       |       |           | 28.2  | 30.4  | 32.7  | 28.6 |
| 24.0         |          |           |          |       |       |       |           | 24.0  | 26.2  | 28.5  | 26.8 |
| 危険角度 (°)     | -        | -         | -        | -     | -     | -     | -         | -     | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |           |       |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0         | 100   | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0         | 50    | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0         | 0     | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100       | 0     | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t       | 200t  | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35      | 2.60  | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7         | 12    | 14    | 14    | 7    |

(単位: ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 132.0    | 135.0 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 120.5    | 122.8 | 97.5  | 68.7 | 115.0     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 106.3    | 108.5 | 88.5  | 62.3 | 107.7     | 95.5  | 67.9 | 100.0    | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 94.7     | 97.0  | 81.0  | 56.9 | 96.1      | 87.9  | 62.4 | 93.0     | 80.0 | 66.6 | 83.0      | 70.0 | 70.0     |
| 10.0         | 85.1     | 87.4  | 74.5  | 52.4 | 86.5      | 81.3  | 57.7 | 85.7     | 73.9 | 61.8 | 78.4      | 65.2 | 70.0     |
| 11.0         | 76.9     | 79.3  | 68.8  | 48.5 | 78.4      | 75.6  | 53.6 | 78.4     | 68.6 | 57.6 | 73.0      | 61.0 | 64.2     |
| 12.0         | 69.3     | 72.0  | 63.8  | 45.1 | 70.9      | 70.7  | 50.0 | 71.0     | 64.0 | 53.9 | 68.3      | 57.5 | 60.5     |
| 14.0         | 56.8     | 59.5  | 55.5  | 39.4 | 58.4      | 59.6  | 44.1 | 58.5     | 56.3 | 47.8 | 59.4      | 51.5 | 54.1     |
| 16.0         | 47.4     | 50.1  | 49.0  | 34.7 | 49.0      | 50.3  | 39.3 | 49.1     | 50.1 | 42.7 | 50.0      | 45.9 | 49.0     |
| 18.0         | 40.2     | 42.9  | 43.5  | 31.0 | 41.8      | 43.0  | 35.4 | 41.8     | 43.8 | 38.2 | 42.7      | 41.7 | 43.7     |
| 20.0         | 34.4     | 37.0  | 37.5  | 27.9 | 36.0      | 37.1  | 32.1 | 36.0     | 37.8 | 34.4 | 36.8      | 37.7 | 37.5     |
| 22.0         | 29.3     | 31.7  | 32.2  | 25.3 | 30.7      | 31.7  | 29.3 | 30.7     | 32.4 | 31.1 | 31.5      | 33.1 | 32.2     |
| 24.0         | 25.0     | 27.4  | 27.9  | 23.2 | 26.4      | 27.4  | 26.9 | 26.4     | 28.1 | 28.2 | 27.1      | 28.8 | 27.8     |
| 26.0         | 21.6     | 23.9  | 24.4  | 21.3 | 22.8      | 23.9  | 24.9 | 22.8     | 24.5 | 25.7 | 23.6      | 25.2 | 24.3     |
| 28.0         | 18.7     | 21.1  | 21.5  | 19.8 | 19.9      | 21.0  | 23.1 | 19.9     | 21.6 | 22.7 | 20.6      | 22.2 | 21.3     |
| 30.0         |          |       |       |      | 17.5      | 18.5  | 20.8 | 17.5     | 19.1 | 20.2 | 18.1      | 19.7 | 18.8     |
| 32.0         |          |       |       |      | 15.5      | 16.5  | 18.7 | 15.4     | 17.0 | 18.1 | 16.0      | 17.6 | 16.7     |
| 34.0         |          |       |       |      | 13.8      | 14.8  | 17.0 | 13.7     | 15.2 | 16.3 | 14.2      | 15.8 | 14.9     |
| 36.0         |          |       |       |      |           |       |      | 12.2     | 13.6 | 14.7 | 12.7      | 14.2 | 13.3     |
| 38.0         |          |       |       |      |           |       |      | 10.9     | 12.3 | 13.4 | 11.3      | 12.8 | 11.9     |
| 40.0         |          |       |       |      |           |       |      |          |      |      | 10.1      | 11.6 | 10.7     |
| 42.0         |          |       |       |      |           |       |      |          |      |      | 9.1       | 10.6 | 9.6      |
| 44.0         |          |       |       |      |           |       |      |          |      |      |           |      | 8.7      |
| 46.0         |          |       |       |      |           |       |      |          |      |      |           |      | 7.8      |
| 48.0         |          |       |       |      |           |       |      |          |      |      |           |      | 6.2      |
| 危険角度 (°)     | -        | -     | -     | -    | -         | -     | -    | -        | -    | -    | -         | -    | 4        |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位: ton)



# 13.6m — 50.0m

# メインブーム

B2性能 C/W 60t O/R 8.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 200.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 193.5    | 175.0     | 141.4 | 155.0    | 160.0 | 153.0 | 83.0 |           |       |       |      |
| 4.5          | 176.5    | 175.0     | 134.2 | 155.0    | 160.0 | 146.2 | 80.7 | 135.0     | 155.0 | 155.0 | 83.0 |
| 5.0          | 162.1    | 162.2     | 127.7 | 155.0    | 160.0 | 137.5 | 75.6 | 135.0     | 155.0 | 148.8 | 83.0 |
| 6.0          | 138.8    | 138.9     | 116.6 | 138.3    | 140.0 | 122.9 | 67.2 | 135.0     | 139.3 | 135.5 | 75.5 |
| 7.0          | 120.8    | 121.0     | 107.3 | 120.4    | 122.1 | 111.1 | 60.4 | 119.6     | 121.4 | 123.5 | 68.5 |
| 8.0          | 106.6    | 106.7     | 99.5  | 106.1    | 107.9 | 101.4 | 54.8 | 105.3     | 107.2 | 109.3 | 62.7 |
| 9.0          | 95.0     | 95.1      | 92.9  | 94.5     | 96.3  | 93.2  | 50.2 | 93.7      | 95.6  | 97.8  | 57.8 |
| 10.0         | 85.4     | 85.5      | 87.2  | 84.9     | 86.7  | 86.2  | 46.5 | 84.0      | 86.0  | 88.2  | 53.6 |
| 11.0         | 77.4     | 77.4      | 79.4  | 76.8     | 78.6  | 80.2  | 43.5 | 75.9      | 77.9  | 80.1  | 49.9 |
| 12.0         |          | 69.8      | 72.2  | 69.1     | 71.2  | 73.2  | 40.5 | 68.1      | 70.4  | 73.0  | 46.7 |
| 14.0         |          | 57.4      | 59.7  | 56.6     | 58.8  | 60.7  | 36.0 | 55.6      | 57.9  | 60.5  | 41.4 |
| 16.0         |          | 46.4      | 48.6  | 45.5     | 47.7  | 49.5  | 32.5 | 44.5      | 46.7  | 49.3  | 37.2 |
| 18.0         |          |           |       | 37.1     | 39.2  | 41.0  | 29.5 | 36.1      | 38.3  | 40.7  | 33.8 |
| 20.0         |          |           |       | 30.9     | 32.9  | 34.6  | 26.5 | 29.8      | 31.9  | 34.3  | 31.0 |
| 22.0         |          |           |       |          |       |       |      | 25.0      | 27.1  | 29.4  | 28.6 |
| 24.0         |          |           |       |          |       |       |      | 21.2      | 23.3  | 25.5  | 26.8 |
| 危険角度 (°)     | -        | -         | -     | -        | -     | -     | -    | -         | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 132.0    | 135.0 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 120.5    | 122.8 | 97.5  | 68.7 | 115.0     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 106.3    | 108.5 | 88.5  | 62.3 | 107.7     | 95.5  | 67.9 | 100.0    | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 94.7     | 97.0  | 81.0  | 56.9 | 96.1      | 87.9  | 62.4 | 93.0     | 80.0 | 66.6 | 83.0      | 70.0 | 70.0     |
| 10.0         | 85.1     | 87.4  | 74.5  | 52.4 | 86.5      | 81.3  | 57.7 | 85.7     | 73.9 | 61.8 | 78.4      | 65.2 | 70.0     |
| 11.0         | 76.9     | 79.3  | 68.8  | 48.5 | 78.4      | 75.6  | 53.6 | 78.4     | 68.6 | 57.6 | 73.0      | 61.0 | 64.2     |
| 12.0         | 69.3     | 72.0  | 63.8  | 45.1 | 70.9      | 70.7  | 50.0 | 71.0     | 64.0 | 53.9 | 68.3      | 57.5 | 60.5     |
| 14.0         | 56.8     | 59.5  | 55.5  | 39.4 | 58.4      | 59.6  | 44.1 | 58.5     | 56.3 | 47.8 | 59.4      | 51.5 | 54.1     |
| 16.0         | 45.7     | 48.3  | 48.9  | 34.7 | 47.2      | 48.4  | 39.3 | 47.3     | 49.2 | 42.7 | 48.2      | 45.9 | 49.0     |
| 18.0         | 37.2     | 39.7  | 40.3  | 31.0 | 38.7      | 39.8  | 35.4 | 38.7     | 40.6 | 38.2 | 39.6      | 41.3 | 40.3     |
| 20.0         | 30.9     | 33.3  | 33.9  | 27.9 | 32.3      | 33.4  | 32.1 | 32.3     | 34.1 | 34.4 | 33.2      | 34.8 | 33.9     |
| 22.0         | 26.0     | 28.4  | 28.9  | 25.3 | 27.4      | 28.4  | 29.3 | 27.4     | 29.1 | 30.3 | 28.2      | 29.8 | 28.9     |
| 24.0         | 22.2     | 24.5  | 25.0  | 23.2 | 23.5      | 24.5  | 26.9 | 23.5     | 25.1 | 26.3 | 24.2      | 25.8 | 24.9     |
| 26.0         | 19.0     | 21.3  | 21.8  | 21.3 | 20.3      | 21.3  | 23.7 | 20.3     | 21.9 | 23.1 | 21.0      | 22.6 | 21.7     |
| 28.0         | 16.5     | 18.7  | 19.2  | 19.8 | 17.6      | 18.7  | 21.0 | 17.6     | 19.2 | 20.4 | 18.3      | 19.9 | 19.0     |
| 30.0         |          |       |       |      | 15.4      | 16.4  | 18.7 | 15.4     | 17.0 | 18.1 | 16.1      | 17.6 | 16.7     |
| 32.0         |          |       |       |      | 13.6      | 14.6  | 16.8 | 13.5     | 15.0 | 16.2 | 14.1      | 15.7 | 14.8     |
| 34.0         |          |       |       |      | 12.0      | 13.0  | 15.2 | 11.9     | 13.4 | 14.5 | 12.5      | 14.0 | 13.1     |
| 36.0         |          |       |       |      |           |       |      | 10.5     | 12.0 | 13.1 | 11.0      | 12.5 | 11.6     |
| 38.0         |          |       |       |      |           |       |      | 9.4      | 10.8 | 11.9 | 9.8       | 11.3 | 10.4     |
| 40.0         |          |       |       |      |           |       |      |          |      |      | 8.7       | 10.2 | 9.3      |
| 42.0         |          |       |       |      |           |       |      |          |      |      | 7.5       | 9.2  | 8.3      |
| 44.0         |          |       |       |      |           |       |      |          |      |      |           |      | 7.2      |
| 46.0         |          |       |       |      |           |       |      |          |      |      |           |      | 6.3      |
| 48.0         |          |       |       |      |           |       |      |          |      |      |           |      | 5.6      |
| 危険角度 (°)     | -        | -     | -     | -    | -         | -     | -    | -        | -    | -    | -         | -    | 4        |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

B3性能 C/W 60t O/R 7.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       |       | 22.7mブーム |       |      |       | 27.25mブーム |       |      |   |
|--------------|----------|-----------|-------|-------|----------|-------|------|-------|-----------|-------|------|---|
| 2.5          | 200.0    |           |       |       |          |       |      |       |           |       |      |   |
| 3.0          | 200.0    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |   |
| 3.5          | 200.0    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |   |
| 4.0          | 193.5    | 175.0     | 141.4 | 155.0 | 160.0    | 153.0 | 83.0 |       |           |       |      |   |
| 4.5          | 176.5    | 175.0     | 134.2 | 155.0 | 160.0    | 146.2 | 80.7 | 135.0 | 155.0     | 155.0 | 83.0 |   |
| 5.0          | 162.1    | 162.2     | 127.7 | 155.0 | 160.0    | 137.5 | 75.6 | 135.0 | 155.0     | 148.8 | 83.0 |   |
| 6.0          | 138.8    | 138.9     | 116.6 | 138.3 | 140.0    | 122.9 | 67.2 | 135.0 | 139.3     | 135.5 | 75.5 |   |
| 7.0          | 120.8    | 121.0     | 107.3 | 120.4 | 122.1    | 111.1 | 60.4 | 119.6 | 121.4     | 123.5 | 68.5 |   |
| 8.0          | 106.6    | 106.7     | 99.5  | 106.1 | 107.9    | 101.4 | 54.8 | 105.3 | 107.2     | 109.3 | 62.7 |   |
| 9.0          | 95.0     | 95.1      | 92.9  | 94.5  | 96.3     | 93.2  | 50.2 | 93.7  | 95.6      | 97.8  | 57.8 |   |
| 10.0         | 83.1     | 83.2      | 85.7  | 82.5  | 84.8     | 86.2  | 46.5 | 81.4  | 83.9      | 86.6  | 53.6 |   |
| 11.0         | 70.1     | 70.2      | 72.6  | 69.5  | 71.7     | 73.6  | 43.5 | 68.5  | 70.8      | 73.4  | 49.9 |   |
| 12.0         |          | 60.3      | 62.6  | 59.6  | 61.7     | 63.6  | 40.5 | 58.7  | 60.9      | 63.4  | 46.7 |   |
| 14.0         |          | 46.4      | 48.5  | 45.7  | 47.7     | 49.4  | 36.0 | 44.8  | 46.9      | 49.2  | 41.4 |   |
| 16.0         |          | 37.1      | 39.1  | 36.3  | 38.2     | 39.9  | 32.5 | 35.4  | 37.4      | 39.7  | 37.2 |   |
| 18.0         |          |           |       | 29.6  | 31.5     | 33.1  | 29.5 | 28.7  | 30.6      | 32.8  | 33.8 |   |
| 20.0         |          |           |       | 24.6  | 26.5     | 28.0  | 26.5 | 23.6  | 25.5      | 27.7  | 29.2 |   |
| 22.0         |          |           |       |       |          |       |      | 19.7  | 21.6      | 23.7  | 25.1 |   |
| 24.0         |          |           |       |       |          |       |      | 16.6  | 18.5      | 20.6  | 21.9 |   |
| 危険角度 (°)     | -        | -         | -     | -     | -        | -     | -    | -     | -         | -     | -    | - |
| 伸長状態 (伸長割合%) |          |           |       |       |          |       |      |       |           |       |      |   |
| ブーム2 (%)     | 0        | 0         | 0     | 50    | 0        | 0     | 0    | 100   | 50        | 0     | 0    |   |
| ブーム3 (%)     | 0        | 50        | 0     | 50    | 50       | 0     | 0    | 50    | 50        | 50    | 0    |   |
| ブーム4 (%)     | 0        | 0         | 0     | 0     | 50       | 50    | 0    | 0     | 50        | 50    | 50   |   |
| ブーム5 (%)     | 0        | 0         | 50    | 0     | 0        | 50    | 100  | 0     | 0         | 50    | 100  |   |
| フック種類        | 200t     | 200t      | 200t  | 200t  | 200t     | 200t  | 83t  | 200t  | 200t      | 200t  | 83t  |   |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60  | 2.60     | 2.60  | 1.35 | 2.60  | 2.60      | 2.60  | 1.35 |   |
| 掛数           | 19       | 16        | 14    | 14    | 16       | 14    | 7    | 12    | 14        | 14    | 7    |   |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 132.0    | 135.0 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 120.5    | 122.8 | 97.5  | 68.7 | 115.0     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 106.3    | 108.5 | 88.5  | 62.3 | 107.7     | 95.5  | 67.9 | 100.0    | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 94.7     | 97.0  | 81.0  | 56.9 | 96.1      | 87.9  | 62.4 | 93.0     | 80.0 | 66.6 | 83.0      | 70.0 | 70.0     |
| 10.0         | 82.7     | 85.6  | 74.5  | 52.4 | 84.5      | 81.3  | 57.7 | 84.5     | 73.9 | 61.8 | 78.4      | 65.2 | 70.0     |
| 11.0         | 69.7     | 72.5  | 68.8  | 48.5 | 71.4      | 72.6  | 53.6 | 71.4     | 68.6 | 57.6 | 72.4      | 61.0 | 64.2     |
| 12.0         | 59.9     | 62.5  | 63.1  | 45.1 | 61.4      | 62.6  | 50.0 | 61.5     | 63.4 | 53.9 | 62.4      | 57.5 | 60.5     |
| 14.0         | 45.9     | 48.3  | 48.9  | 39.4 | 47.4      | 48.4  | 44.1 | 47.4     | 49.2 | 47.8 | 48.3      | 49.9 | 49.0     |
| 16.0         | 36.5     | 38.8  | 39.4  | 34.7 | 37.9      | 38.9  | 39.3 | 37.9     | 39.6 | 40.8 | 38.7      | 40.3 | 39.4     |
| 18.0         | 29.7     | 32.0  | 32.5  | 31.0 | 31.0      | 32.0  | 34.4 | 31.1     | 32.7 | 33.9 | 31.8      | 33.4 | 32.5     |
| 20.0         | 24.6     | 26.8  | 27.3  | 27.9 | 25.9      | 26.9  | 29.2 | 25.9     | 27.5 | 28.6 | 26.6      | 28.2 | 27.3     |
| 22.0         | 20.6     | 22.8  | 23.3  | 25.0 | 21.9      | 22.8  | 25.1 | 21.9     | 23.5 | 24.6 | 22.6      | 24.1 | 23.2     |
| 24.0         | 17.5     | 19.6  | 20.1  | 21.7 | 18.7      | 19.6  | 21.8 | 18.7     | 20.2 | 21.3 | 19.4      | 20.8 | 20.0     |
| 26.0         | 14.9     | 17.0  | 17.4  | 19.1 | 16.0      | 17.0  | 19.1 | 16.1     | 17.5 | 18.6 | 16.7      | 18.2 | 17.3     |
| 28.0         | 12.8     | 14.9  | 15.3  | 16.9 | 13.9      | 14.8  | 16.9 | 13.9     | 15.3 | 16.4 | 14.5      | 15.9 | 15.1     |
| 30.0         |          |       |       |      | 12.1      | 13.0  | 15.0 | 12.0     | 13.5 | 14.5 | 12.6      | 14.0 | 13.2     |
| 32.0         |          |       |       |      | 10.5      | 11.4  | 13.5 | 10.5     | 11.9 | 12.9 | 11.0      | 12.4 | 11.6     |
| 34.0         |          |       |       |      | 9.3       | 10.2  | 12.1 | 9.1      | 10.5 | 11.5 | 9.6       | 11.0 | 10.2     |
| 36.0         |          |       |       |      |           |       |      | 8.0      | 9.3  | 10.3 | 8.4       | 9.8  | 9.0      |
| 38.0         |          |       |       |      |           |       |      | 7.0      | 8.3  | 9.3  | 7.4       | 8.8  | 7.9      |
| 40.0         |          |       |       |      |           |       |      |          |      |      | 6.5       | 7.9  | 7.0      |
| 42.0         |          |       |       |      |           |       |      |          |      |      | 5.6       | 7.1  | 6.2      |
| 44.0         |          |       |       |      |           |       |      |          |      |      |           |      | 5.4      |
| 46.0         |          |       |       |      |           |       |      |          |      |      |           |      | 4.5      |
| 危険角度 (°)     | -        | -     | -     | -    | -         | -     | -    | -        | -    | -    | -         | -    | 16       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

B4性能 C/W 60t O/R 6.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       | 27.25mブーム |       |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|-----------|-------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |           |       |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 3.5          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 4.0          | 193.5    | 175.0     | 141.4    | 155.0 | 160.0 | 153.0 | 83.0      |       |       |       |      |
| 4.5          | 176.5    | 175.0     | 134.2    | 155.0 | 160.0 | 146.2 | 80.7      | 135.0 | 155.0 | 155.0 | 83.0 |
| 5.0          | 162.1    | 162.2     | 127.7    | 155.0 | 160.0 | 137.5 | 75.6      | 135.0 | 155.0 | 148.8 | 83.0 |
| 6.0          | 138.8    | 138.9     | 116.6    | 138.3 | 140.0 | 122.9 | 67.2      | 135.0 | 139.3 | 135.5 | 75.5 |
| 7.0          | 120.8    | 121.0     | 107.3    | 120.4 | 122.1 | 111.1 | 60.4      | 119.6 | 121.4 | 123.5 | 68.5 |
| 8.0          | 102.6    | 102.8     | 99.5     | 102.1 | 104.4 | 101.4 | 54.8      | 100.9 | 103.5 | 106.4 | 62.7 |
| 9.0          | 82.9     | 83.0      | 85.5     | 82.3  | 84.5  | 86.6  | 50.2      | 81.3  | 83.7  | 86.4  | 57.8 |
| 10.0         | 68.9     | 69.1      | 71.4     | 68.4  | 70.5  | 72.4  | 46.5      | 67.4  | 69.7  | 72.2  | 53.6 |
| 11.0         | 58.6     | 58.7      | 60.9     | 58.0  | 60.1  | 61.9  | 43.5      | 57.1  | 59.3  | 61.7  | 49.9 |
| 12.0         |          | 50.7      | 52.8     | 50.1  | 52.0  | 53.8  | 40.5      | 49.1  | 51.2  | 53.6  | 46.7 |
| 14.0         |          | 39.2      | 41.2     | 38.5  | 40.4  | 42.1  | 36.0      | 37.6  | 39.6  | 41.9  | 41.4 |
| 16.0         |          | 31.4      | 33.3     | 30.6  | 32.5  | 34.1  | 32.5      | 29.8  | 31.7  | 33.9  | 35.5 |
| 18.0         |          |           |          | 24.9  | 26.7  | 28.3  | 28.4      | 24.0  | 25.9  | 28.0  | 29.5 |
| 20.0         |          |           |          | 20.6  | 22.4  | 23.9  | 24.0      | 19.7  | 21.5  | 23.6  | 25.1 |
| 22.0         |          |           |          |       |       |       |           | 16.3  | 18.1  | 20.2  | 21.5 |
| 24.0         |          |           |          |       |       |       |           | 13.6  | 15.4  | 17.4  | 18.7 |
| 危険角度 (°)     | -        | -         | -        | -     | -     | -     | -         | -     | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |           |       |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0         | 100   | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0         | 50    | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0         | 0     | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100       | 0     | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t       | 200t  | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35      | 2.60  | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7         | 12    | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 132.0    | 135.0 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 120.5    | 122.8 | 97.5  | 68.7 | 115.0     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 102.3    | 105.4 | 88.5  | 62.3 | 104.2     | 95.5  | 67.9 | 100.0    | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 82.6     | 85.4  | 81.0  | 56.9 | 84.3      | 85.5  | 62.4 | 84.3     | 80.0 | 66.6 | 83.0      | 70.0 | 70.0     |
| 10.0         | 68.6     | 71.3  | 72.0  | 52.4 | 70.2      | 71.4  | 57.7 | 70.3     | 72.3 | 61.8 | 71.3      | 65.2 | 70.0     |
| 11.0         | 58.3     | 60.8  | 61.4  | 48.5 | 59.8      | 60.9  | 53.6 | 59.9     | 61.8 | 57.6 | 60.8      | 61.0 | 61.5     |
| 12.0         | 50.3     | 52.7  | 53.3  | 45.1 | 51.7      | 52.8  | 50.0 | 51.8     | 53.6 | 53.9 | 52.7      | 54.4 | 53.4     |
| 14.0         | 38.7     | 41.0  | 41.6  | 39.4 | 40.1      | 41.1  | 43.7 | 40.1     | 41.9 | 43.1 | 41.0      | 42.6 | 41.7     |
| 16.0         | 30.8     | 33.0  | 33.6  | 34.7 | 32.1      | 33.1  | 35.5 | 32.2     | 33.8 | 35.0 | 32.9      | 34.5 | 33.6     |
| 18.0         | 25.0     | 27.2  | 27.7  | 29.4 | 26.3      | 27.3  | 29.6 | 26.3     | 27.9 | 29.0 | 27.1      | 28.6 | 27.7     |
| 20.0         | 20.6     | 22.8  | 23.2  | 24.9 | 21.9      | 22.8  | 25.1 | 21.9     | 23.5 | 24.5 | 22.6      | 24.1 | 23.2     |
| 22.0         | 17.2     | 19.3  | 19.8  | 21.4 | 18.4      | 19.3  | 21.5 | 18.4     | 19.9 | 21.0 | 19.1      | 20.6 | 19.7     |
| 24.0         | 14.4     | 16.5  | 17.0  | 18.6 | 15.6      | 16.5  | 18.7 | 15.6     | 17.1 | 18.1 | 16.3      | 17.7 | 16.9     |
| 26.0         | 12.2     | 14.2  | 14.7  | 16.3 | 13.3      | 14.2  | 16.3 | 13.3     | 14.8 | 15.8 | 13.9      | 15.4 | 14.5     |
| 28.0         | 10.3     | 12.4  | 12.8  | 14.3 | 11.4      | 12.3  | 14.4 | 11.4     | 12.8 | 13.8 | 12.0      | 13.4 | 12.6     |
| 30.0         |          |       |       |      | 9.8       | 10.7  | 12.7 | 9.8      | 11.2 | 12.2 | 10.3      | 11.7 | 10.9     |
| 32.0         |          |       |       |      | 8.4       | 9.3   | 11.3 | 8.4      | 9.8  | 10.8 | 8.9       | 10.3 | 9.5      |
| 34.0         |          |       |       |      | 7.3       | 8.2   | 10.2 | 7.2      | 8.5  | 9.6  | 7.7       | 9.1  | 8.3      |
| 36.0         |          |       |       |      |           |       |      | 6.1      | 7.5  | 8.5  | 6.7       | 8.0  | 7.2      |
| 38.0         |          |       |       |      |           |       |      |          | 6.6  | 7.6  | 5.6       | 7.1  | 6.3      |
| 40.0         |          |       |       |      |           |       |      |          |      |      | 4.5       | 6.6  | 5.3      |
| 42.0         |          |       |       |      |           |       |      |          |      |      |           | 5.6  | 4.4      |
| 危険角度 (°)     | -        | -     | -     | -    | -         | -     | -    | 18       | -    | -    | 20        | -    | 28       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

C1性能 C/W 40t O/R 9.2m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 184.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 166.4    | 166.5     | 141.4 | 155.0    | 160.0 | 153.0 | 83.0 |           |       |       |      |
| 4.5          | 151.6    | 151.7     | 134.2 | 151.2    | 152.7 | 146.2 | 80.7 | 135.0     | 152.1 | 154.0 | 83.0 |
| 5.0          | 139.0    | 139.1     | 127.7 | 138.6    | 140.2 | 137.5 | 75.6 | 135.0     | 139.5 | 141.5 | 83.0 |
| 6.0          | 118.7    | 118.8     | 116.6 | 118.3    | 119.9 | 121.5 | 67.2 | 117.5     | 119.3 | 121.3 | 75.5 |
| 7.0          | 103.1    | 103.2     | 105.1 | 102.6    | 104.3 | 105.9 | 60.4 | 101.8     | 103.6 | 105.8 | 68.5 |
| 8.0          | 90.6     | 90.8      | 92.7  | 90.2     | 91.9  | 93.6  | 54.8 | 89.3      | 91.2  | 93.4  | 62.7 |
| 9.0          | 80.5     | 80.7      | 82.6  | 80.1     | 81.9  | 83.5  | 50.2 | 79.2      | 81.1  | 83.3  | 57.8 |
| 10.0         | 71.3     | 71.4      | 73.8  | 70.7     | 72.9  | 74.8  | 46.5 | 69.7      | 72.0  | 74.6  | 53.6 |
| 11.0         | 63.2     | 63.3      | 65.7  | 62.6     | 64.8  | 66.7  | 43.5 | 61.6      | 63.9  | 68.5  | 49.9 |
| 12.0         |          | 56.6      | 58.9  | 55.9     | 58.0  | 60.0  | 40.5 | 54.9      | 57.1  | 59.7  | 46.7 |
| 14.0         |          | 46.1      | 48.4  | 45.3     | 47.5  | 49.4  | 36.0 | 44.2      | 46.6  | 49.2  | 41.4 |
| 16.0         |          | 38.3      | 40.6  | 37.4     | 39.6  | 41.5  | 32.5 | 36.3      | 38.6  | 41.2  | 37.2 |
| 18.0         |          |           |       | 31.3     | 33.5  | 35.4  | 29.5 | 30.2      | 32.5  | 35.1  | 33.8 |
| 20.0         |          |           |       | 26.1     | 28.2  | 30.0  | 26.5 | 25.0      | 27.2  | 29.6  | 31.0 |
| 22.0         |          |           |       |          |       |       |      | 20.6      | 22.8  | 25.1  | 26.7 |
| 24.0         |          |           |       |          |       |       |      | 17.2      | 19.3  | 21.6  | 23.1 |
| 危険角度 (°)     | -        | -         | -     | -        | -     | -     | -    | -         | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 118.4    | 120.6 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 102.8    | 105.0 | 97.5  | 68.7 | 104.1     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 90.3     | 92.6  | 88.5  | 62.3 | 91.7      | 92.7  | 67.9 | 91.7     | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 80.2     | 82.5  | 81.0  | 56.9 | 81.6      | 82.7  | 62.4 | 81.6     | 80.0 | 66.6 | 66.6      | 62.5 | 70.0     |
| 10.0         | 70.9     | 73.7  | 74.4  | 52.4 | 72.6      | 73.8  | 57.7 | 72.6     | 73.9 | 61.8 | 73.6      | 65.2 | 70.0     |
| 11.0         | 62.8     | 65.5  | 66.2  | 48.5 | 64.5      | 65.7  | 53.6 | 64.5     | 66.6 | 57.6 | 65.5      | 61.0 | 64.2     |
| 12.0         | 56.1     | 58.8  | 59.5  | 45.1 | 57.7      | 58.9  | 50.0 | 57.8     | 59.8 | 53.9 | 58.7      | 57.5 | 59.7     |
| 14.0         | 45.5     | 48.2  | 48.8  | 39.4 | 47.1      | 48.3  | 44.1 | 47.1     | 49.2 | 47.8 | 48.1      | 50.0 | 49.1     |
| 16.0         | 37.5     | 40.2  | 40.9  | 34.7 | 39.1      | 40.3  | 39.3 | 39.2     | 41.2 | 42.6 | 40.1      | 42.0 | 41.1     |
| 18.0         | 31.4     | 34.1  | 34.7  | 31.0 | 33.0      | 34.2  | 35.4 | 33.0     | 35.0 | 36.4 | 33.9      | 35.8 | 34.9     |
| 20.0         | 26.1     | 28.6  | 29.2  | 27.9 | 27.6      | 28.7  | 31.3 | 27.6     | 29.4 | 30.7 | 28.4      | 30.2 | 29.2     |
| 22.0         | 21.7     | 24.1  | 24.6  | 25.3 | 23.1      | 24.1  | 26.7 | 23.1     | 24.8 | 26.1 | 23.9      | 25.6 | 24.6     |
| 24.0         | 18.2     | 20.6  | 21.1  | 22.9 | 19.5      | 20.6  | 23.0 | 19.5     | 21.2 | 22.4 | 20.3      | 21.9 | 21.0     |
| 26.0         | 15.4     | 17.7  | 18.2  | 20.0 | 16.6      | 17.7  | 20.1 | 16.6     | 18.3 | 19.5 | 17.4      | 19.0 | 18.0     |
| 28.0         | 13.1     | 15.4  | 15.8  | 17.6 | 14.3      | 15.3  | 17.6 | 14.3     | 15.9 | 17.0 | 14.9      | 16.5 | 15.6     |
| 30.0         |          |       |       |      | 12.3      | 13.3  | 15.6 | 12.3     | 13.8 | 15.0 | 12.9      | 14.5 | 13.6     |
| 32.0         |          |       |       |      | 10.6      | 11.6  | 13.9 | 10.6     | 12.1 | 13.3 | 11.2      | 12.7 | 11.8     |
| 34.0         |          |       |       |      | 9.3       | 10.3  | 12.5 | 9.1      | 10.6 | 11.8 | 9.7       | 11.3 | 10.3     |
| 36.0         |          |       |       |      |           |       |      | 7.7      | 9.4  | 10.5 | 8.4       | 10.0 | 9.1      |
| 38.0         |          |       |       |      |           |       |      | 6.4      | 8.3  | 9.4  | 7.0       | 8.8  | 7.9      |
| 40.0         |          |       |       |      |           |       |      |          |      |      | 5.8       | 7.9  | 6.7      |
| 42.0         |          |       |       |      |           |       |      |          |      |      | 4.8       | 6.9  | 5.6      |
| 44.0         |          |       |       |      |           |       |      |          |      |      |           |      | 4.7      |
| 危険角度 (°)     | -        | -     | -     | -    | -         | -     | -    | -        | -    | -    | -         | -    | 22       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)





# 13.6m — 50.0m

# メインブーム

C2性能 C/W 40t O/R 8.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       | 27.25mブーム |       |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|-----------|-------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |           |       |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 3.5          | 184.0    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 4.0          | 166.4    | 166.5     | 141.4    | 155.0 | 160.0 | 153.0 | 83.0      |       |       |       |      |
| 4.5          | 151.6    | 151.7     | 134.2    | 151.2 | 152.7 | 146.2 | 80.7      | 135.0 | 152.1 | 154.0 | 83.0 |
| 5.0          | 139.0    | 139.1     | 127.7    | 138.6 | 140.2 | 137.5 | 75.6      | 135.0 | 139.5 | 141.5 | 83.0 |
| 6.0          | 118.7    | 118.8     | 116.6    | 118.3 | 119.9 | 121.5 | 67.2      | 117.5 | 119.3 | 121.3 | 75.5 |
| 7.0          | 103.1    | 103.2     | 105.1    | 102.6 | 104.3 | 105.9 | 60.4      | 101.8 | 103.6 | 105.8 | 68.5 |
| 8.0          | 90.6     | 90.8      | 92.7     | 90.2  | 91.9  | 93.6  | 54.8      | 89.3  | 91.2  | 93.4  | 62.7 |
| 9.0          | 80.5     | 80.7      | 82.6     | 80.1  | 81.9  | 83.5  | 50.2      | 79.2  | 81.1  | 83.3  | 57.8 |
| 10.0         | 71.3     | 71.4      | 73.8     | 70.7  | 72.9  | 74.8  | 46.5      | 69.7  | 72.0  | 74.6  | 53.6 |
| 11.0         | 63.2     | 63.3      | 65.7     | 62.6  | 64.8  | 66.7  | 43.5      | 61.6  | 63.9  | 68.5  | 49.9 |
| 12.0         |          | 56.6      | 58.9     | 55.9  | 58.0  | 60.0  | 40.5      | 54.9  | 57.1  | 59.7  | 46.7 |
| 14.0         |          | 45.2      | 47.6     | 44.4  | 46.7  | 48.6  | 36.0      | 43.4  | 45.8  | 48.4  | 41.4 |
| 16.0         |          | 35.6      | 37.8     | 34.7  | 36.9  | 38.7  | 32.5      | 33.7  | 36.0  | 38.5  | 37.2 |
| 18.0         |          |           |          | 27.9  | 30.0  | 31.7  | 29.5      | 26.9  | 29.0  | 31.5  | 33.2 |
| 20.0         |          |           |          | 22.8  | 24.9  | 26.6  | 26.5      | 21.7  | 23.9  | 26.2  | 27.9 |
| 22.0         |          |           |          |       |       |       |           | 17.8  | 19.9  | 22.2  | 23.8 |
| 24.0         |          |           |          |       |       |       |           | 14.7  | 16.8  | 19.1  | 20.6 |
| 危険角度 (°)     | -        | -         | -        | -     | -     | -     | -         | -     | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |           |       |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0         | 100   | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0         | 50    | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0         | 0     | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100       | 0     | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t       | 200t  | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35      | 2.60  | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7         | 12    | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       | 36.35mブーム |       |       | 40.9mブーム |       |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|-----------|-------|-------|----------|-------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0      |       |       |          |       |      |           |      |          |
| 6.0          | 118.4    | 120.6 | 108.4 | 76.5      | 115.0 | 105.0 | 80.0     |       |      |           |      |          |
| 7.0          | 102.8    | 105.0 | 97.5  | 68.7      | 104.1 | 105.0 | 74.4     | 100.0 | 83.0 | 78.0      |      |          |
| 8.0          | 90.3     | 92.6  | 88.5  | 62.3      | 91.7  | 92.7  | 67.9     | 91.7  | 83.0 | 72.1      | 83.0 | 74.0     |
| 9.0          | 80.2     | 82.5  | 81.0  | 56.9      | 81.6  | 82.7  | 62.4     | 81.6  | 80.0 | 66.6      | 82.5 | 70.0     |
| 10.0         | 70.9     | 73.7  | 74.4  | 52.4      | 72.6  | 73.8  | 57.7     | 72.6  | 73.9 | 61.8      | 73.6 | 65.2     |
| 11.0         | 62.8     | 65.5  | 66.2  | 48.5      | 64.5  | 65.7  | 53.6     | 64.5  | 66.6 | 57.6      | 65.5 | 61.0     |
| 12.0         | 56.1     | 58.8  | 59.5  | 45.1      | 57.7  | 58.9  | 50.0     | 57.8  | 59.8 | 53.9      | 58.7 | 57.5     |
| 14.0         | 44.7     | 47.4  | 48.1  | 39.4      | 46.3  | 47.5  | 44.1     | 46.4  | 48.4 | 47.8      | 47.3 | 49.2     |
| 16.0         | 34.9     | 37.5  | 38.1  | 34.7      | 36.5  | 37.6  | 39.3     | 36.5  | 38.4 | 39.8      | 37.4 | 39.2     |
| 18.0         | 28.0     | 30.5  | 31.1  | 31.0      | 29.5  | 30.6  | 33.2     | 29.5  | 31.3 | 32.6      | 30.4 | 32.1     |
| 20.0         | 22.8     | 25.3  | 25.8  | 27.8      | 24.3  | 25.3  | 27.9     | 24.3  | 26.1 | 27.3      | 25.1 | 26.8     |
| 22.0         | 18.9     | 21.3  | 21.8  | 23.7      | 20.2  | 21.3  | 23.8     | 20.3  | 22.0 | 23.2      | 21.0 | 22.7     |
| 24.0         | 15.7     | 18.1  | 18.6  | 20.4      | 17.0  | 18.1  | 20.5     | 17.1  | 18.7 | 19.9      | 17.8 | 19.4     |
| 26.0         | 13.2     | 15.5  | 16.0  | 17.8      | 14.4  | 15.5  | 17.8     | 14.4  | 16.1 | 17.2      | 15.2 | 16.7     |
| 28.0         | 11.1     | 13.4  | 13.8  | 15.6      | 12.3  | 13.3  | 15.6     | 12.3  | 13.9 | 15.0      | 13.0 | 14.5     |
| 30.0         |          |       |       |           | 10.5  | 11.5  | 13.8     | 10.5  | 12.0 | 13.2      | 11.1 | 12.7     |
| 32.0         |          |       |       |           | 9.0   | 10.0  | 12.2     | 8.9   | 10.5 | 11.6      | 9.6  | 11.1     |
| 34.0         |          |       |       |           | 7.5   | 8.8   | 10.9     | 7.3   | 9.1  | 10.2      | 8.1  | 9.7      |
| 36.0         |          |       |       |           |       |       |          | 6.0   | 7.9  | 9.1       | 6.7  | 8.5      |
| 38.0         |          |       |       |           |       |       |          |       | 6.8  | 8.1       | 5.4  | 7.5      |
| 40.0         |          |       |       |           |       |       |          |       |      |           | 4.4  | 6.4      |
| 42.0         |          |       |       |           |       |       |          |       |      |           |      | 5.5      |
| 危険角度 (°)     | -        | -     | -     | -         | -     | -     | -        | 18    | -    | -         | 20   | -        |
| 伸長状態 (伸長割合%) |          |       |       |           |       |       |          |       |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0         | 100   | 50    | 0        | 100   | 50   | 0         | 100  | 50       |
| ブーム3 (%)     | 50       | 50    | 100   | 0         | 50    | 100   | 50       | 100   | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100       | 50    | 50    | 100      | 50    | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100       | 50    | 50    | 100      | 50    | 50   | 100       | 50   | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t       | 200t  | 200t  | 83t      | 200t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35      | 2.60  | 2.60  | 1.35     | 2.60  | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7         | 10    | 10    | 7        | 10    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

C3性能 C/W 40t O/R 7.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       |       | 22.7mブーム |       |      |       | 27.25mブーム |       |      |   |
|--------------|----------|-----------|-------|-------|----------|-------|------|-------|-----------|-------|------|---|
| 2.5          | 200.0    |           |       |       |          |       |      |       |           |       |      |   |
| 3.0          | 200.0    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |   |
| 3.5          | 184.0    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |   |
| 4.0          | 166.4    | 166.5     | 141.4 | 155.0 | 160.0    | 153.0 | 83.0 |       |           |       |      |   |
| 4.5          | 151.6    | 151.7     | 134.2 | 151.2 | 152.7    | 146.2 | 80.7 | 135.0 | 152.1     | 154.0 | 83.0 |   |
| 5.0          | 139.0    | 139.1     | 127.7 | 138.6 | 140.2    | 137.5 | 75.6 | 135.0 | 139.5     | 141.5 | 83.0 |   |
| 6.0          | 118.7    | 118.8     | 116.6 | 118.3 | 119.9    | 121.5 | 67.2 | 117.5 | 119.3     | 121.3 | 75.5 |   |
| 7.0          | 103.1    | 103.2     | 105.1 | 102.6 | 104.3    | 105.9 | 60.4 | 101.8 | 103.6     | 105.8 | 68.5 |   |
| 8.0          | 90.6     | 90.8      | 92.7  | 90.2  | 91.9     | 93.6  | 54.8 | 89.3  | 91.2      | 93.4  | 62.7 |   |
| 9.0          | 79.8     | 80.0      | 82.6  | 79.2  | 81.6     | 83.5  | 50.2 | 78.1  | 80.7      | 83.3  | 57.8 |   |
| 10.0         | 65.3     | 65.4      | 67.9  | 64.7  | 67.0     | 69.0  | 46.5 | 63.6  | 66.0      | 68.8  | 53.6 |   |
| 11.0         | 54.7     | 54.8      | 57.2  | 54.1  | 56.3     | 58.3  | 43.5 | 53.1  | 55.4      | 58.0  | 49.9 |   |
| 12.0         |          | 46.8      | 49.1  | 46.1  | 48.2     | 50.1  | 40.5 | 45.1  | 47.4      | 49.9  | 46.7 |   |
| 14.0         |          | 35.5      | 37.6  | 34.8  | 36.8     | 38.5  | 36.0 | 33.9  | 36.0      | 38.3  | 40.1 |   |
| 16.0         |          | 28.0      | 30.0  | 27.2  | 29.1     | 30.8  | 30.9 | 26.3  | 28.3      | 30.5  | 32.2 |   |
| 18.0         |          |           |       | 21.7  | 23.6     | 25.2  | 25.4 | 20.8  | 22.8      | 25.0  | 26.5 |   |
| 20.0         |          |           |       | 17.7  | 19.6     | 21.1  | 21.2 | 16.7  | 18.7      | 20.8  | 22.3 |   |
| 22.0         |          |           |       |       |          |       |      | 13.6  | 15.5      | 17.6  | 19.0 |   |
| 24.0         |          |           |       |       |          |       |      | 11.0  | 13.0      | 15.0  | 16.4 |   |
| 危険角度 (°)     | -        | -         | -     | -     | -        | -     | -    | -     | -         | -     | -    | - |
| 伸長状態 (伸長割合%) |          |           |       |       |          |       |      |       |           |       |      |   |
| ブーム2 (%)     | 0        | 0         | 0     | 50    | 0        | 0     | 0    | 100   | 50        | 0     | 0    |   |
| ブーム3 (%)     | 0        | 50        | 0     | 50    | 50       | 0     | 0    | 50    | 50        | 50    | 0    |   |
| ブーム4 (%)     | 0        | 0         | 0     | 0     | 50       | 50    | 0    | 0     | 50        | 50    | 50   |   |
| ブーム5 (%)     | 0        | 0         | 50    | 0     | 0        | 50    | 100  | 0     | 0         | 50    | 100  |   |
| フック種類        | 200t     | 200t      | 200t  | 200t  | 200t     | 200t  | 83t  | 200t  | 200t      | 200t  | 83t  |   |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60  | 2.60     | 2.60  | 1.35 | 2.60  | 2.60      | 2.60  | 1.35 |   |
| 掛数           | 19       | 16        | 14    | 14    | 16       | 14    | 7    | 12    | 14        | 14    | 7    |   |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 118.4    | 120.6 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 102.8    | 105.0 | 97.5  | 68.7 | 104.1     | 105.0 | 74.4 | 100.0    | 83.0 | 78.0 |           |      |          |
| 8.0          | 90.3     | 92.6  | 88.5  | 62.3 | 91.7      | 92.7  | 67.9 | 91.7     | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 79.5     | 82.5  | 81.0  | 56.9 | 81.4      | 82.7  | 62.4 | 81.4     | 80.0 | 66.6 | 81.6      | 70.0 | 70.0     |
| 10.0         | 64.9     | 67.8  | 68.5  | 52.4 | 66.7      | 67.9  | 57.7 | 66.7     | 68.9 | 61.8 | 67.8      | 65.2 | 68.6     |
| 11.0         | 54.4     | 57.1  | 57.8  | 48.5 | 56.0      | 57.2  | 53.6 | 56.1     | 58.1 | 57.6 | 57.0      | 58.9 | 57.8     |
| 12.0         | 46.3     | 48.9  | 49.6  | 45.1 | 47.9      | 49.1  | 50.0 | 48.0     | 49.9 | 51.3 | 48.9      | 50.7 | 49.7     |
| 14.0         | 35.0     | 37.4  | 38.0  | 39.4 | 36.5      | 37.5  | 40.2 | 36.5     | 38.3 | 39.6 | 37.4      | 39.1 | 38.1     |
| 16.0         | 27.3     | 29.7  | 30.2  | 32.1 | 28.7      | 29.8  | 32.3 | 28.8     | 30.5 | 31.7 | 29.6      | 31.2 | 30.3     |
| 18.0         | 21.8     | 24.1  | 24.6  | 26.4 | 23.2      | 24.2  | 26.6 | 23.2     | 24.9 | 26.0 | 24.0      | 25.5 | 24.7     |
| 20.0         | 17.7     | 19.9  | 20.4  | 22.2 | 19.0      | 20.0  | 22.3 | 19.0     | 20.6 | 21.7 | 19.8      | 21.3 | 20.4     |
| 22.0         | 14.5     | 16.7  | 17.1  | 18.9 | 15.7      | 16.7  | 19.0 | 15.8     | 17.3 | 18.4 | 16.5      | 18.0 | 17.1     |
| 24.0         | 11.9     | 14.1  | 14.5  | 16.2 | 13.1      | 14.1  | 16.3 | 13.2     | 14.7 | 15.7 | 13.8      | 15.3 | 14.5     |
| 26.0         | 9.9      | 12.0  | 12.4  | 14.0 | 11.0      | 11.9  | 14.1 | 11.0     | 12.5 | 13.6 | 11.7      | 13.1 | 12.3     |
| 28.0         | 8.2      | 10.3  | 10.7  | 12.3 | 9.3       | 10.2  | 12.3 | 9.3      | 10.7 | 11.8 | 9.9       | 11.3 | 10.5     |
| 30.0         |          |       |       |      | 7.8       | 8.7   | 10.8 | 7.8      | 9.2  | 10.2 | 8.4       | 9.8  | 8.9      |
| 32.0         |          |       |       |      | 6.6       | 7.5   | 9.5  | 6.5      | 7.9  | 8.9  | 7.1       | 8.5  | 7.6      |
| 34.0         |          |       |       |      |           | 6.5   | 8.4  |          | 6.8  | 7.8  | 5.9       | 7.3  | 6.5      |
| 36.0         |          |       |       |      |           |       |      |          | 5.8  | 6.8  | 4.6       | 6.4  | 5.5      |
| 38.0         |          |       |       |      |           |       |      |          | 4.8  | 6.0  |           | 5.5  | 4.3      |
| 40.0         |          |       |       |      |           |       |      |          |      |      |           | 4.6  |          |
| 危険角度 (°)     | -        | -     | -     | -    | 15        | -     | -    | 33       | -    | -    | 33        | 20   | 37       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

C4性能 C/W 40t O/R 6.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 200.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 184.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 166.4    | 166.5     | 141.4 | 155.0    | 160.0 | 153.0 | 83.0 |           |       |       |      |
| 4.5          | 151.6    | 151.7     | 134.2 | 151.2    | 152.7 | 146.2 | 80.7 | 135.0     | 152.1 | 154.0 | 83.0 |
| 5.0          | 139.0    | 139.1     | 127.7 | 138.6    | 140.2 | 137.5 | 75.6 | 135.0     | 139.5 | 141.5 | 83.0 |
| 6.0          | 118.7    | 118.8     | 116.6 | 118.3    | 119.9 | 121.5 | 67.2 | 117.5     | 119.3 | 121.3 | 75.5 |
| 7.0          | 103.1    | 103.2     | 105.1 | 102.6    | 104.3 | 105.9 | 60.4 | 101.8     | 103.6 | 105.8 | 68.5 |
| 8.0          | 80.6     | 80.8      | 83.4  | 80.0     | 82.4  | 84.6  | 54.8 | 78.9      | 81.5  | 84.4  | 62.7 |
| 9.0          | 64.6     | 64.8      | 67.3  | 64.1     | 66.3  | 68.4  | 50.2 | 63.1      | 65.4  | 68.1  | 57.8 |
| 10.0         | 53.4     | 53.5      | 55.8  | 52.9     | 55.0  | 56.9  | 46.5 | 51.9      | 54.1  | 56.7  | 53.6 |
| 11.0         | 45.1     | 45.2      | 47.4  | 44.5     | 46.5  | 48.4  | 43.5 | 43.6      | 45.7  | 48.2  | 49.9 |
| 12.0         |          | 38.7      | 40.8  | 38.0     | 40.0  | 41.8  | 40.5 | 37.1      | 39.2  | 41.6  | 43.4 |
| 14.0         |          | 29.4      | 31.4  | 28.7     | 30.6  | 32.3  | 32.4 | 27.9      | 29.9  | 32.1  | 33.8 |
| 16.0         |          | 23.1      | 25.0  | 22.4     | 24.2  | 25.8  | 25.9 | 21.5      | 23.4  | 25.6  | 27.2 |
| 18.0         |          |           |       | 17.8     | 19.6  | 21.1  | 21.3 | 16.9      | 18.8  | 20.9  | 22.4 |
| 20.0         |          |           |       | 14.3     | 16.1  | 17.6  | 17.8 | 13.4      | 15.2  | 17.3  | 18.8 |
| 22.0         |          |           |       |          |       |       |      | 10.6      | 12.5  | 14.5  | 15.9 |
| 24.0         |          |           |       |          |       |       |      | 8.5       | 10.3  | 12.4  | 13.7 |
| 危険角度 (°)     | -        | -         | -     | -        | -     | -     | -    | -         | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 118.4    | 120.6 | 108.4 | 76.5 | 115.0     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 102.8    | 105.0 | 97.5  | 68.7 | 102.5     | 104.4 | 74.4 | 97.6     | 83.0 | 78.0 |           |      |          |
| 8.0          | 80.3     | 83.3  | 84.1  | 62.3 | 82.2      | 83.5  | 67.9 | 81.2     | 83.0 | 72.1 | 79.3      | 74.0 | 70.0     |
| 9.0          | 64.3     | 67.2  | 67.9  | 56.9 | 66.1      | 67.3  | 62.4 | 66.1     | 68.3 | 66.6 | 67.1      | 69.1 | 66.3     |
| 10.0         | 53.1     | 55.7  | 56.4  | 52.4 | 54.7      | 55.9  | 57.7 | 54.7     | 56.8 | 58.1 | 55.7      | 57.6 | 56.5     |
| 11.0         | 44.7     | 47.3  | 47.9  | 48.5 | 46.3      | 47.4  | 50.2 | 46.3     | 48.2 | 49.5 | 47.2      | 49.0 | 48.0     |
| 12.0         | 38.3     | 40.7  | 41.3  | 43.3 | 39.7      | 40.8  | 43.5 | 39.8     | 41.6 | 42.9 | 40.7      | 42.4 | 41.4     |
| 14.0         | 28.9     | 31.3  | 31.8  | 33.7 | 30.3      | 31.4  | 33.9 | 30.4     | 32.1 | 33.3 | 31.2      | 32.8 | 31.9     |
| 16.0         | 22.5     | 24.8  | 25.3  | 27.1 | 23.9      | 24.9  | 27.3 | 23.9     | 25.6 | 26.7 | 24.7      | 26.2 | 25.3     |
| 18.0         | 17.9     | 20.0  | 20.6  | 22.3 | 19.1      | 20.1  | 22.4 | 19.2     | 20.8 | 21.9 | 19.9      | 21.4 | 20.6     |
| 20.0         | 14.3     | 16.5  | 17.0  | 18.7 | 15.6      | 16.5  | 18.8 | 15.6     | 17.2 | 18.2 | 16.3      | 17.8 | 16.9     |
| 22.0         | 11.6     | 13.7  | 14.1  | 15.8 | 12.8      | 13.7  | 15.9 | 12.8     | 14.3 | 15.4 | 13.5      | 14.9 | 14.1     |
| 24.0         | 9.4      | 11.4  | 11.9  | 13.5 | 10.5      | 11.4  | 13.6 | 10.5     | 12.0 | 13.1 | 11.2      | 12.6 | 11.8     |
| 26.0         | 7.5      | 9.6   | 10.0  | 11.6 | 8.7       | 9.6   | 11.7 | 8.7      | 10.1 | 11.2 | 9.3       | 10.7 | 9.9      |
| 28.0         | 5.8      | 8.1   | 8.5   | 10.1 | 7.1       | 8.0   | 10.1 | 7.1      | 8.6  | 9.6  | 7.7       | 9.1  | 8.3      |
| 30.0         |          |       |       |      | 5.7       | 6.8   | 8.8  | 5.7      | 7.2  | 8.2  | 6.4       | 7.8  | 7.0      |
| 32.0         |          |       |       |      |           | 5.6   | 7.7  |          | 6.1  | 7.1  | 5.0       | 6.6  | 5.8      |
| 34.0         |          |       |       |      |           |       | 6.7  |          | 4.9  | 6.1  |           | 5.7  | 4.6      |
| 36.0         |          |       |       |      |           |       |      |          |      | 5.3  |           | 4.6  |          |
| 38.0         |          |       |       |      |           |       |      |          |      | 4.4  |           |      |          |
| 危険角度 (°)     | 15       | -     | -     | -    | 27        | 15    | -    | 39       | 27   | -    | 42        | 33   | 44       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

C5性能 C/W 40t O/R 5.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       |       | 22.7mブーム |       |      |       | 27.25mブーム |       |      |  |
|--------------|----------|-----------|-------|-------|----------|-------|------|-------|-----------|-------|------|--|
| 2.5          | 200.0    |           |       |       |          |       |      |       |           |       |      |  |
| 3.0          | 200.0    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |  |
| 3.5          | 184.0    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |  |
| 4.0          | 166.4    | 166.5     | 141.4 | 155.0 | 160.0    | 153.0 | 83.0 |       |           |       |      |  |
| 4.5          | 151.6    | 151.7     | 134.2 | 151.2 | 152.7    | 146.2 | 80.7 | 135.0 | 152.1     | 154.0 | 83.0 |  |
| 5.0          | 139.0    | 139.1     | 127.7 | 138.6 | 140.2    | 137.5 | 75.6 | 135.0 | 139.5     | 141.5 | 83.0 |  |
| 6.0          | 103.1    | 103.4     | 106.1 | 102.6 | 105.0    | 107.3 | 67.2 | 101.4 | 104.0     | 107.0 | 75.5 |  |
| 7.0          | 76.5     | 76.7      | 79.1  | 76.0  | 78.2     | 80.2  | 60.4 | 75.0  | 77.3      | 80.0  | 68.5 |  |
| 8.0          | 59.9     | 60.1      | 62.3  | 59.5  | 61.5     | 63.4  | 54.8 | 58.5  | 60.7      | 63.2  | 62.7 |  |
| 9.0          | 48.6     | 48.8      | 50.9  | 48.2  | 50.1     | 51.9  | 50.2 | 47.3  | 49.3      | 51.7  | 53.5 |  |
| 10.0         | 40.5     | 40.6      | 42.6  | 40.0  | 41.8     | 43.5  | 43.7 | 39.1  | 41.1      | 43.3  | 45.1 |  |
| 11.0         | 34.3     | 34.4      | 36.3  | 33.8  | 35.6     | 37.2  | 37.3 | 32.9  | 34.8      | 37.0  | 38.7 |  |
| 12.0         |          | 29.5      | 31.4  | 28.9  | 30.7     | 32.2  | 32.4 | 28.1  | 29.9      | 32.0  | 33.7 |  |
| 14.0         |          | 22.4      | 24.2  | 21.8  | 23.5     | 25.0  | 25.1 | 21.0  | 22.8      | 24.8  | 26.3 |  |
| 16.0         |          | 17.5      | 19.2  | 16.8  | 18.5     | 19.9  | 20.0 | 16.0  | 17.8      | 19.7  | 21.2 |  |
| 18.0         |          |           |       | 13.2  | 14.8     | 16.2  | 16.3 | 12.4  | 14.1      | 16.0  | 17.4 |  |
| 20.0         |          |           |       | 10.4  | 12.1     | 13.4  | 13.6 | 9.6   | 11.3      | 13.2  | 14.5 |  |
| 22.0         |          |           |       |       |          |       |      | 7.4   | 9.1       | 10.9  | 12.2 |  |
| 24.0         |          |           |       |       |          |       |      |       | 7.4       | 9.2   | 10.4 |  |
| 危険角度 (°)     | -        | -         | -     | -     | -        | -     | -    | 25    | -         | -     | -    |  |
| 伸長状態 (伸長割合%) |          |           |       |       |          |       |      |       |           |       |      |  |
| ブーム2 (%)     | 0        | 0         | 0     | 50    | 0        | 0     | 0    | 100   | 50        | 0     | 0    |  |
| ブーム3 (%)     | 0        | 50        | 0     | 50    | 50       | 0     | 0    | 50    | 50        | 50    | 0    |  |
| ブーム4 (%)     | 0        | 0         | 0     | 0     | 50       | 50    | 0    | 0     | 50        | 50    | 50   |  |
| ブーム5 (%)     | 0        | 0         | 50    | 0     | 0        | 50    | 100  | 0     | 0         | 50    | 100  |  |
| フック種類        | 200t     | 200t      | 200t  | 200t  | 200t     | 200t  | 83t  | 200t  | 200t      | 200t  | 83t  |  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60  | 2.60     | 2.60  | 1.35 | 2.60  | 2.60      | 2.60  | 1.35 |  |
| 掛数           | 19       | 16        | 14    | 14    | 16       | 14    | 7    | 12    | 14        | 14    | 7    |  |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|------|----------|------|------|-----------|------|----------|
| 5.0          | 132.0    | 135.0 | 115.0 | 83.0 |           |       |      |      |          |      |      |           |      |          |
| 6.0          | 102.8    | 106.0 | 106.8 | 76.5 | 101.4     | 103.3 | 80.0 |      |          |      |      |           |      |          |
| 7.0          | 76.2     | 79.0  | 79.8  | 68.7 | 78.0      | 79.2  | 74.4 | 78.0 | 80.2     | 78.0 |      |           |      |          |
| 8.0          | 59.7     | 62.3  | 62.9  | 62.3 | 61.3      | 62.4  | 65.2 | 61.3 | 63.3     | 64.6 | 62.3 | 64.0      | 63.0 |          |
| 9.0          | 48.4     | 50.8  | 51.4  | 53.4 | 49.9      | 51.0  | 53.6 | 49.9 | 51.8     | 53.0 | 50.8 | 52.5      | 51.5 |          |
| 10.0         | 40.2     | 42.5  | 43.1  | 45.0 | 41.6      | 42.6  | 45.2 | 41.6 | 43.4     | 44.6 | 42.5 | 44.1      | 43.2 |          |
| 11.0         | 34.0     | 36.2  | 36.8  | 38.6 | 35.3      | 36.3  | 38.8 | 35.4 | 37.1     | 38.2 | 36.2 | 37.7      | 36.8 |          |
| 12.0         | 29.1     | 31.3  | 31.8  | 33.6 | 30.4      | 31.4  | 33.7 | 30.4 | 32.1     | 33.2 | 31.2 | 32.7      | 31.9 |          |
| 14.0         | 21.9     | 24.0  | 24.5  | 26.2 | 23.2      | 24.1  | 26.4 | 23.2 | 24.8     | 25.8 | 23.9 | 25.4      | 24.6 |          |
| 16.0         | 16.9     | 19.0  | 19.4  | 21.1 | 18.1      | 19.0  | 21.2 | 18.2 | 19.7     | 20.7 | 18.9 | 20.3      | 19.5 |          |
| 18.0         | 13.3     | 15.2  | 15.7  | 17.3 | 14.4      | 15.3  | 17.4 | 14.5 | 15.9     | 16.9 | 15.1 | 16.5      | 15.7 |          |
| 20.0         | 10.4     | 12.4  | 12.8  | 14.4 | 11.6      | 12.4  | 14.5 | 11.6 | 13.0     | 14.0 | 12.2 | 13.6      | 12.8 |          |
| 22.0         | 8.2      | 10.1  | 10.6  | 12.1 | 9.3       | 10.2  | 12.2 | 9.3  | 10.7     | 11.7 | 10.0 | 11.3      | 10.5 |          |
| 24.0         | 6.4      | 8.3   | 8.8   | 10.2 | 7.5       | 8.4   | 10.3 | 7.5  | 8.9      | 9.8  | 8.1  | 9.4       | 8.7  |          |
| 26.0         |          | 6.9   | 7.3   | 8.7  | 6.0       | 6.9   | 8.8  | 6.0  | 7.4      | 8.3  | 6.6  | 7.9       | 7.2  |          |
| 28.0         |          | 5.7   | 6.0   | 7.5  |           | 5.6   | 7.5  |      | 6.1      | 7.0  | 5.3  | 6.6       | 5.9  |          |
| 30.0         |          |       |       |      |           |       | 6.4  |      | 5.0      | 5.9  | 4.0  | 5.5       | 4.8  |          |
| 32.0         |          |       |       |      |           |       | 5.5  |      |          | 5.0  |      | 4.6       |      |          |
| 34.0         |          |       |       |      |           |       | 4.8  |      |          | 4.2  |      |           |      |          |
| 危険角度 (°)     | 35       | 15    | 15    | -    | 39        | 34    | -    | 48   | 39       | 27   | 46   | 42        | 51   |          |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100  | 50       | 0    | 100  | 50        | 100  |          |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100  | 100      | 100  | 100  | 100       | 100  |          |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50   | 100      | 100  | 100  | 100       | 100  |          |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50   | 50       | 100  | 50   | 100       | 100  |          |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t | 83t      | 83t  | 83t  | 83t       | 83t  |          |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60 | 1.35     | 1.35 | 1.35 | 1.35      | 1.35 |          |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10   | 7        | 7    | 7    | 7         | 6    |          |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

D1性能 C/W 25t O/R 9.2m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 195.7    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 175.3    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 158.4    | 158.5     | 141.4 | 155.0    | 159.5 | 153.0 | 83.0 |           |       |       |      |
| 4.5          | 144.3    | 144.4     | 134.2 | 143.9    | 145.4 | 146.2 | 80.7 | 135.0     | 144.8 | 146.7 | 83.0 |
| 5.0          | 132.2    | 132.3     | 127.7 | 131.8    | 133.4 | 134.9 | 75.6 | 131.0     | 132.7 | 134.7 | 83.0 |
| 6.0          | 112.8    | 112.9     | 114.8 | 112.4    | 114.0 | 115.6 | 67.2 | 111.6     | 113.4 | 115.4 | 75.5 |
| 7.0          | 97.8     | 97.9      | 99.9  | 97.4     | 99.1  | 100.7 | 60.4 | 96.6      | 98.4  | 100.5 | 68.5 |
| 8.0          | 84.6     | 84.8      | 87.2  | 84.1     | 86.3  | 88.2  | 54.8 | 83.1      | 85.4  | 88.0  | 62.7 |
| 9.0          | 73.2     | 73.4      | 75.8  | 72.7     | 74.8  | 76.8  | 50.2 | 71.7      | 74.0  | 76.6  | 57.8 |
| 10.0         | 64.1     | 64.3      | 66.6  | 63.6     | 65.7  | 67.7  | 46.5 | 62.6      | 64.9  | 67.5  | 53.6 |
| 11.0         | 56.7     | 56.8      | 59.2  | 56.1     | 58.3  | 60.2  | 43.5 | 55.1      | 57.4  | 60.0  | 49.9 |
| 12.0         |          | 50.6      | 53.0  | 49.9     | 52.1  | 54.0  | 40.5 | 48.9      | 51.2  | 53.8  | 46.7 |
| 14.0         |          | 41.0      | 43.3  | 40.1     | 42.4  | 44.3  | 36.0 | 39.0      | 41.4  | 44.1  | 41.4 |
| 16.0         |          | 31.7      | 34.0  | 30.8     | 33.0  | 35.0  | 32.5 | 29.8      | 32.1  | 34.7  | 36.6 |
| 18.0         |          |           |       | 24.3     | 26.5  | 28.3  | 28.5 | 23.3      | 25.5  | 28.0  | 29.8 |
| 20.0         |          |           |       | 19.6     | 21.7  | 23.5  | 23.6 | 18.5      | 20.7  | 23.1  | 24.8 |
| 22.0         |          |           |       |          |       |       |      | 14.9      | 17.0  | 19.4  | 21.0 |
| 24.0         |          |           |       |          |       |       |      | 12.0      | 14.2  | 16.5  | 18.0 |
| 危険角度 (°)     | -        | -         | -     | -        | -     | -     | -    | -         | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 131.9    | 134.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 112.5    | 114.7 | 108.4 | 76.5 | 113.8     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 97.5     | 99.8  | 97.5  | 68.7 | 98.9      | 99.9  | 74.4 | 98.9     | 83.0 | 78.0 |           |      |          |
| 8.0          | 84.3     | 87.1  | 87.8  | 62.3 | 86.0      | 87.2  | 67.9 | 86.0     | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 72.9     | 75.6  | 76.4  | 56.9 | 74.6      | 75.8  | 62.4 | 74.6     | 76.7 | 66.6 | 75.6      | 70.0 | 70.0     |
| 10.0         | 63.8     | 66.5  | 67.2  | 52.4 | 65.5      | 66.7  | 57.7 | 65.5     | 67.6 | 61.8 | 66.5      | 65.2 | 67.5     |
| 11.0         | 56.3     | 59.0  | 59.7  | 48.5 | 58.0      | 59.2  | 53.6 | 58.0     | 60.1 | 57.6 | 59.0      | 60.9 | 60.0     |
| 12.0         | 50.1     | 52.8  | 53.5  | 45.1 | 51.8      | 53.0  | 50.0 | 51.8     | 53.9 | 53.9 | 52.8      | 54.7 | 53.8     |
| 14.0         | 40.3     | 43.1  | 43.7  | 39.4 | 42.0      | 43.2  | 44.1 | 42.0     | 44.1 | 45.4 | 43.0      | 44.9 | 44.0     |
| 16.0         | 31.0     | 33.7  | 34.3  | 34.7 | 32.6      | 33.8  | 36.7 | 32.6     | 34.7 | 36.0 | 33.6      | 35.5 | 34.4     |
| 18.0         | 24.5     | 27.0  | 27.6  | 29.7 | 26.0      | 27.1  | 29.9 | 26.0     | 27.9 | 29.2 | 26.9      | 28.7 | 27.7     |
| 20.0         | 19.6     | 22.1  | 22.7  | 24.7 | 21.1      | 22.2  | 24.8 | 21.1     | 22.9 | 24.2 | 22.0      | 23.7 | 22.7     |
| 22.0         | 15.9     | 18.4  | 18.9  | 20.8 | 17.3      | 18.4  | 21.0 | 17.4     | 19.1 | 20.4 | 18.2      | 19.8 | 18.9     |
| 24.0         | 13.0     | 15.4  | 15.9  | 17.8 | 14.4      | 15.4  | 17.9 | 14.4     | 16.1 | 17.3 | 15.1      | 16.8 | 15.8     |
| 26.0         | 10.7     | 13.0  | 13.5  | 15.4 | 12.0      | 13.0  | 15.4 | 12.0     | 13.6 | 14.8 | 12.7      | 14.3 | 13.4     |
| 28.0         | 8.6      | 11.1  | 11.6  | 13.4 | 10.0      | 11.0  | 13.4 | 10.0     | 11.6 | 12.8 | 10.7      | 12.3 | 11.4     |
| 30.0         |          |       |       |      | 8.2       | 9.4   | 11.7 | 8.2      | 9.9  | 11.1 | 9.0       | 10.6 | 9.7      |
| 32.0         |          |       |       |      | 6.5       | 7.9   | 10.3 | 6.5      | 8.5  | 9.6  | 7.3       | 9.1  | 8.2      |
| 34.0         |          |       |       |      |           | 6.6   | 9.1  |          | 7.1  | 8.4  | 5.8       | 7.9  | 6.7      |
| 36.0         |          |       |       |      |           |       |      |          | 5.8  | 7.3  | 4.5       | 6.6  | 5.4      |
| 38.0         |          |       |       |      |           |       |      |          | 4.7  | 6.3  |           | 5.5  | 4.3      |
| 40.0         |          |       |       |      |           |       |      |          |      |      |           | 4.5  |          |
| 危険角度 (°)     | -        | -     | -     | -    | 15        | -     | -    | 33       | -    | -    | 33        | 20   | 37       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

D2性能 C/W 25t O/R 8.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       |       | 22.7mブーム |       |      |       | 27.25mブーム |       |      |   |
|--------------|----------|-----------|-------|-------|----------|-------|------|-------|-----------|-------|------|---|
| 2.5          | 200.0    |           |       |       |          |       |      |       |           |       |      |   |
| 3.0          | 195.7    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |   |
| 3.5          | 175.3    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |   |
| 4.0          | 158.4    | 158.5     | 141.4 | 155.0 | 159.5    | 153.0 | 83.0 |       |           |       |      |   |
| 4.5          | 144.3    | 144.4     | 134.2 | 143.9 | 145.4    | 146.2 | 80.7 | 135.0 | 144.8     | 146.7 | 83.0 |   |
| 5.0          | 132.2    | 132.3     | 127.7 | 131.8 | 133.4    | 134.9 | 75.6 | 131.0 | 132.7     | 134.7 | 83.0 |   |
| 6.0          | 112.8    | 112.9     | 114.8 | 112.4 | 114.0    | 115.6 | 67.2 | 111.6 | 113.4     | 115.4 | 75.5 |   |
| 7.0          | 97.8     | 97.9      | 99.9  | 97.4  | 99.1     | 100.7 | 60.4 | 96.6  | 98.4      | 100.5 | 68.5 |   |
| 8.0          | 84.6     | 84.8      | 87.2  | 84.1  | 86.3     | 88.2  | 54.8 | 83.1  | 85.4      | 88.0  | 62.7 |   |
| 9.0          | 73.2     | 73.4      | 75.8  | 72.7  | 74.8     | 76.8  | 50.2 | 71.7  | 74.0      | 76.6  | 57.8 |   |
| 10.0         | 64.1     | 64.3      | 66.6  | 63.6  | 65.7     | 67.7  | 46.5 | 62.6  | 64.9      | 67.5  | 53.6 |   |
| 11.0         | 56.5     | 56.6      | 59.2  | 55.8  | 58.3     | 60.2  | 43.5 | 54.6  | 57.3      | 60.0  | 49.9 |   |
| 12.0         |          | 47.8      | 50.3  | 47.0  | 49.3     | 51.5  | 40.5 | 45.8  | 48.4      | 51.2  | 46.7 |   |
| 14.0         |          | 35.5      | 37.9  | 34.7  | 36.9     | 38.9  | 36.0 | 33.7  | 36.0      | 38.7  | 40.7 |   |
| 16.0         |          | 27.5      | 29.7  | 26.7  | 28.8     | 30.6  | 30.8 | 25.6  | 27.9      | 30.4  | 32.2 |   |
| 18.0         |          |           |       | 21.0  | 23.0     | 24.8  | 25.0 | 19.9  | 22.1      | 24.5  | 26.3 |   |
| 20.0         |          |           |       | 16.8  | 18.9     | 20.6  | 20.7 | 15.7  | 17.8      | 20.2  | 21.9 |   |
| 22.0         |          |           |       |       |          |       |      | 12.5  | 14.6      | 16.9  | 18.4 |   |
| 24.0         |          |           |       |       |          |       |      | 9.7   | 12.0      | 14.3  | 15.8 |   |
| 危険角度 (°)     | -        | -         | -     | -     | -        | -     | -    | -     | -         | -     | -    | - |
| 伸長状態 (伸長割合%) |          |           |       |       |          |       |      |       |           |       |      |   |
| ブーム2 (%)     | 0        | 0         | 0     | 50    | 0        | 0     | 0    | 100   | 50        | 0     | 0    |   |
| ブーム3 (%)     | 0        | 50        | 0     | 50    | 50       | 0     | 0    | 50    | 50        | 50    | 0    |   |
| ブーム4 (%)     | 0        | 0         | 0     | 0     | 50       | 50    | 0    | 0     | 50        | 50    | 50   |   |
| ブーム5 (%)     | 0        | 0         | 50    | 0     | 0        | 50    | 100  | 0     | 0         | 50    | 100  |   |
| フック種類        | 200t     | 200t      | 200t  | 200t  | 200t     | 200t  | 83t  | 200t  | 200t      | 200t  | 83t  |   |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60  | 2.60     | 2.60  | 1.35 | 2.60  | 2.60      | 2.60  | 1.35 |   |
| 掛数           | 19       | 16        | 14    | 14    | 16       | 14    | 7    | 12    | 14        | 14    | 7    |   |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 131.9    | 134.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 112.5    | 114.7 | 108.4 | 76.5 | 113.8     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 97.5     | 99.8  | 97.5  | 68.7 | 98.9      | 99.9  | 74.4 | 98.9     | 83.0 | 78.0 |           |      |          |
| 8.0          | 84.3     | 87.1  | 87.8  | 62.3 | 86.0      | 87.2  | 67.9 | 86.0     | 83.0 | 72.1 | 83.0      | 74.0 | 70.0     |
| 9.0          | 72.9     | 75.6  | 76.4  | 56.9 | 74.6      | 75.8  | 62.4 | 74.6     | 76.7 | 66.6 | 75.6      | 70.0 | 70.0     |
| 10.0         | 63.8     | 66.5  | 67.2  | 52.4 | 65.5      | 66.7  | 57.7 | 65.5     | 67.6 | 61.8 | 66.5      | 65.2 | 65.9     |
| 11.0         | 56.1     | 59.0  | 59.7  | 48.5 | 58.0      | 59.2  | 53.6 | 58.0     | 60.1 | 57.6 | 58.2      | 60.9 | 57.4     |
| 12.0         | 47.2     | 50.2  | 50.9  | 45.1 | 49.0      | 50.3  | 50.0 | 49.0     | 51.3 | 52.8 | 50.1      | 52.2 | 50.5     |
| 14.0         | 34.9     | 37.7  | 38.3  | 39.4 | 36.6      | 37.8  | 40.8 | 36.6     | 38.7 | 40.1 | 37.6      | 39.5 | 38.4     |
| 16.0         | 26.8     | 29.4  | 30.0  | 32.1 | 28.4      | 29.5  | 32.3 | 28.4     | 30.3 | 31.7 | 29.3      | 31.1 | 30.1     |
| 18.0         | 21.1     | 23.6  | 24.2  | 26.2 | 22.5      | 23.7  | 26.3 | 22.6     | 24.4 | 25.7 | 23.4      | 25.2 | 24.2     |
| 20.0         | 16.8     | 19.2  | 19.8  | 21.7 | 18.2      | 19.3  | 21.9 | 18.3     | 20.0 | 21.3 | 19.1      | 20.7 | 19.8     |
| 22.0         | 13.5     | 15.9  | 16.4  | 18.3 | 14.9      | 15.9  | 18.4 | 14.9     | 16.6 | 17.8 | 15.7      | 17.3 | 16.4     |
| 24.0         | 10.9     | 13.2  | 13.7  | 15.6 | 12.2      | 13.3  | 15.7 | 12.2     | 13.9 | 15.1 | 13.0      | 14.6 | 13.7     |
| 26.0         | 8.6      | 11.1  | 11.6  | 13.4 | 10.1      | 11.1  | 13.5 | 10.1     | 11.7 | 12.9 | 10.8      | 12.4 | 11.5     |
| 28.0         | 6.5      | 9.4   | 9.8   | 11.6 | 8.1       | 9.3   | 11.6 | 8.1      | 9.9  | 11.0 | 9.0       | 10.5 | 9.6      |
| 30.0         |          |       |       |      | 6.3       | 7.7   | 10.1 | 6.3      | 8.3  | 9.5  | 7.2       | 9.0  | 8.1      |
| 32.0         |          |       |       |      |           | 6.2   | 8.8  |          | 6.8  | 8.2  | 5.6       | 7.7  | 6.5      |
| 34.0         |          |       |       |      |           |       | 7.7  |          | 5.5  | 7.0  | 4.2       | 6.3  | 5.1      |
| 36.0         |          |       |       |      |           |       |      |          | 4.3  | 5.8  |           | 5.1  |          |
| 38.0         |          |       |       |      |           |       |      |          |      | 4.8  |           | 4.1  |          |
| 危険角度 (°)     | 15       | -     | -     | -    | 27        | 15    | -    | 39       | 18   | -    | 37        | 29   | 44       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

D3性能 C/W 25t O/R 7.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       | 27.25mブーム |       |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|-----------|-------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |           |       |       |       |      |
| 3.0          | 195.7    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 3.5          | 175.3    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 4.0          | 158.4    | 158.5     | 141.4    | 155.0 | 159.5 | 153.0 | 83.0      |       |       |       |      |
| 4.5          | 144.3    | 144.4     | 134.2    | 143.9 | 145.4 | 146.2 | 80.7      | 135.0 | 144.8 | 146.7 | 83.0 |
| 5.0          | 132.2    | 132.3     | 127.7    | 131.8 | 133.4 | 134.9 | 75.6      | 131.0 | 132.7 | 134.7 | 83.0 |
| 6.0          | 112.8    | 112.9     | 114.8    | 112.4 | 114.0 | 115.6 | 67.2      | 111.6 | 113.4 | 115.4 | 75.5 |
| 7.0          | 97.8     | 97.9      | 99.9     | 97.4  | 99.1  | 100.7 | 60.4      | 96.6  | 98.4  | 100.5 | 68.5 |
| 8.0          | 81.6     | 81.8      | 84.7     | 80.9  | 83.6  | 86.1  | 54.8      | 79.7  | 82.5  | 85.8  | 62.7 |
| 9.0          | 63.9     | 64.1      | 66.8     | 63.3  | 65.8  | 68.0  | 50.2      | 62.2  | 64.8  | 67.8  | 57.8 |
| 10.0         | 51.9     | 52.1      | 54.5     | 51.3  | 53.6  | 55.7  | 46.5      | 50.3  | 52.7  | 55.4  | 53.6 |
| 11.0         | 43.2     | 43.3      | 45.7     | 42.6  | 44.8  | 46.7  | 43.5      | 41.6  | 43.9  | 46.5  | 48.5 |
| 12.0         |          | 36.7      | 38.9     | 36.0  | 38.1  | 39.9  | 40.1      | 35.0  | 37.2  | 39.7  | 41.7 |
| 14.0         |          | 27.3      | 29.4     | 26.6  | 28.6  | 30.4  | 30.5      | 25.7  | 27.8  | 30.1  | 31.9 |
| 16.0         |          | 21.1      | 23.1     | 20.4  | 22.3  | 23.9  | 24.1      | 19.4  | 21.4  | 23.7  | 25.4 |
| 18.0         |          |           |          | 15.9  | 17.7  | 19.3  | 19.5      | 14.9  | 16.9  | 19.1  | 20.7 |
| 20.0         |          |           |          | 12.5  | 14.4  | 15.0  | 16.1      | 11.6  | 13.5  | 15.6  | 17.1 |
| 22.0         |          |           |          |       |       |       |           | 9.0   | 10.9  | 13.0  | 14.4 |
| 24.0         |          |           |          |       |       |       |           | 6.7   | 8.8   | 10.9  | 12.2 |
| 危険角度 (°)     | -        | -         | -        | -     | -     | -     | -         | -     | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |           |       |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0         | 100   | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0         | 50    | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0         | 0     | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100       | 0     | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t       | 200t  | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35      | 2.60  | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7         | 12    | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 131.9    | 134.0 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 112.5    | 114.7 | 108.4 | 76.5 | 113.8     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 97.5     | 99.8  | 97.5  | 68.7 | 98.9      | 99.9  | 74.4 | 96.6     | 83.0 | 78.0 |           |      |          |
| 8.0          | 81.2     | 84.6  | 85.5  | 62.3 | 82.8      | 84.8  | 67.9 | 79.1     | 82.3 | 72.1 | 77.0      | 74.0 | 70.0     |
| 9.0          | 63.6     | 66.7  | 67.5  | 56.9 | 65.5      | 66.9  | 62.4 | 65.5     | 67.9 | 66.6 | 65.0      | 67.8 | 63.7     |
| 10.0         | 51.6     | 54.4  | 55.2  | 52.4 | 53.3      | 54.6  | 57.7 | 53.4     | 55.5 | 57.0 | 54.4      | 56.4 | 54.9     |
| 11.0         | 42.8     | 45.5  | 46.2  | 48.5 | 44.5      | 45.7  | 48.6 | 44.5     | 46.6 | 48.0 | 45.5      | 47.4 | 46.3     |
| 12.0         | 36.2     | 38.8  | 39.4  | 41.6 | 37.8      | 38.9  | 41.8 | 37.8     | 39.8 | 41.1 | 38.8      | 40.6 | 39.5     |
| 14.0         | 26.8     | 29.3  | 29.9  | 31.8 | 28.3      | 29.4  | 32.0 | 28.3     | 30.2 | 31.4 | 29.2      | 30.9 | 29.9     |
| 16.0         | 20.5     | 22.8  | 23.4  | 25.3 | 21.9      | 22.9  | 25.4 | 21.9     | 23.7 | 24.8 | 22.7      | 24.4 | 23.4     |
| 18.0         | 16.0     | 18.2  | 18.7  | 20.6 | 17.3      | 18.3  | 20.7 | 17.3     | 19.0 | 20.1 | 18.1      | 19.7 | 18.8     |
| 20.0         | 12.6     | 14.8  | 15.3  | 17.0 | 13.8      | 14.8  | 17.1 | 13.9     | 15.5 | 16.6 | 14.6      | 16.1 | 15.3     |
| 22.0         | 9.9      | 12.1  | 12.5  | 14.3 | 11.1      | 12.1  | 14.4 | 11.2     | 12.7 | 13.8 | 11.9      | 13.4 | 12.5     |
| 24.0         | 7.8      | 9.9   | 10.4  | 12.1 | 9.0       | 9.9   | 12.1 | 9.0      | 10.5 | 11.6 | 9.7       | 11.2 | 10.3     |
| 26.0         | 5.8      | 8.2   | 8.6   | 10.3 | 7.2       | 8.2   | 10.3 | 7.3      | 8.7  | 9.8  | 7.9       | 9.3  | 8.5      |
| 28.0         |          | 6.8   | 7.2   | 8.8  | 5.6       | 6.7   | 8.8  | 5.6      | 7.2  | 8.3  | 6.4       | 7.8  | 7.0      |
| 30.0         |          |       |       |      |           |       | 7.6  |          | 6.0  | 7.0  | 4.9       | 6.6  | 5.7      |
| 32.0         |          |       |       |      |           |       | 6.5  |          | 4.7  | 5.9  |           | 5.5  | 4.3      |
| 34.0         |          |       |       |      |           |       | 5.7  |          |      | 5.0  |           | 4.3  |          |
| 36.0         |          |       |       |      |           |       |      |          |      | 4.0  |           |      |          |
| 危険角度 (°)     | 25       | -     | -     | -    | 34        | 34    | -    | 44       | 33   | 18   | 46        | 37   | 48       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

D4性能 C/W 25t O/R 6.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       |       | 22.7mブーム |       |      |       | 27.25mブーム |       |      |  |
|--------------|----------|-----------|-------|-------|----------|-------|------|-------|-----------|-------|------|--|
| 2.5          | 200.0    |           |       |       |          |       |      |       |           |       |      |  |
| 3.0          | 195.7    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |  |
| 3.5          | 175.3    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |  |
| 4.0          | 158.4    | 158.5     | 141.4 | 155.0 | 159.5    | 153.0 | 83.0 |       |           |       |      |  |
| 4.5          | 144.3    | 144.4     | 134.2 | 143.9 | 145.4    | 146.2 | 80.7 | 135.0 | 144.8     | 146.7 | 83.0 |  |
| 5.0          | 132.2    | 132.3     | 127.7 | 131.8 | 133.4    | 134.9 | 75.6 | 131.0 | 132.7     | 134.7 | 83.0 |  |
| 6.0          | 112.8    | 112.9     | 114.8 | 112.4 | 114.0    | 115.6 | 67.2 | 111.1 | 113.4     | 115.4 | 75.5 |  |
| 7.0          | 84.1     | 84.4      | 87.3  | 83.5  | 86.2     | 88.6  | 60.4 | 82.3  | 85.1      | 88.3  | 68.5 |  |
| 8.0          | 64.1     | 64.3      | 66.9  | 63.5  | 65.9     | 68.1  | 54.8 | 62.4  | 65.0      | 67.9  | 62.7 |  |
| 9.0          | 51.0     | 51.2      | 53.6  | 50.4  | 52.7     | 54.7  | 50.2 | 49.4  | 51.8      | 54.5  | 56.6 |  |
| 10.0         | 41.7     | 41.9      | 44.2  | 41.2  | 43.3     | 45.2  | 45.4 | 40.2  | 42.5      | 45.0  | 47.0 |  |
| 11.0         | 34.9     | 35.0      | 37.2  | 34.3  | 36.4     | 38.2  | 38.4 | 33.4  | 35.5      | 38.0  | 39.9 |  |
| 12.0         |          | 29.7      | 31.8  | 29.0  | 31.0     | 32.8  | 32.9 | 28.1  | 30.2      | 32.6  | 34.4 |  |
| 14.0         |          | 22.1      | 24.1  | 21.4  | 23.3     | 25.0  | 25.1 | 20.5  | 22.5      | 24.5  | 26.5 |  |
| 16.0         |          | 16.9      | 18.8  | 16.2  | 18.0     | 19.6  | 19.8 | 15.3  | 17.2      | 19.4  | 21.0 |  |
| 18.0         |          |           |       | 12.4  | 14.2     | 15.8  | 15.9 | 11.5  | 13.4      | 15.5  | 17.0 |  |
| 20.0         |          |           |       | 9.6   | 11.4     | 12.9  | 13.0 | 8.7   | 10.5      | 12.6  | 14.0 |  |
| 22.0         |          |           |       |       |          |       |      | 6.1   | 8.3       | 10.3  | 11.7 |  |
| 24.0         |          |           |       |       |          |       |      |       | 6.5       | 8.6   | 9.9  |  |
| 危険角度 (°)     | -        | -         | -     | -     | -        | -     | -    | 25    | -         | -     | -    |  |
| 伸長状態 (伸長割合%) |          |           |       |       |          |       |      |       |           |       |      |  |
| ブーム2 (%)     | 0        | 0         | 0     | 50    | 0        | 0     | 0    | 100   | 50        | 0     | 0    |  |
| ブーム3 (%)     | 0        | 50        | 0     | 50    | 50       | 0     | 0    | 50    | 50        | 50    | 0    |  |
| ブーム4 (%)     | 0        | 0         | 0     | 0     | 50       | 50    | 0    | 0     | 50        | 50    | 50   |  |
| ブーム5 (%)     | 0        | 0         | 50    | 0     | 0        | 50    | 100  | 0     | 0         | 50    | 100  |  |
| フック種類        | 200t     | 200t      | 200t  | 200t  | 200t     | 200t  | 83t  | 200t  | 200t      | 200t  | 83t  |  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60  | 2.60     | 2.60  | 1.35 | 2.60  | 2.60      | 2.60  | 1.35 |  |
| 掛数           | 19       | 16        | 14    | 14    | 16       | 14    | 7    | 12    | 14        | 14    | 7    |  |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|------|----------|------|------|-----------|------|----------|
| 5.0          | 131.9    | 134.0 | 115.0 | 83.0 |           |       |      |      |          |      |      |           |      |          |
| 6.0          | 106.0    | 110.7 | 108.4 | 76.5 | 102.2     | 104.3 | 80.0 |      |          |      |      |           |      |          |
| 7.0          | 83.2     | 87.2  | 88.1  | 68.7 | 81.4      | 83.3  | 74.4 | 77.4 | 80.6     | 78.0 |      |           |      |          |
| 8.0          | 63.8     | 66.8  | 67.6  | 62.3 | 65.6      | 67.0  | 67.9 | 63.9 | 66.9     | 68.9 | 62.5 | 65.3      | 61.1 |          |
| 9.0          | 50.7     | 53.5  | 54.2  | 56.5 | 52.4      | 53.7  | 56.7 | 52.4 | 54.6     | 56.0 | 53.0 | 55.4      | 52.1 |          |
| 10.0         | 41.4     | 44.1  | 44.8  | 46.9 | 43.0      | 44.2  | 47.1 | 43.1 | 45.1     | 46.5 | 44.1 | 45.9      | 44.9 |          |
| 11.0         | 34.6     | 37.1  | 37.7  | 39.8 | 36.1      | 37.2  | 40.0 | 36.1 | 38.1     | 39.4 | 37.1 | 38.8      | 37.8 |          |
| 12.0         | 29.2     | 31.7  | 32.3  | 34.3 | 30.7      | 31.8  | 34.5 | 30.8 | 32.6     | 33.9 | 31.6 | 33.4      | 32.4 |          |
| 14.0         | 21.6     | 23.9  | 24.5  | 26.4 | 23.0      | 24.0  | 26.5 | 23.0 | 24.8     | 26.0 | 23.8 | 25.5      | 24.5 |          |
| 16.0         | 16.3     | 18.6  | 19.1  | 20.9 | 17.7      | 18.7  | 21.1 | 17.7 | 19.4     | 20.5 | 18.5 | 20.0      | 19.1 |          |
| 18.0         | 12.5     | 14.7  | 15.2  | 16.9 | 13.8      | 14.8  | 17.1 | 13.8 | 15.4     | 16.5 | 14.6 | 16.1      | 15.2 |          |
| 20.0         | 9.6      | 11.8  | 12.2  | 13.9 | 10.9      | 11.8  | 14.1 | 10.9 | 12.4     | 13.5 | 11.6 | 13.1      | 12.2 |          |
| 22.0         | 7.3      | 9.5   | 9.9   | 11.6 | 8.5       | 9.5   | 11.7 | 8.6  | 10.1     | 11.2 | 9.3  | 10.7      | 9.9  |          |
| 24.0         |          | 7.6   | 8.1   | 9.7  | 6.7       | 7.6   | 9.8  | 6.7  | 8.2      | 9.3  | 7.4  | 8.8       | 8.0  |          |
| 26.0         |          | 6.1   | 6.6   | 8.2  |           | 6.1   | 8.2  |      | 6.7      | 7.7  | 5.7  | 7.2       | 6.4  |          |
| 28.0         |          |       |       | 6.9  |           |       | 6.9  |      | 5.2      | 6.4  | 4.1  | 5.9       | 4.9  |          |
| 30.0         |          |       |       |      |           |       | 5.8  |      |          | 5.3  |      | 4.7       |      |          |
| 32.0         |          |       |       |      |           |       | 4.9  |      |          | 4.1  |      |           |      |          |
| 危険角度 (°)     | 41       | 25    | 25    | -    | 44        | 39    | 15   | 51   | 44       | 39   | 49   | 46        | 54   |          |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100  | 50       | 0    | 100  | 50        | 100  |          |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100  | 100      | 100  | 100  | 100       | 100  |          |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50   | 100      | 100  | 100  | 100       | 100  |          |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50   | 50       | 100  | 50   | 100       | 100  |          |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t | 83t      | 83t  | 83t  | 83t       | 83t  |          |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60 | 1.35     | 1.35 | 1.35 | 1.35      | 1.35 |          |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10   | 7        | 7    | 7    | 7         | 6    |          |

(単位 : ton)





# 13.6m — 50.0m

# メインブーム

D5性能 C/W 25t O/R 5.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 195.7    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 175.3    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 158.4    | 158.5     | 141.4 | 155.0    | 159.5 | 153.0 | 83.0 |           |       |       |      |
| 4.5          | 144.3    | 144.4     | 134.2 | 143.9    | 145.4 | 146.2 | 80.7 | 134.0     | 138.3 | 143.2 | 83.0 |
| 5.0          | 122.6    | 122.9     | 126.2 | 121.9    | 124.9 | 127.7 | 75.6 | 113.4     | 117.4 | 122.0 | 83.0 |
| 6.0          | 82.0     | 82.2      | 85.0  | 81.4     | 83.9  | 86.2  | 67.2 | 80.3      | 82.9  | 85.9  | 75.5 |
| 7.0          | 60.3     | 60.5      | 62.9  | 59.5     | 62.0  | 64.0  | 60.4 | 58.8      | 61.1  | 63.8  | 66.0 |
| 8.0          | 46.8     | 47.0      | 49.2  | 46.3     | 48.3  | 50.2  | 50.4 | 45.4      | 47.5  | 50.0  | 52.0 |
| 9.0          | 37.6     | 37.7      | 39.8  | 37.1     | 39.0  | 40.8  | 40.9 | 36.2      | 38.3  | 40.6  | 42.5 |
| 10.0         | 30.9     | 31.0      | 33.0  | 30.4     | 32.3  | 34.0  | 34.1 | 29.6      | 31.5  | 33.8  | 35.5 |
| 11.0         | 25.9     | 26.0      | 27.9  | 25.4     | 27.2  | 28.8  | 28.9 | 24.5      | 26.4  | 28.6  | 30.3 |
| 12.0         |          | 22.0      | 23.9  | 21.4     | 23.2  | 24.7  | 24.9 | 20.6      | 22.4  | 24.5  | 26.2 |
| 14.0         |          | 16.2      | 18.0  | 15.6     | 17.3  | 18.8  | 18.9 | 14.8      | 16.6  | 18.6  | 20.1 |
| 16.0         |          | 12.2      | 14.0  | 11.6     | 13.2  | 14.7  | 14.8 | 10.8      | 12.5  | 14.5  | 15.9 |
| 18.0         |          |           |       | 8.6      | 10.3  | 11.7  | 11.8 | 7.8       | 9.5   | 11.4  | 12.8 |
| 20.0         |          |           |       | 6.4      | 8.0   | 9.4   | 9.5  |           | 7.2   | 9.1   | 10.4 |
| 22.0         |          |           |       |          |       |       |      |           |       | 7.3   | 8.6  |
| 24.0         |          |           |       |          |       |       |      |           |       | 5.9   | 7.1  |
| 危険角度 (°)     | -        | -         | -     | -        | -     | -     | -    | 43        | 34    | -     | -    |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       | 36.35mブーム |      |      |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|-----------|------|------|------|----------|------|------|-----------|------|----------|
| 5.0          | 107.2    | 111.9 | 113.1 | 83.0      |      |      |      |          |      |      |           |      |          |
| 6.0          | 81.7     | 84.8  | 85.7  | 76.5      | 79.8 | 81.6 | 80.0 |          |      |      |           |      |          |
| 7.0          | 60.0     | 62.8  | 63.6  | 65.9      | 61.7 | 63.0 | 66.1 | 61.2     | 63.9 | 65.4 |           |      |          |
| 8.0          | 46.5     | 49.1  | 49.8  | 51.9      | 48.1 | 49.3 | 52.1 | 48.1     | 50.1 | 51.5 | 49.1      | 50.9 | 49.0     |
| 9.0          | 37.3     | 39.7  | 40.4  | 42.4      | 38.8 | 39.9 | 42.6 | 38.8     | 40.7 | 41.9 | 39.7      | 41.4 | 40.5     |
| 10.0         | 30.6     | 33.0  | 33.5  | 35.5      | 32.1 | 33.1 | 35.6 | 32.1     | 33.9 | 35.0 | 32.9      | 34.6 | 33.6     |
| 11.0         | 25.6     | 27.8  | 28.4  | 30.2      | 26.9 | 27.9 | 30.4 | 27.0     | 28.7 | 29.8 | 27.8      | 29.3 | 28.4     |
| 12.0         | 21.6     | 23.8  | 24.3  | 26.1      | 22.9 | 23.9 | 26.2 | 22.9     | 24.6 | 25.7 | 23.7      | 25.2 | 24.4     |
| 14.0         | 15.8     | 17.8  | 18.4  | 20.0      | 17.0 | 17.9 | 20.2 | 17.0     | 18.6 | 19.7 | 17.8      | 19.2 | 18.4     |
| 16.0         | 11.7     | 13.7  | 14.2  | 15.8      | 12.9 | 13.8 | 16.0 | 12.9     | 14.4 | 15.5 | 13.6      | 15.0 | 14.2     |
| 18.0         | 8.7      | 10.7  | 11.1  | 12.7      | 9.9  | 10.7 | 12.8 | 9.9      | 11.4 | 12.4 | 10.6      | 11.9 | 11.2     |
| 20.0         | 6.4      | 8.4   | 8.8   | 10.3      | 7.5  | 8.4  | 10.5 | 7.6      | 9.0  | 10.0 | 8.2       | 9.6  | 8.8      |
| 22.0         |          | 6.5   | 7.0   | 8.5       | 5.7  | 6.6  | 8.6  | 5.7      | 7.1  | 8.1  | 6.4       | 7.7  | 6.9      |
| 24.0         |          |       |       | 7.0       |      |      | 7.1  |          | 5.6  | 6.6  | 4.9       | 6.2  | 5.4      |
| 26.0         |          |       |       | 5.7       |      |      | 5.8  |          | 4.3  | 5.3  |           | 4.9  | 4.0      |
| 28.0         |          |       |       | 4.7       |      |      | 4.8  |          |      | 4.3  |           |      |          |
| 危険角度 (°)     | 47       | 41    | 41    | -         | 49   | 49   | 34   | 54       | 48   | 44   | 56        | 52   | 57       |
| 伸長状態 (伸長割合%) |          |       |       |           |      |      |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0         | 100  | 50   | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0         | 50   | 100  | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100       | 50   | 50   | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100       | 50   | 50   | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t       | 200t | 200t | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35      | 2.60 | 2.60 | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7         | 10   | 10   | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

E1性能 C/W 10t O/R 9.2m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       | 27.25mブーム |       |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|-----------|-------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |           |       |       |       |      |
| 3.0          | 185.9    | 175.0     | 150.0    |       |       |       |           |       |       |       |      |
| 3.5          | 166.4    | 166.5     | 150.0    |       |       |       |           |       |       |       |      |
| 4.0          | 150.3    | 150.4     | 141.4    | 149.9 | 151.5 | 152.9 | 83.0      |       |       |       |      |
| 4.5          | 136.8    | 136.9     | 134.2    | 136.4 | 138.0 | 139.5 | 80.7      | 135.0 | 137.4 | 139.3 | 83.0 |
| 5.0          | 125.3    | 125.4     | 127.2    | 124.9 | 126.5 | 128.1 | 75.6      | 124.2 | 125.9 | 127.9 | 83.0 |
| 6.0          | 106.7    | 106.9     | 108.8    | 106.3 | 108.1 | 109.6 | 67.2      | 105.3 | 107.4 | 109.4 | 75.5 |
| 7.0          | 88.9     | 89.1      | 91.5     | 88.4  | 90.6  | 92.6  | 60.4      | 87.4  | 89.7  | 92.4  | 68.5 |
| 8.0          | 75.5     | 75.7      | 78.1     | 75.0  | 77.2  | 79.2  | 54.8      | 74.0  | 76.3  | 79.0  | 62.7 |
| 9.0          | 65.1     | 65.3      | 67.7     | 64.6  | 66.8  | 68.8  | 50.2      | 63.6  | 65.9  | 68.6  | 57.8 |
| 10.0         | 56.8     | 57.0      | 59.4     | 56.3  | 58.5  | 60.4  | 46.5      | 55.3  | 57.6  | 60.2  | 53.6 |
| 11.0         | 49.9     | 50.1      | 52.6     | 49.2  | 51.7  | 53.6  | 43.5      | 47.9  | 50.8  | 53.4  | 49.9 |
| 12.0         |          | 41.6      | 44.3     | 40.8  | 43.3  | 45.5  | 40.5      | 39.6  | 42.3  | 45.3  | 46.7 |
| 14.0         |          | 30.1      | 32.6     | 29.3  | 31.6  | 33.7  | 33.9      | 28.2  | 30.7  | 33.4  | 35.5 |
| 16.0         |          | 22.8      | 25.1     | 21.9  | 24.1  | 26.0  | 26.2      | 20.9  | 23.2  | 25.8  | 27.7 |
| 18.0         |          |           |          | 16.8  | 18.9  | 20.7  | 20.9      | 15.7  | 18.0  | 20.4  | 22.2 |
| 20.0         |          |           |          | 13.0  | 15.1  | 16.9  | 17.0      | 11.9  | 14.1  | 16.5  | 18.2 |
| 22.0         |          |           |          |       |       |       |           | 8.7   | 11.2  | 13.6  | 15.2 |
| 24.0         |          |           |          |       |       |       |           | 5.9   | 8.9   | 11.3  | 12.8 |
| 危険角度 (°)     | -        | -         | -        | -     | -     | -     | -         | -     | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |           |       |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0         | 100   | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0         | 50    | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0         | 0     | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100       | 0     | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t       | 200t  | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35      | 2.60  | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7         | 12    | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 125.1    | 127.2 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 106.5    | 108.7 | 108.4 | 76.5 | 107.9     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 88.7     | 91.4  | 92.1  | 68.7 | 90.4      | 91.6  | 74.4 | 90.4     | 83.0 | 78.0 |           |      |          |
| 8.0          | 75.3     | 78.0  | 78.7  | 62.3 | 77.0      | 78.2  | 67.9 | 77.0     | 79.1 | 72.1 | 78.0      | 74.0 | 70.0     |
| 9.0          | 64.9     | 67.6  | 68.3  | 56.9 | 66.5      | 67.8  | 62.4 | 66.6     | 68.7 | 66.6 | 67.6      | 69.5 | 68.2     |
| 10.0         | 56.6     | 59.3  | 60.0  | 52.4 | 58.2      | 59.4  | 57.7 | 58.3     | 60.3 | 61.7 | 58.9      | 61.1 | 57.9     |
| 11.0         | 49.5     | 52.5  | 53.1  | 48.5 | 51.4      | 52.6  | 53.6 | 50.9     | 53.5 | 54.9 | 50.4      | 53.3 | 49.8     |
| 12.0         | 41.0     | 44.2  | 44.9  | 45.1 | 42.9      | 44.3  | 47.7 | 43.0     | 45.3 | 46.9 | 43.7      | 46.3 | 43.4     |
| 14.0         | 29.5     | 32.4  | 33.1  | 35.4 | 31.3      | 32.5  | 35.6 | 31.3     | 33.4 | 34.9 | 32.3      | 34.3 | 33.2     |
| 16.0         | 22.1     | 24.8  | 25.4  | 27.6 | 23.7      | 24.9  | 27.8 | 23.7     | 25.7 | 27.1 | 24.7      | 26.5 | 25.5     |
| 18.0         | 16.9     | 19.5  | 20.1  | 22.1 | 18.4      | 19.6  | 22.3 | 18.4     | 20.3 | 21.7 | 19.3      | 21.1 | 20.1     |
| 20.0         | 13.0     | 15.5  | 16.1  | 18.1 | 14.5      | 15.6  | 18.2 | 14.5     | 16.4 | 17.6 | 15.4      | 17.1 | 16.1     |
| 22.0         | 10.1     | 12.5  | 13.1  | 15.0 | 11.5      | 12.6  | 15.1 | 11.5     | 13.3 | 14.5 | 12.3      | 14.0 | 13.0     |
| 24.0         | 7.3      | 10.2  | 10.7  | 12.6 | 9.1       | 10.2  | 12.7 | 9.2      | 10.9 | 12.1 | 9.9       | 11.6 | 10.6     |
| 26.0         |          | 8.3   | 8.8   | 10.6 | 6.8       | 8.3   | 10.7 | 6.9      | 8.9  | 10.1 | 7.8       | 9.6  | 8.6      |
| 28.0         |          | 6.4   | 7.0   | 9.0  |           | 6.3   | 9.0  |          | 7.1  | 8.4  | 5.9       | 7.9  | 6.8      |
| 30.0         |          |       |       |      |           |       | 7.7  |          | 5.5  | 7.0  | 4.2       | 6.4  | 5.1      |
| 32.0         |          |       |       |      |           |       | 6.5  |          | 4.1  | 5.6  |           | 4.9  |          |
| 34.0         |          |       |       |      |           |       | 5.3  |          |      | 4.4  |           |      |          |
| 危険角度 (°)     | 35       | 15    | -     | -    | 39        | 34    | -    | 48       | 33   | 27   | 46        | 42   | 51       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

E2性能 C/W 10t O/R 8.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |      |           |       |       |      |
| 3.0          | 185.9    | 175.0     | 150.0    |       |       |       |      |           |       |       |      |
| 3.5          | 166.4    | 166.5     | 150.0    |       |       |       |      |           |       |       |      |
| 4.0          | 150.3    | 150.4     | 141.4    | 149.9 | 151.5 | 152.9 | 83.0 |           |       |       |      |
| 4.5          | 136.8    | 136.9     | 134.2    | 136.4 | 138.0 | 139.5 | 80.7 | 135.0     | 137.4 | 139.3 | 83.0 |
| 5.0          | 125.3    | 125.4     | 127.2    | 124.9 | 126.5 | 128.1 | 75.6 | 124.2     | 125.9 | 127.9 | 83.0 |
| 6.0          | 106.7    | 106.9     | 108.8    | 106.3 | 108.1 | 109.6 | 67.2 | 105.3     | 107.4 | 109.4 | 75.5 |
| 7.0          | 88.9     | 89.1      | 91.5     | 88.4  | 90.6  | 92.6  | 60.4 | 87.4      | 89.7  | 92.4  | 68.5 |
| 8.0          | 75.5     | 75.7      | 78.1     | 75.0  | 77.2  | 79.2  | 54.8 | 74.0      | 76.3  | 79.0  | 62.7 |
| 9.0          | 65.0     | 65.2      | 67.7     | 64.3  | 66.8  | 68.8  | 50.2 | 62.9      | 65.9  | 68.6  | 57.8 |
| 10.0         | 51.6     | 51.8      | 54.7     | 50.9  | 53.6  | 56.0  | 46.5 | 49.7      | 52.5  | 55.7  | 53.6 |
| 11.0         | 42.2     | 42.3      | 45.0     | 41.5  | 44.0  | 46.2  | 43.5 | 40.3      | 43.0  | 46.0  | 48.3 |
| 12.0         |          | 35.3      | 37.8     | 34.5  | 36.9  | 39.0  | 39.2 | 33.4      | 35.9  | 38.8  | 41.0 |
| 14.0         |          | 25.6      | 27.9     | 24.8  | 27.0  | 29.0  | 29.1 | 23.7      | 26.1  | 28.7  | 30.7 |
| 16.0         |          | 19.3      | 21.5     | 18.4  | 20.5  | 22.4  | 22.6 | 17.4      | 19.6  | 22.1  | 24.0 |
| 18.0         |          |           |          | 13.9  | 16.0  | 17.8  | 17.9 | 12.9      | 15.1  | 17.5  | 19.2 |
| 20.0         |          |           |          | 10.6  | 12.7  | 14.4  | 14.5 | 9.3       | 11.7  | 14.0  | 15.7 |
| 22.0         |          |           |          |       |       |       |      | 6.2       | 9.1   | 11.4  | 13.0 |
| 24.0         |          |           |          |       |       |       |      |           | 6.6   | 9.4   | 10.8 |
| 危険角度 (°)     | -        | -         | -        | -     | -     | -     | -    | 25        | -     | -     | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 125.1    | 127.2 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 106.5    | 108.7 | 108.4 | 76.5 | 107.9     | 105.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 88.7     | 91.4  | 92.1  | 68.7 | 90.4      | 91.6  | 74.4 | 90.4     | 83.0 | 78.0 |           |      |          |
| 8.0          | 75.3     | 78.0  | 78.7  | 62.3 | 77.0      | 78.2  | 67.9 | 73.6     | 77.1 | 72.1 | 71.6      | 74.0 |          |
| 9.0          | 63.9     | 67.6  | 68.3  | 56.9 | 63.4      | 65.4  | 62.4 | 60.6     | 63.9 | 66.2 | 59.5      | 62.5 |          |
| 10.0         | 51.2     | 54.5  | 55.4  | 52.4 | 53.1      | 54.7  | 57.7 | 50.9     | 54.1 | 56.2 | 50.3      | 53.2 |          |
| 11.0         | 41.8     | 44.9  | 45.7  | 48.2 | 43.6      | 45.0  | 48.4 | 43.4     | 46.1 | 47.7 | 43.1      | 45.9 |          |
| 12.0         | 34.7     | 37.7  | 38.4  | 40.9 | 36.5      | 37.8  | 41.1 | 36.6     | 38.8 | 40.3 | 37.4      | 39.7 |          |
| 14.0         | 25.0     | 27.7  | 28.4  | 30.6 | 26.6      | 27.9  | 30.8 | 26.7     | 28.4 | 30.1 | 27.7      | 29.6 |          |
| 16.0         | 18.6     | 21.2  | 21.8  | 23.9 | 20.1      | 21.3  | 24.1 | 20.2     | 22.1 | 23.4 | 21.1      | 22.9 |          |
| 18.0         | 14.0     | 16.5  | 17.1  | 19.1 | 15.5      | 16.6  | 19.3 | 15.5     | 17.4 | 18.7 | 16.4      | 18.1 |          |
| 20.0         | 10.6     | 13.1  | 13.6  | 15.6 | 12.1      | 13.1  | 15.7 | 12.1     | 13.9 | 15.1 | 12.9      | 14.6 |          |
| 22.0         | 7.6      | 10.4  | 11.0  | 12.8 | 9.4       | 10.5  | 13.0 | 9.4      | 11.2 | 12.4 | 10.2      | 11.9 |          |
| 24.0         |          | 8.3   | 8.8   | 10.7 | 6.9       | 8.3   | 10.8 | 7.0      | 9.0  | 10.2 | 8.0       | 9.7  |          |
| 26.0         |          | 6.3   | 6.9   | 8.9  |           | 6.2   | 9.0  |          | 7.1  | 8.4  | 5.8       | 7.9  |          |
| 28.0         |          |       |       | 7.5  |           |       | 7.5  |          | 5.3  | 6.9  | 4.1       | 6.2  |          |
| 30.0         |          |       |       |      |           |       | 6.2  |          |      | 5.4  |           | 4.7  |          |
| 32.0         |          |       |       |      |           |       | 4.9  |          |      | 4.1  |           |      |          |
| 危険角度 (°)     | 41       | 25    | 25    | -    | 44        | 39    | 15   | 51       | 44   | 33   | 49        | 46   | 54       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

E3性能 C/W 10t O/R 7.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       |       | 22.7mブーム |       |      |       | 27.25mブーム |       |      |  |
|--------------|----------|-----------|-------|-------|----------|-------|------|-------|-----------|-------|------|--|
| 2.5          | 200.0    |           |       |       |          |       |      |       |           |       |      |  |
| 3.0          | 185.9    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |  |
| 3.5          | 166.4    | 166.5     | 150.0 |       |          |       |      |       |           |       |      |  |
| 4.0          | 150.3    | 150.4     | 141.4 | 149.9 | 151.5    | 152.9 | 83.0 |       |           |       |      |  |
| 4.5          | 136.8    | 136.9     | 134.2 | 136.4 | 138.0    | 139.5 | 80.7 | 135.0 | 137.4     | 139.3 | 83.0 |  |
| 5.0          | 125.3    | 125.4     | 127.2 | 124.9 | 126.5    | 128.1 | 75.6 | 124.2 | 125.9     | 127.9 | 83.0 |  |
| 6.0          | 106.7    | 106.9     | 108.8 | 106.3 | 108.1    | 109.6 | 67.2 | 105.3 | 107.4     | 109.4 | 75.5 |  |
| 7.0          | 83.9     | 84.2      | 87.6  | 83.2  | 86.3     | 89.1  | 60.4 | 81.6  | 85.1      | 88.8  | 68.5 |  |
| 8.0          | 61.6     | 61.8      | 64.8  | 61.0  | 63.7     | 66.1  | 54.8 | 59.7  | 62.6      | 65.8  | 62.7 |  |
| 9.0          | 47.7     | 47.9      | 50.6  | 47.1  | 49.6     | 51.8  | 50.2 | 46.0  | 48.6      | 51.6  | 53.9 |  |
| 10.0         | 38.3     | 38.4      | 40.9  | 37.7  | 40.0     | 42.1  | 42.2 | 36.6  | 39.1      | 41.8  | 44.0 |  |
| 11.0         | 31.4     | 31.6      | 33.9  | 30.8  | 33.0     | 35.0  | 35.1 | 29.8  | 32.1      | 34.8  | 36.8 |  |
| 12.0         |          | 26.3      | 28.6  | 25.6  | 27.7     | 29.6  | 29.8 | 24.7  | 26.9      | 29.4  | 31.3 |  |
| 14.0         |          | 19.0      | 21.1  | 18.3  | 20.3     | 22.0  | 22.2 | 17.4  | 19.5      | 21.8  | 23.6 |  |
| 16.0         |          | 14.1      | 16.1  | 13.4  | 15.3     | 16.9  | 17.1 | 12.5  | 14.5      | 16.7  | 18.4 |  |
| 18.0         |          |           |       | 9.9   | 11.7     | 13.3  | 13.5 | 8.9   | 10.9      | 13.1  | 14.7 |  |
| 20.0         |          |           |       | 7.3   | 9.1      | 10.7  | 10.8 | 5.9   | 8.2       | 10.4  | 11.9 |  |
| 22.0         |          |           |       |       |          |       |      |       | 6.0       | 8.3   | 9.7  |  |
| 24.0         |          |           |       |       |          |       |      |       |           | 6.7   | 8.0  |  |
| 危険角度 (°)     | -        | -         | -     | -     | -        | -     | -    | 34    | 25        | -     | -    |  |
| 伸長状態 (伸長割合%) |          |           |       |       |          |       |      |       |           |       |      |  |
| ブーム2 (%)     | 0        | 0         | 0     | 50    | 0        | 0     | 0    | 100   | 50        | 0     | 0    |  |
| ブーム3 (%)     | 0        | 50        | 0     | 50    | 50       | 0     | 0    | 50    | 50        | 50    | 0    |  |
| ブーム4 (%)     | 0        | 0         | 0     | 0     | 50       | 50    | 0    | 0     | 50        | 50    | 50   |  |
| ブーム5 (%)     | 0        | 0         | 50    | 0     | 0        | 50    | 100  | 0     | 0         | 50    | 100  |  |
| フック種類        | 200t     | 200t      | 200t  | 200t  | 200t     | 200t  | 83t  | 200t  | 200t      | 200t  | 83t  |  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60  | 2.60     | 2.60  | 1.35 | 2.60  | 2.60      | 2.60  | 1.35 |  |
| 掛数           | 19       | 16        | 14    | 14    | 16       | 14    | 7    | 12    | 14        | 14    | 7    |  |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 125.1    | 127.2 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 103.1    | 108.4 | 108.4 | 76.5 | 99.1      | 101.4 | 80.0 |          |      |      |           |      |          |
| 7.0          | 78.7     | 83.4  | 84.7  | 68.7 | 76.9      | 79.0  | 74.4 | 72.7     | 76.2 | 78.0 |           |      |          |
| 8.0          | 61.3     | 64.7  | 65.5  | 62.3 | 61.8      | 63.7  | 67.9 | 58.8     | 62.1 | 64.3 | 57.6      | 60.5 | 56.2     |
| 9.0          | 47.4     | 50.5  | 51.3  | 53.8 | 49.3      | 50.7  | 54.0 | 48.7     | 51.7 | 53.3 | 48.1      | 50.8 | 47.3     |
| 10.0         | 37.9     | 40.8  | 41.5  | 43.9 | 39.7      | 41.0  | 44.1 | 39.7     | 41.9 | 43.4 | 40.7      | 42.8 | 40.3     |
| 11.0         | 31.1     | 33.8  | 34.5  | 36.7 | 32.7      | 33.9  | 36.9 | 32.8     | 34.8 | 36.2 | 33.8      | 35.6 | 34.6     |
| 12.0         | 25.9     | 28.5  | 29.1  | 31.2 | 27.4      | 28.6  | 31.4 | 27.5     | 29.4 | 30.8 | 28.4      | 30.2 | 29.2     |
| 14.0         | 18.5     | 20.9  | 21.5  | 23.5 | 20.0      | 21.0  | 23.7 | 20.0     | 21.8 | 23.1 | 20.9      | 22.6 | 21.6     |
| 16.0         | 13.5     | 15.9  | 16.4  | 18.3 | 14.9      | 16.0  | 18.5 | 15.0     | 16.7 | 17.9 | 15.8      | 17.4 | 16.5     |
| 18.0         | 10.0     | 12.2  | 12.7  | 14.6 | 11.3      | 12.3  | 14.7 | 11.3     | 13.0 | 14.1 | 12.1      | 13.7 | 12.8     |
| 20.0         | 7.3      | 9.5   | 10.0  | 11.7 | 8.6       | 9.6   | 11.9 | 8.6      | 10.2 | 11.3 | 9.3       | 10.9 | 10.0     |
| 22.0         |          | 7.4   | 7.9   | 9.6  | 6.5       | 7.4   | 9.7  | 6.5      | 8.0  | 9.1  | 7.2       | 8.7  | 7.8      |
| 24.0         |          | 5.6   | 6.2   | 7.8  |           | 5.6   | 7.9  |          | 6.3  | 7.4  | 5.3       | 6.9  | 6.1      |
| 26.0         |          |       |       | 6.4  |           |       | 6.5  |          | 4.6  | 5.9  |           | 5.5  | 4.3      |
| 28.0         |          |       |       | 5.3  |           |       | 5.3  |          |      | 4.6  |           | 4.0  |          |
| 30.0         |          |       |       |      |           |       | 4.1  |          |      |      |           |      |          |
| 危険角度 (°)     | 47       | 35    | 35    | -    | 49        | 44    | 27   | 54       | 48   | 44   | 56        | 49   | 57       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

E4性能 C/W 10t O/R 6.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム | 22.7mブーム |       |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|----------|-------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |          |       |       |       |      |           |       |       |      |
| 3.0          | 185.9    | 175.0     | 150.0    |       |       |       |      |           |       |       |      |
| 3.5          | 166.4    | 166.5     | 150.0    |       |       |       |      |           |       |       |      |
| 4.0          | 150.3    | 150.4     | 141.4    | 149.9 | 151.5 | 152.9 | 83.0 |           |       |       |      |
| 4.5          | 136.8    | 136.9     | 134.2    | 136.4 | 138.0 | 139.5 | 80.7 | 135.0     | 137.4 | 139.3 | 83.0 |
| 5.0          | 125.3    | 125.4     | 127.2    | 124.9 | 126.5 | 128.1 | 75.6 | 113.5     | 118.1 | 123.4 | 83.0 |
| 6.0          | 89.6     | 89.9      | 93.4     | 88.9  | 92.0  | 94.9  | 67.2 | 82.0      | 86.0  | 90.7  | 75.5 |
| 7.0          | 62.9     | 63.1      | 66.0     | 62.2  | 64.9  | 67.4  | 60.4 | 61.0      | 63.8  | 67.1  | 68.5 |
| 8.0          | 47.3     | 47.5      | 50.1     | 46.7  | 49.1  | 51.3  | 51.5 | 45.6      | 48.1  | 51.0  | 53.4 |
| 9.0          | 37.0     | 37.2      | 39.7     | 36.0  | 38.7  | 40.8  | 40.9 | 35.5      | 37.8  | 40.5  | 42.7 |
| 10.0         | 29.9     | 30.0      | 32.3     | 29.3  | 31.4  | 33.4  | 33.5 | 28.3      | 30.6  | 33.1  | 35.2 |
| 11.0         | 24.5     | 24.6      | 26.8     | 24.0  | 26.0  | 27.8  | 28.0 | 23.0      | 25.2  | 27.6  | 29.5 |
| 12.0         |          | 20.5      | 22.6     | 19.9  | 21.8  | 23.6  | 23.7 | 18.9      | 21.0  | 23.4  | 25.2 |
| 14.0         |          | 14.6      | 16.6     | 13.9  | 15.8  | 17.5  | 17.6 | 13.0      | 15.0  | 17.3  | 19.0 |
| 16.0         |          | 10.6      | 12.5     | 9.9   | 11.7  | 13.3  | 13.4 | 9.0       | 10.9  | 13.1  | 14.7 |
| 18.0         |          |           |          | 6.9   | 8.8   | 10.3  | 10.4 | 5.6       | 8.0   | 10.1  | 11.6 |
| 20.0         |          |           |          |       | 6.6   | 8.1   | 8.2  |           |       | 7.8   | 9.2  |
| 22.0         |          |           |          |       |       |       |      |           |       | 6.0   | 7.4  |
| 24.0         |          |           |          |       |       |       |      |           |       |       | 6.0  |
| 危険角度 (°)     | -        | -         | -        | 25    | -     | -     | -    | 43        | 43    | 25    | -    |
| 伸長状態 (伸長割合%) |          |           |          |       |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0        | 50    | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0        | 50    | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0        | 0     | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50       | 0     | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t     | 200t  | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60     | 2.60  | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14       | 14    | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |      |      |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|------|------|------|----------|------|------|-----------|------|----------|
| 5.0          | 106.4    | 111.7 | 113.1 | 83.0 |           |      |      |      |          |      |      |           |      |          |
| 6.0          | 78.4     | 83.2  | 84.4  | 76.5 | 76.2      | 78.2 | 80.0 |      |          |      |      |           |      |          |
| 7.0          | 60.8     | 65.1  | 66.2  | 68.7 | 59.9      | 61.8 | 66.5 | 56.8 | 60.0     | 62.1 |      |           |      |          |
| 8.0          | 47.0     | 50.0  | 50.8  | 53.3 | 48.5      | 50.2 | 53.5 | 46.2 | 49.3     | 51.3 | 45.5 | 48.2      | 44.6 |          |
| 9.0          | 36.8     | 39.6  | 40.3  | 42.6 | 38.5      | 39.7 | 42.8 | 38.3 | 40.7     | 42.1 | 38.0 | 40.6      | 37.6 |          |
| 10.0         | 29.5     | 32.2  | 32.9  | 35.1 | 31.2      | 32.4 | 35.3 | 31.2 | 33.2     | 34.6 | 32.2 | 34.0      | 32.0 |          |
| 11.0         | 24.2     | 26.7  | 27.4  | 29.5 | 25.7      | 26.9 | 29.6 | 25.8 | 27.7     | 29.0 | 26.7 | 28.5      | 27.5 |          |
| 12.0         | 20.1     | 22.5  | 23.1  | 25.1 | 21.5      | 22.6 | 25.3 | 21.6 | 23.4     | 24.7 | 22.5 | 24.2      | 23.2 |          |
| 14.0         | 14.1     | 16.4  | 17.0  | 18.9 | 15.5      | 16.5 | 19.0 | 15.5 | 17.3     | 18.5 | 16.4 | 18.0      | 17.1 |          |
| 16.0         | 10.0     | 12.3  | 12.8  | 14.6 | 11.4      | 12.4 | 14.8 | 11.4 | 13.1     | 14.2 | 12.2 | 13.7      | 12.8 |          |
| 18.0         | 7.1      | 9.2   | 9.7   | 11.5 | 8.3       | 9.3  | 11.6 | 8.4  | 10.0     | 11.1 | 9.1  | 10.6      | 9.8  |          |
| 20.0         |          | 6.9   | 7.4   | 9.1  | 5.9       | 7.0  | 9.3  | 6.0  | 7.6      | 8.7  | 6.8  | 8.3       | 7.4  |          |
| 22.0         |          |       | 5.6   | 7.3  |           |      | 7.4  |      | 5.8      | 6.9  | 4.6  | 6.4       |      |          |
| 24.0         |          |       |       | 5.8  |           |      | 5.9  |      |          | 5.4  |      | 4.8       |      |          |
| 26.0         |          |       |       | 4.5  |           |      | 4.6  |      |          |      |      |           |      |          |
| 危険角度 (°)     | 52       | 47    | 41    | 25   | 53        | 53   | 39   | 60   | 54       | 51   | 59   | 56        | 61   |          |
| 伸長状態 (伸長割合%) |          |       |       |      |           |      |      |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50   | 0    | 100  | 50       | 0    | 100  | 50        | 100  |          |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100  | 50   | 100  | 100      | 100  | 100  | 100       | 100  |          |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50   | 100  | 50   | 100      | 100  | 100  | 100       | 100  |          |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50   | 100  | 50   | 50       | 100  | 50   | 100       | 100  |          |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t | 83t  | 200t | 83t      | 83t  | 83t  | 83t       | 83t  |          |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60 | 1.35 | 2.60 | 1.35     | 1.35 | 1.35 | 1.35      | 1.35 |          |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10   | 7    | 10   | 7        | 7    | 7    | 7         | 6    |          |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

E5性能 C/W 10t O/R 5.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       |       | 22.7mブーム |       |      |      | 27.25mブーム |       |      |  |
|--------------|----------|-----------|-------|-------|----------|-------|------|------|-----------|-------|------|--|
| 2.5          | 200.0    |           |       |       |          |       |      |      |           |       |      |  |
| 3.0          | 185.9    | 175.0     | 150.0 |       |          |       |      |      |           |       |      |  |
| 3.5          | 166.4    | 166.5     | 150.0 |       |          |       |      |      |           |       |      |  |
| 4.0          | 150.3    | 150.4     | 141.4 | 136.0 | 140.6    | 144.9 | 83.0 |      |           |       |      |  |
| 4.5          | 120.4    | 120.7     | 124.5 | 110.1 | 114.2    | 118.2 | 80.7 | 98.3 | 102.5     | 107.5 | 83.0 |  |
| 5.0          | 91.7     | 92.0      | 95.3  | 91.0  | 94.0     | 96.8  | 75.6 | 82.5 | 86.5      | 91.0  | 83.0 |  |
| 6.0          | 60.5     | 60.7      | 63.4  | 59.9  | 62.4     | 64.7  | 64.9 | 58.8 | 61.4      | 64.4  | 66.9 |  |
| 7.0          | 43.8     | 44.0      | 46.4  | 43.3  | 45.4     | 47.5  | 47.7 | 42.2 | 44.6      | 47.3  | 49.4 |  |
| 8.0          | 33.4     | 33.5      | 35.8  | 32.9  | 34.9     | 36.8  | 37.0 | 32.0 | 34.1      | 36.6  | 38.6 |  |
| 9.0          | 26.3     | 26.5      | 28.5  | 25.8  | 27.8     | 29.5  | 29.7 | 24.9 | 27.0      | 29.3  | 31.2 |  |
| 10.0         | 21.2     | 21.3      | 23.3  | 20.7  | 22.5     | 24.2  | 24.4 | 19.8 | 21.8      | 24.0  | 25.8 |  |
| 11.0         | 17.3     | 17.4      | 19.3  | 16.8  | 18.6     | 20.2  | 20.4 | 16.0 | 17.9      | 20.0  | 21.7 |  |
| 12.0         |          | 14.4      | 16.2  | 13.8  | 15.5     | 17.1  | 17.2 | 13.0 | 14.8      | 16.9  | 18.5 |  |
| 14.0         |          | 9.9       | 11.7  | 9.3   | 11.0     | 12.5  | 12.6 | 8.5  | 10.3      | 12.3  | 13.8 |  |
| 16.0         |          | 6.9       | 8.6   | 6.2   | 7.9      | 9.3   | 9.4  |      | 7.2       | 9.1   | 10.6 |  |
| 18.0         |          |           |       |       | 5.6      | 7.0   | 7.1  |      |           | 6.8   | 8.2  |  |
| 20.0         |          |           |       |       |          |       | 5.4  |      |           |       | 6.3  |  |
| 22.0         |          |           |       |       |          |       |      |      |           |       | 4.9  |  |
| 危険角度 (°)     | -        | -         | -     | 35    | 25       | 25    | -    | 55   | 49        | 43    | 25   |  |
| 伸長状態 (伸長割合%) |          |           |       |       |          |       |      |      |           |       |      |  |
| ブーム2 (%)     | 0        | 0         | 0     | 50    | 0        | 0     | 0    | 100  | 50        | 0     | 0    |  |
| ブーム3 (%)     | 0        | 50        | 0     | 50    | 50       | 0     | 0    | 50   | 50        | 50    | 0    |  |
| ブーム4 (%)     | 0        | 0         | 0     | 0     | 50       | 50    | 0    | 0    | 50        | 50    | 50   |  |
| ブーム5 (%)     | 0        | 0         | 50    | 0     | 0        | 50    | 100  | 0    | 0         | 50    | 100  |  |
| フック種類        | 200t     | 200t      | 200t  | 200t  | 200t     | 200t  | 83t  | 200t | 200t      | 200t  | 83t  |  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60  | 2.60     | 2.60  | 1.35 | 2.60 | 2.60      | 2.60  | 1.35 |  |
| 掛数           | 19       | 16        | 14    | 14    | 16       | 14    | 7    | 12   | 14        | 14    | 7    |  |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |      |      |      | 36.35mブーム |      |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|------|------|------|-----------|------|------|----------|------|------|-----------|------|----------|
| 5.0          | 78.2     | 82.8 | 84.1 | 83.0 |           |      |      |          |      |      |           |      |          |
| 6.0          | 58.8     | 63.0 | 64.1 | 66.8 | 57.7      | 59.5 | 64.1 |          |      |      |           |      |          |
| 7.0          | 43.5     | 46.3 | 47.0 | 49.3 | 45.2      | 46.5 | 49.6 | 43.4     | 46.3 | 48.3 |           |      |          |
| 8.0          | 33.1     | 35.7 | 36.4 | 38.5 | 34.7      | 35.8 | 38.7 | 34.7     | 36.7 | 38.0 | 35.0      | 37.5 | 34.5     |
| 9.0          | 26.0     | 28.5 | 29.1 | 31.1 | 27.5      | 28.6 | 31.3 | 27.6     | 29.4 | 30.7 | 28.5      | 30.1 | 29.0     |
| 10.0         | 20.9     | 23.2 | 23.8 | 25.7 | 22.3      | 23.4 | 25.9 | 22.4     | 24.1 | 25.3 | 23.2      | 24.8 | 23.9     |
| 11.0         | 17.0     | 19.2 | 19.8 | 21.6 | 18.4      | 19.4 | 21.8 | 18.4     | 20.1 | 21.3 | 19.2      | 20.8 | 19.9     |
| 12.0         | 14.0     | 16.1 | 16.7 | 18.4 | 15.3      | 16.2 | 18.6 | 15.3     | 16.9 | 18.1 | 16.1      | 17.6 | 16.7     |
| 14.0         | 9.5      | 11.6 | 12.1 | 13.8 | 10.7      | 11.7 | 13.9 | 10.8     | 12.3 | 13.4 | 11.5      | 12.9 | 12.1     |
| 16.0         | 6.3      | 8.4  | 8.9  | 10.5 | 7.6       | 8.5  | 10.6 | 7.6      | 9.1  | 10.1 | 8.3       | 9.7  | 8.9      |
| 18.0         |          | 6.0  | 6.5  | 8.1  |           | 6.1  | 8.2  |          | 6.7  | 7.7  | 5.9       | 7.3  | 6.5      |
| 20.0         |          |      |      | 6.2  |           |      | 6.4  |          | 4.9  | 5.9  |           | 5.5  |          |
| 22.0         |          |      |      | 4.8  |           |      | 4.9  |          |      | 4.4  |           |      |          |
| 危険角度 (°)     | 56       | 52   | 52   | 41   | 61        | 57   | 53   | 65       | 58   | 54   | 65        | 61   | 67       |
| 伸長状態 (伸長割合%) |          |      |      |      |           |      |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50   | 0    | 0    | 100       | 50   | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50   | 100  | 0    | 50        | 100  | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50   | 50   | 100  | 50        | 50   | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50   | 50   | 100  | 50        | 50   | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t | 200t | 83t  | 200t      | 200t | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60 | 2.60 | 1.35 | 2.60      | 2.60 | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12   | 10   | 7    | 10        | 10   | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

F1性能 C/W 0t O/R 9.2m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 180.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 161.1    | 161.2     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 145.5    | 145.6     | 141.4 | 145.1    | 146.7 | 148.1 | 83.0 |           |       |       |      |
| 4.5          | 132.4    | 132.5     | 134.2 | 132.0    | 133.6 | 135.1 | 80.7 | 131.3     | 133.0 | 134.9 | 83.0 |
| 5.0          | 121.2    | 121.3     | 123.1 | 120.8    | 122.5 | 124.0 | 75.6 | 120.1     | 121.8 | 123.8 | 83.0 |
| 6.0          | 99.2     | 99.5      | 101.8 | 98.8     | 101.0 | 103.0 | 67.2 | 97.8      | 100.1 | 102.8 | 75.5 |
| 7.0          | 82.4     | 82.7      | 85.0  | 82.0     | 84.2  | 86.2  | 60.4 | 81.0      | 83.3  | 86.0  | 68.5 |
| 8.0          | 69.9     | 70.1      | 72.4  | 69.4     | 71.6  | 73.6  | 54.8 | 68.4      | 70.7  | 73.4  | 62.7 |
| 9.0          | 60.1     | 60.3      | 62.7  | 59.6     | 61.8  | 63.8  | 50.2 | 58.6      | 60.9  | 63.6  | 57.8 |
| 10.0         | 49.4     | 49.6      | 52.7  | 48.6     | 51.5  | 54.1  | 46.5 | 47.3      | 50.3  | 53.8  | 53.6 |
| 11.0         | 39.7     | 39.9      | 42.7  | 39.0     | 41.6  | 44.0  | 43.5 | 37.7      | 40.6  | 43.8  | 46.3 |
| 12.0         |          | 32.8      | 35.5  | 31.9     | 34.4  | 36.7  | 36.9 | 30.8      | 33.4  | 36.4  | 38.8 |
| 14.0         |          | 23.2      | 25.6  | 22.4     | 24.7  | 26.7  | 26.9 | 21.3      | 23.7  | 26.5  | 28.6 |
| 16.0         |          | 17.1      | 19.4  | 16.2     | 18.4  | 20.3  | 20.5 | 15.1      | 17.5  | 20.1  | 22.0 |
| 18.0         |          |           |       | 11.9     | 14.0  | 15.9  | 16.0 | 10.8      | 13.1  | 15.6  | 17.4 |
| 20.0         |          |           |       | 8.5      | 10.9  | 12.7  | 12.8 | 7.0       | 9.9   | 12.3  | 14.0 |
| 22.0         |          |           |       |          |       |       |      |           | 7.0   | 9.8   | 11.4 |
| 24.0         |          |           |       |          |       |       |      |           |       | 7.9   | 9.4  |
| 危険角度 (°)     | -        | -         | -     | -        | -     | -     | -    | 34        | 25    | -     | -    |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 121.0    | 123.1 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 99.1     | 101.8 | 102.5 | 76.5 | 100.8     | 102.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 82.3     | 85.0  | 85.7  | 68.7 | 84.0      | 85.2  | 74.4 | 84.0     | 83.0 | 78.0 |           |      |          |
| 8.0          | 69.7     | 72.4  | 73.1  | 62.3 | 71.4      | 72.6  | 67.9 | 70.6     | 73.5 | 72.1 | 68.7      | 72.1 | 66.7     |
| 9.0          | 59.9     | 62.6  | 63.3  | 56.9 | 60.2      | 62.3  | 62.4 | 57.3     | 60.8 | 63.2 | 56.2      | 59.4 | 55.0     |
| 10.0         | 49.0     | 52.5  | 53.4  | 52.4 | 49.7      | 51.7  | 56.5 | 47.5     | 50.8 | 53.0 | 47.0      | 50.0 | 46.3     |
| 11.0         | 39.3     | 42.6  | 43.4  | 46.1 | 41.3      | 42.8  | 46.4 | 40.0     | 43.2 | 45.3 | 39.9      | 42.7 | 39.5     |
| 12.0         | 32.2     | 35.3  | 36.1  | 38.7 | 34.1      | 35.5  | 38.9 | 34.1     | 36.5 | 38.1 | 34.2      | 37.0 | 34.1     |
| 14.0         | 22.6     | 25.5  | 26.1  | 28.5 | 24.3      | 25.6  | 28.7 | 24.4     | 26.5 | 28.0 | 25.4      | 27.4 | 26.0     |
| 16.0         | 16.4     | 19.1  | 19.7  | 21.9 | 18.0      | 19.2  | 22.1 | 18.0     | 20.0 | 21.4 | 18.9      | 20.8 | 19.7     |
| 18.0         | 12.0     | 14.6  | 15.2  | 17.3 | 13.5      | 14.7  | 17.4 | 13.6     | 15.5 | 16.8 | 14.4      | 16.2 | 15.2     |
| 20.0         | 8.6      | 11.3  | 11.9  | 13.9 | 10.3      | 11.4  | 14.0 | 10.3     | 12.1 | 13.4 | 11.1      | 12.8 | 11.9     |
| 22.0         | 5.6      | 8.8   | 9.3   | 11.3 | 7.5       | 8.8   | 11.4 | 7.5      | 9.5  | 10.8 | 8.6       | 10.2 | 9.3      |
| 24.0         |          | 6.5   | 7.2   | 9.2  |           | 6.5   | 9.3  |          | 7.4  | 8.7  | 6.1       | 8.2  | 7.1      |
| 26.0         |          |       |       | 7.6  |           |       | 7.6  |          | 5.4  | 7.0  | 4.1       | 6.3  | 5.1      |
| 28.0         |          |       |       | 6.1  |           |       | 6.1  |          |      | 5.3  |           | 4.6  |          |
| 30.0         |          |       |       |      |           |       | 4.7  |          |      |      |           |      |          |
| 危険角度 (°)     | 41       | 35    | 35    | -    | 49        | 44    | 27   | 54       | 48   | 44   | 52        | 49   | 57       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

F2性能 C/W 0t O/R 8.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       |       | 22.7mブーム |       |      |       | 27.25mブーム |       |      |  |
|--------------|----------|-----------|-------|-------|----------|-------|------|-------|-----------|-------|------|--|
| 2.5          | 200.0    |           |       |       |          |       |      |       |           |       |      |  |
| 3.0          | 180.0    | 175.0     | 150.0 |       |          |       |      |       |           |       |      |  |
| 3.5          | 161.1    | 161.2     | 150.0 |       |          |       |      |       |           |       |      |  |
| 4.0          | 145.5    | 145.6     | 141.4 | 145.1 | 146.7    | 148.1 | 83.0 |       |           |       |      |  |
| 4.5          | 132.4    | 132.5     | 134.2 | 132.0 | 133.6    | 135.1 | 80.7 | 131.3 | 133.0     | 134.9 | 83.0 |  |
| 5.0          | 121.2    | 121.3     | 123.1 | 120.8 | 122.5    | 124.0 | 75.6 | 120.1 | 121.8     | 123.8 | 83.0 |  |
| 6.0          | 99.2     | 99.5      | 101.8 | 98.8  | 101.0    | 103.0 | 67.2 | 97.8  | 100.1     | 102.8 | 75.5 |  |
| 7.0          | 82.4     | 82.7      | 85.0  | 82.0  | 84.2     | 86.2  | 60.4 | 81.0  | 83.3      | 86.0  | 68.5 |  |
| 8.0          | 69.0     | 69.3      | 72.4  | 68.2  | 71.5     | 73.6  | 54.8 | 64.3  | 68.5      | 73.3  | 62.7 |  |
| 9.0          | 52.0     | 52.2      | 55.3  | 51.3  | 54.1     | 58.8  | 50.2 | 49.9  | 53.0      | 56.5  | 57.8 |  |
| 10.0         | 40.8     | 41.0      | 43.9  | 40.1  | 42.8     | 45.2  | 45.4 | 38.9  | 41.7      | 44.9  | 47.5 |  |
| 11.0         | 33.0     | 33.1      | 35.8  | 32.3  | 34.8     | 37.1  | 37.2 | 31.1  | 33.8      | 36.8  | 39.1 |  |
| 12.0         |          | 27.3      | 29.8  | 26.5  | 28.9     | 31.0  | 31.2 | 25.4  | 27.9      | 30.7  | 33.0 |  |
| 14.0         |          | 19.2      | 21.6  | 18.4  | 20.6     | 22.6  | 22.8 | 17.4  | 19.7      | 22.4  | 24.4 |  |
| 16.0         |          | 14.0      | 16.2  | 13.1  | 15.2     | 17.1  | 17.3 | 12.1  | 14.3      | 16.8  | 18.7 |  |
| 18.0         |          |           |       | 9.2   | 11.5     | 13.2  | 13.4 | 7.9   | 10.5      | 13.0  | 14.7 |  |
| 20.0         |          |           |       | 5.9   | 8.7      | 10.4  | 10.6 |       | 7.4       | 10.1  | 11.7 |  |
| 22.0         |          |           |       |       |          |       |      |       |           | 7.9   | 9.5  |  |
| 24.0         |          |           |       |       |          |       |      |       |           | 5.9   | 7.7  |  |
| 危険角度 (°)     | -        | -         | -     | -     | -        | -     | -    | 43    | 34        | -     | -    |  |
| 伸長状態 (伸長割合%) |          |           |       |       |          |       |      |       |           |       |      |  |
| ブーム2 (%)     | 0        | 0         | 0     | 50    | 0        | 0     | 0    | 100   | 50        | 0     | 0    |  |
| ブーム3 (%)     | 0        | 50        | 0     | 50    | 50       | 0     | 0    | 50    | 50        | 50    | 0    |  |
| ブーム4 (%)     | 0        | 0         | 0     | 0     | 50       | 50    | 0    | 0     | 50        | 50    | 50   |  |
| ブーム5 (%)     | 0        | 0         | 50    | 0     | 0        | 50    | 100  | 0     | 0         | 50    | 100  |  |
| フック種類        | 200t     | 200t      | 200t  | 200t  | 200t     | 200t  | 83t  | 200t  | 200t      | 200t  | 83t  |  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60  | 2.60     | 2.60  | 1.35 | 2.60  | 2.60      | 2.60  | 1.35 |  |
| 掛数           | 19       | 16        | 14    | 14    | 16       | 14    | 7    | 12    | 14        | 14    | 7    |  |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |       |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|-------|------|----------|------|------|-----------|------|----------|
| 5.0          | 121.0    | 123.1 | 115.0 | 83.0 |           |       |      |          |      |      |           |      |          |
| 6.0          | 99.1     | 101.8 | 102.5 | 76.5 | 100.8     | 102.0 | 80.0 |          |      |      |           |      |          |
| 7.0          | 80.7     | 85.0  | 85.7  | 68.7 | 78.6      | 80.9  | 74.4 | 73.9     | 77.8 | 78.0 |           |      |          |
| 8.0          | 62.6     | 67.4  | 68.7  | 62.3 | 61.9      | 64.0  | 67.9 | 58.7     | 62.2 | 64.6 | 57.3      | 60.5 | 55.9     |
| 9.0          | 50.1     | 54.8  | 55.7  | 56.9 | 50.2      | 52.2  | 57.0 | 47.9     | 51.2 | 53.4 | 47.2      | 50.2 | 46.3     |
| 10.0         | 40.4     | 43.8  | 44.6  | 47.4 | 41.5      | 43.4  | 47.6 | 39.8     | 42.9 | 45.0 | 39.5      | 42.3 | 39.1     |
| 11.0         | 32.6     | 35.7  | 36.5  | 39.0 | 34.5      | 35.9  | 39.3 | 33.5     | 36.5 | 38.5 | 33.5      | 36.2 | 33.4     |
| 12.0         | 26.7     | 29.7  | 30.4  | 32.8 | 28.5      | 29.8  | 33.1 | 28.5     | 30.8 | 32.3 | 28.7      | 31.3 | 28.7     |
| 14.0         | 18.6     | 21.4  | 22.0  | 24.3 | 20.3      | 21.5  | 24.5 | 20.3     | 22.4 | 23.8 | 21.3      | 23.2 | 21.8     |
| 16.0         | 13.3     | 15.9  | 16.5  | 18.6 | 14.8      | 16.0  | 18.8 | 14.9     | 16.8 | 18.1 | 15.8      | 17.6 | 16.6     |
| 18.0         | 9.4      | 12.0  | 12.6  | 14.6 | 11.0      | 12.1  | 14.8 | 11.0     | 12.9 | 14.1 | 11.9      | 13.6 | 12.6     |
| 20.0         | 6.0      | 9.1   | 9.7   | 11.6 | 7.9       | 9.2   | 11.8 | 8.0      | 9.9  | 11.1 | 8.9       | 10.6 | 9.7      |
| 22.0         |          | 6.6   | 7.3   | 9.3  |           | 6.7   | 9.4  |          | 7.6  | 8.8  | 6.3       | 8.3  | 7.3      |
| 24.0         |          |       |       | 7.5  |           |       | 7.6  |          | 5.4  | 7.0  | 4.1       | 6.3  | 5.1      |
| 26.0         |          |       |       | 5.8  |           |       | 5.9  |          |      | 5.2  |           | 4.5  |          |
| 28.0         |          |       |       | 4.4  |           |       | 4.5  |          |      |      |           |      |          |
| 危険角度 (°)     | 47       | 41    | 41    | 15   | 53        | 49    | 34   | 58       | 51   | 48   | 56        | 52   | 59       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |       |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50    | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100   | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50    | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10    | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)





# 13.6m — 50.0m

# メインブーム

F3性能 C/W 0t O/R 7.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 180.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 161.1    | 161.2     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 145.5    | 145.6     | 141.4 | 145.1    | 146.7 | 148.1 | 83.0 |           |       |       |      |
| 4.5          | 132.4    | 132.5     | 134.2 | 132.0    | 133.6 | 135.1 | 80.7 | 131.3     | 133.0 | 134.9 | 83.0 |
| 5.0          | 121.2    | 121.3     | 123.1 | 120.8    | 122.5 | 124.0 | 75.6 | 120.1     | 121.8 | 123.8 | 83.0 |
| 6.0          | 99.2     | 99.5      | 101.8 | 96.1     | 100.6 | 103.0 | 67.2 | 86.3      | 90.9  | 96.2  | 75.5 |
| 7.0          | 67.3     | 67.5      | 70.9  | 66.6     | 69.6  | 72.4  | 60.4 | 63.9      | 68.0  | 72.1  | 68.5 |
| 8.0          | 48.8     | 49.1      | 52.0  | 48.2     | 50.9  | 53.3  | 53.5 | 47.0      | 49.8  | 53.1  | 55.7 |
| 9.0          | 37.4     | 37.6      | 40.2  | 36.8     | 39.2  | 41.4  | 41.6 | 35.6      | 38.2  | 41.2  | 43.5 |
| 10.0         | 29.6     | 29.7      | 32.2  | 29.0     | 31.2  | 33.3  | 33.5 | 27.9      | 30.3  | 33.1  | 35.1 |
| 11.0         | 23.9     | 24.0      | 26.4  | 23.3     | 25.5  | 27.4  | 27.6 | 22.3      | 24.6  | 27.2  | 29.3 |
| 12.0         |          | 19.7      | 22.0  | 19.0     | 21.1  | 23.0  | 23.1 | 18.0      | 20.3  | 22.8  | 24.7 |
| 14.0         |          | 13.7      | 15.8  | 13.0     | 14.9  | 16.7  | 16.8 | 12.0      | 14.1  | 16.5  | 18.3 |
| 16.0         |          | 9.7       | 11.7  | 8.9      | 10.8  | 12.5  | 12.6 | 8.0       | 10.0  | 12.3  | 13.9 |
| 18.0         |          |           |       | 5.7      | 7.9   | 9.5   | 9.6  |           | 7.1   | 9.2   | 10.8 |
| 20.0         |          |           |       |          | 5.6   | 7.3   | 7.4  |           |       | 7.0   | 8.5  |
| 22.0         |          |           |       |          |       |       |      |           |       |       | 6.7  |
| 24.0         |          |           |       |          |       |       |      |           |       |       | 5.3  |
| 危険角度 (°)     | -        | -         | -     | 25       | -     | -     | -    | 49        | 43    | 34    | -    |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |       |       |      | 36.35mブーム |      |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|-------|-------|------|-----------|------|------|----------|------|------|-----------|------|----------|
| 5.0          | 115.9    | 122.2 | 115.0 | 83.0 |           |      |      |          |      |      |           |      |          |
| 6.0          | 82.0     | 87.3  | 88.7  | 76.5 | 79.2      | 81.6 | 80.0 |          |      |      |           |      |          |
| 7.0          | 61.8     | 66.6  | 67.8  | 68.7 | 60.8      | 62.9 | 68.0 | 57.3     | 60.9 | 63.2 |           |      |          |
| 8.0          | 48.4     | 51.9  | 52.8  | 55.6 | 48.3      | 50.3 | 55.0 | 45.9     | 49.1 | 51.3 | 45.1      | 48.0 | 44.2     |
| 9.0          | 37.0     | 40.1  | 40.9  | 43.4 | 38.9      | 40.3 | 43.7 | 37.5     | 40.6 | 42.7 | 37.2      | 40.0 | 36.7     |
| 10.0         | 29.2     | 32.1  | 32.8  | 35.2 | 31.0      | 32.2 | 35.4 | 31.0     | 33.2 | 34.7 | 31.1      | 33.8 | 31.0     |
| 11.0         | 23.5     | 26.3  | 26.9  | 29.2 | 25.2      | 26.4 | 29.4 | 25.2     | 27.3 | 28.7 | 26.2      | 28.1 | 26.3     |
| 12.0         | 19.2     | 21.8  | 22.5  | 24.6 | 20.8      | 22.0 | 24.8 | 20.9     | 22.8 | 24.2 | 21.8      | 23.6 | 22.6     |
| 14.0         | 13.2     | 15.6  | 16.2  | 18.2 | 14.6      | 15.7 | 18.3 | 14.7     | 16.5 | 17.7 | 15.5      | 17.2 | 16.2     |
| 16.0         | 9.1      | 11.4  | 11.9  | 13.8 | 10.4      | 11.5 | 14.0 | 10.5     | 12.2 | 13.4 | 11.3      | 12.9 | 12.0     |
| 18.0         | 5.9      | 8.4   | 8.9   | 10.7 | 7.4       | 8.5  | 10.9 | 7.5      | 9.1  | 10.3 | 8.2       | 9.8  | 8.9      |
| 20.0         |          | 6.1   | 6.6   | 8.4  |           | 6.2  | 8.5  |          | 6.8  | 7.9  | 5.9       | 7.5  | 6.6      |
| 22.0         |          |       |       | 6.6  |           |      | 6.7  |          | 4.8  | 6.1  |           | 5.7  |          |
| 24.0         |          |       |       | 5.1  |           |      | 5.2  |          |      | 4.5  |           |      |          |
| 危険角度 (°)     | 52       | 47    | 47    | 35   | 57        | 53   | 44   | 63       | 54   | 51   | 62        | 59   | 65       |
| 伸長状態 (伸長割合%) |          |       |       |      |           |      |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50    | 0     | 0    | 100       | 50   | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50    | 100   | 0    | 50        | 100  | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50    | 50    | 100  | 50        | 50   | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50    | 50    | 100  | 50        | 50   | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t  | 200t  | 83t  | 200t      | 200t | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60 | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12    | 10    | 7    | 10        | 10   | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

F4性能 C/W 0t O/R 6.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |       |       |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|-------|-------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |       |       |      |
| 3.0          | 180.0    | 175.0     | 150.0 |          |       |       |      |           |       |       |      |
| 3.5          | 161.1    | 161.2     | 150.0 |          |       |       |      |           |       |       |      |
| 4.0          | 145.5    | 145.6     | 141.4 | 145.1    | 146.7 | 148.1 | 83.0 |           |       |       |      |
| 4.5          | 132.4    | 132.5     | 134.2 | 124.4    | 129.4 | 134.1 | 80.7 | 109.0     | 114.1 | 119.9 | 83.0 |
| 5.0          | 117.5    | 113.1     | 118.4 | 100.3    | 104.9 | 109.1 | 75.6 | 89.1      | 93.7  | 99.0  | 83.0 |
| 6.0          | 71.2     | 71.5      | 74.9  | 70.5     | 73.5  | 76.4  | 67.2 | 63.3      | 67.4  | 72.0  | 75.5 |
| 7.0          | 49.3     | 49.5      | 52.4  | 48.6     | 51.3  | 53.8  | 54.0 | 47.4      | 50.2  | 53.5  | 56.1 |
| 8.0          | 36.5     | 36.7      | 39.3  | 35.9     | 38.3  | 40.5  | 40.7 | 34.8      | 37.4  | 40.3  | 42.6 |
| 9.0          | 28.1     | 28.3      | 30.7  | 27.6     | 29.8  | 31.9  | 32.0 | 26.6      | 28.9  | 31.6  | 33.8 |
| 10.0         | 22.3     | 22.4      | 24.7  | 21.7     | 23.8  | 25.8  | 25.9 | 20.7      | 23.0  | 25.5  | 27.6 |
| 11.0         | 17.9     | 18.0      | 20.2  | 17.4     | 19.4  | 21.2  | 21.4 | 16.4      | 18.6  | 21.0  | 22.9 |
| 12.0         |          | 14.6      | 16.8  | 14.0     | 16.0  | 17.7  | 17.9 | 13.1      | 15.2  | 17.5  | 19.3 |
| 14.0         |          | 9.8       | 11.8  | 9.1      | 11.0  | 12.7  | 12.8 | 8.3       | 10.2  | 12.5  | 14.2 |
| 16.0         |          | 6.5       | 8.5   |          | 7.7   | 9.3   | 9.4  |           | 6.9   | 9.1   | 10.7 |
| 18.0         |          |           |       |          |       | 6.8   | 6.9  |           |       | 6.6   | 8.1  |
| 20.0         |          |           |       |          |       |       | 5.0  |           |       |       | 6.2  |
| 22.0         |          |           |       |          |       |       |      |           |       |       | 4.6  |
| 危険角度 (°)     | -        | -         | -     | 45       | 35    | 25    | -    | 55        | 49    | 43    | 25   |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |       |       |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50    | 0     | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50    | 50    | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50    | 50    | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0     | 50    | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t  | 200t  | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60  | 2.60  | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14    | 14    | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |      |      |      | 36.35mブーム |      |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|------|------|------|-----------|------|------|----------|------|------|-----------|------|----------|
| 5.0          | 83.7     | 89.0 | 90.4 | 83.0 |           |      |      |          |      |      |           |      |          |
| 6.0          | 60.8     | 65.6 | 66.8 | 70.7 | 59.5      | 61.6 | 66.6 |          |      |      |           |      |          |
| 7.0          | 46.4     | 50.7 | 51.8 | 55.4 | 46.1      | 48.0 | 52.7 | 43.6     | 46.8 | 49.0 |           |      |          |
| 8.0          | 36.2     | 39.2 | 40.0 | 42.5 | 36.8      | 38.6 | 42.7 | 34.9     | 38.0 | 40.0 | 34.6      | 37.3 | 34.1     |
| 9.0          | 27.8     | 30.7 | 31.4 | 33.7 | 29.6      | 30.8 | 33.9 | 28.5     | 31.3 | 33.2 | 28.4      | 31.1 | 28.3     |
| 10.0         | 21.9     | 24.6 | 25.3 | 27.5 | 23.6      | 24.8 | 27.7 | 23.4     | 25.6 | 27.0 | 23.7      | 26.2 | 23.7     |
| 11.0         | 17.6     | 20.1 | 20.7 | 22.8 | 19.1      | 20.2 | 23.0 | 19.2     | 21.1 | 22.4 | 19.8      | 21.8 | 20.0     |
| 12.0         | 14.2     | 16.6 | 17.3 | 19.3 | 15.7      | 16.8 | 19.4 | 15.7     | 17.6 | 18.8 | 16.6      | 18.3 | 17.0     |
| 14.0         | 9.3      | 11.6 | 12.2 | 14.1 | 10.7      | 11.8 | 14.3 | 10.8     | 12.5 | 13.7 | 11.6      | 13.2 | 12.2     |
| 16.0         |          | 8.2  | 8.8  | 10.6 | 7.3       | 8.3  | 10.7 |          | 9.0  | 10.2 | 8.1       | 9.7  | 8.8      |
| 18.0         |          | 5.7  | 6.2  | 8.0  |           | 5.8  | 8.1  |          | 6.5  | 7.6  |           | 7.1  |          |
| 20.0         |          |      |      | 6.1  |           |      | 6.2  |          | 4.2  | 5.6  |           | 5.1  |          |
| 22.0         |          |      |      | 4.4  |           |      | 4.6  |          |      |      |           |      |          |
| 危険角度 (°)     | 60       | 52   | 52   | 41   | 62        | 59   | 49   | 67       | 60   | 58   | 67        | 62   | 69       |
| 伸長状態 (伸長割合%) |          |      |      |      |           |      |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50   | 0    | 0    | 100       | 50   | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50   | 100  | 0    | 50        | 100  | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50   | 50   | 100  | 50        | 50   | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50   | 50   | 100  | 50        | 50   | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t | 200t | 83t  | 200t      | 200t | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60 | 2.60 | 1.35 | 2.60      | 2.60 | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12   | 10   | 7    | 10        | 10   | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)



# 13.6m — 50.0m

# メインブーム

F5性能 C/W 0t O/R 5.4m ブーム

| 作業半径 (m)     | 13.6mブーム | 18.15mブーム |       | 22.7mブーム |       |       |      | 27.25mブーム |      |      |      |
|--------------|----------|-----------|-------|----------|-------|-------|------|-----------|------|------|------|
| 2.5          | 200.0    |           |       |          |       |       |      |           |      |      |      |
| 3.0          | 180.0    | 175.0     | 150.0 |          |       |       |      |           |      |      |      |
| 3.5          | 161.1    | 161.2     | 150.0 |          |       |       |      |           |      |      |      |
| 4.0          | 136.2    | 122.1     | 127.5 | 106.3    | 110.9 | 115.2 | 83.0 |           |      |      |      |
| 4.5          | 95.2     | 95.5      | 99.3  | 85.4     | 89.5  | 93.4  | 80.7 | 75.5      | 79.7 | 84.7 | 83.0 |
| 5.0          | 72.0     | 72.3      | 75.6  | 70.5     | 74.3  | 77.1  | 75.6 | 62.7      | 66.7 | 71.3 | 75.1 |
| 6.0          | 46.7     | 47.0      | 49.7  | 46.2     | 48.6  | 50.9  | 51.1 | 45.0      | 47.6 | 50.9 | 53.1 |
| 7.0          | 33.2     | 33.4      | 35.8  | 32.7     | 34.9  | 36.9  | 37.1 | 31.7      | 34.0 | 36.7 | 38.9 |
| 8.0          | 24.8     | 25.0      | 27.2  | 24.3     | 26.4  | 28.2  | 28.4 | 23.4      | 25.6 | 28.0 | 30.0 |
| 9.0          | 19.1     | 19.3      | 21.4  | 18.6     | 20.6  | 22.3  | 22.5 | 17.7      | 19.8 | 22.1 | 24.0 |
| 10.0         | 15.0     | 15.1      | 17.1  | 14.5     | 16.3  | 18.0  | 18.2 | 13.6      | 15.6 | 17.8 | 19.6 |
| 11.0         | 11.9     | 11.9      | 13.9  | 11.4     | 13.1  | 14.8  | 14.9 | 10.5      | 12.4 | 14.6 | 16.3 |
| 12.0         |          | 9.5       | 11.4  | 8.9      | 10.6  | 12.2  | 12.3 | 8.1       | 9.9  | 12.0 | 13.6 |
| 14.0         |          | 5.9       | 7.7   |          | 7.0   | 8.5   | 8.6  |           | 6.3  | 8.3  | 9.8  |
| 16.0         |          |           |       |          |       | 5.9   | 6.0  |           |      | 5.7  | 7.2  |
| 18.0         |          |           |       |          |       |       | 4.1  |           |      |      | 5.2  |
| 危険角度 (°)     | -        | 20        | 20    | 53       | 45    | 35    | 25   | 61        | 56   | 49   | 43   |
| 伸長状態 (伸長割合%) |          |           |       |          |       |       |      |           |      |      |      |
| ブーム2 (%)     | 0        | 0         | 0     | 50       | 0     | 0     | 0    | 100       | 50   | 0    | 0    |
| ブーム3 (%)     | 0        | 50        | 0     | 50       | 50    | 0     | 0    | 50        | 50   | 50   | 0    |
| ブーム4 (%)     | 0        | 0         | 0     | 0        | 50    | 50    | 0    | 0         | 50   | 50   | 50   |
| ブーム5 (%)     | 0        | 0         | 50    | 0        | 0     | 50    | 100  | 0         | 0    | 50   | 100  |
| フック種類        | 200t     | 200t      | 200t  | 200t     | 200t  | 200t  | 83t  | 200t      | 200t | 200t | 83t  |
| フック質量 (t)    | 2.60     | 2.60      | 2.60  | 2.60     | 2.60  | 2.60  | 1.35 | 2.60      | 2.60 | 2.60 | 1.35 |
| 掛数           | 19       | 16        | 14    | 14       | 16    | 14    | 7    | 12        | 14   | 14   | 7    |

(単位 : ton)

| 作業半径 (m)     | 31.8mブーム |      |      |      | 36.35mブーム |      |      | 40.9mブーム |      |      | 45.45mブーム |      | 50.0mブーム |
|--------------|----------|------|------|------|-----------|------|------|----------|------|------|-----------|------|----------|
| 5.0          | 59.7     | 64.3 | 65.6 | 69.4 |           |      |      |          |      |      |           |      |          |
| 6.0          | 44.0     | 48.2 | 49.3 | 52.8 | 43.6      | 45.4 | 50.0 |          |      |      |           |      |          |
| 7.0          | 33.0     | 35.7 | 36.5 | 38.8 | 33.9      | 35.6 | 39.0 | 32.0     | 35.0 | 36.9 |           |      |          |
| 8.0          | 24.6     | 27.1 | 27.8 | 29.9 | 26.1      | 27.3 | 30.1 | 25.5     | 28.2 | 29.5 | 25.5      | 28.0 | 25.3     |
| 9.0          | 18.8     | 21.3 | 21.9 | 23.9 | 20.3      | 21.4 | 24.1 | 20.4     | 22.2 | 23.5 | 20.7      | 22.9 | 20.8     |
| 10.0         | 14.7     | 17.0 | 17.6 | 19.5 | 16.1      | 17.1 | 19.7 | 16.1     | 17.9 | 19.1 | 17.0      | 18.6 | 17.2     |
| 11.0         | 11.5     | 13.8 | 14.3 | 16.2 | 12.9      | 13.9 | 16.3 | 12.9     | 14.6 | 15.8 | 13.8      | 15.3 | 14.3     |
| 12.0         | 9.1      | 11.3 | 11.8 | 13.6 | 10.4      | 11.4 | 13.7 | 10.4     | 12.1 | 13.2 | 11.2      | 12.7 | 11.8     |
| 14.0         |          | 7.5  | 8.1  | 9.7  |           | 7.6  | 9.9  |          | 8.3  | 9.4  | 7.5       | 8.9  | 8.0      |
| 16.0         |          |      |      | 7.1  |           |      | 7.2  |          | 5.7  | 6.7  |           | 6.3  |          |
| 18.0         |          |      |      | 5.1  |           |      | 5.2  |          |      | 4.7  |           |      |          |
| 危険角度 (°)     | 66       | 60   | 60   | 52   | 68        | 66   | 57   | 72       | 66   | 62   | 72        | 68   | 73       |
| 伸長状態 (伸長割合%) |          |      |      |      |           |      |      |          |      |      |           |      |          |
| ブーム2 (%)     | 100      | 50   | 0    | 0    | 100       | 50   | 0    | 100      | 50   | 0    | 100       | 50   | 100      |
| ブーム3 (%)     | 50       | 50   | 100  | 0    | 50        | 100  | 50   | 100      | 100  | 100  | 100       | 100  | 100      |
| ブーム4 (%)     | 50       | 50   | 50   | 100  | 50        | 50   | 100  | 50       | 100  | 100  | 100       | 100  | 100      |
| ブーム5 (%)     | 0        | 50   | 50   | 100  | 50        | 50   | 100  | 50       | 50   | 100  | 50        | 100  | 100      |
| フック種類        | 200t     | 200t | 200t | 83t  | 200t      | 200t | 83t  | 200t     | 83t  | 83t  | 83t       | 83t  | 83t      |
| フック質量 (t)    | 2.60     | 2.60 | 2.60 | 1.35 | 2.60      | 2.60 | 1.35 | 2.60     | 1.35 | 1.35 | 1.35      | 1.35 | 1.35     |
| 掛数           | 12       | 12   | 10   | 7    | 10        | 10   | 7    | 10       | 7    | 7    | 7         | 7    | 6        |

(単位 : ton)